



# HBU407


NPN EPITAXIAL PLANAR TRANSISTOR

## Description

The HBU407 is designed for use in TV Horizontal output and Switching applications.

## Features

- High Breakdown Voltage



## Absolute Maximum Ratings (Ta=25°C)

- Maximum Temperatures  
Storage Temperature ..... -50 ~ +150 °C  
Junction Temperature ..... 150 °C Maximum
- Maximum Power Dissipation  
Total Power Dissipation (Tc=25°C) ..... 60 W
- Maximum Voltages and Currents (Ta=25°C)  
VCEO Collector to Emitter Voltage ..... 150 V  
VEBO Emitter to Base Voltage ..... 6 V  
IC Collector Current ..... 7 A  
IB Base Current ..... 4 A

## Characteristics (Ta=25°C)

Symbol	Min.	Typ.	Max.	Unit	Test Conditions
*BVCEO	150	-	-	V	IC=100mA, IB=0
ICES	-	-	5	mA	VCE=400V
IEBO	-	-	1	mA	VEB=6V, IC=0
*VCE(sat)	-	-	1	V	IC=5A, IB=0.5A
*VBE(sat)	-	-	1.2	V	IC=5A, IB=0.5A
*hFE1	25	-	-		IC=500mA, VCE=5V
*hFE2	35	-	200		IC=2A, VCE=5V
*hFE3	10	-	-		IC=5A, VCE=5V
FT	10	-	-	MHz	IC=500mA, VCE=10V, f=1MHz


\*Pulse Test : Pulse Width ≤380us, Duty Cycle≤2%

## Classification Of hFE2

Rank	B	C	D
Range	35-85	75-125	115-200



### TO-220AB Dimension



\*:Typical

DIM	Inches		Millimeters		DIM	Inches		Millimeters	
	Min.	Max.	Min.	Max.		Min.	Max.	Min.	Max.
A	0.2197	0.2949	5.58	7.49	I	-	*0.1508	-	*3.83
B	0.3299	0.3504	8.38	8.90	K	0.0295	0.0374	0.75	0.95
C	0.1732	0.185	4.40	4.70	M	0.0449	0.0551	1.14	1.40
D	0.0453	0.0547	1.15	1.39	N	-	*0.1000	-	*2.54
E	0.0138	0.0236	0.35	0.60	O	0.5000	0.5618	12.70	14.27
G	0.3803	0.4047	9.66	10.28	P	0.5701	0.6248	14.48	15.87
H	-	*0.6398	-	*16.25					

- Notes : 1.Dimension and tolerance based on our Spec. dated Sep. 07,1997.  
 2.Controlling dimension : millimeters.  
 3.Maximum lead thickness includes lead finish thickness, and minimum lead thickness is the minimum thickness of base material.  
 4.If there is any question with packing specification or packing method, please contact your local HSMC sales office.

**Material :**

- Lead : 42 Alloy ; solder plating
- Mold Compound : Epoxy resin family, flammability solid burning class:UL94V-0

**Important Notice:**

- All rights are reserved. Reproduction in whole or in part is prohibited without the prior written approval of HSMC.
- HSMC reserves the right to make changes to its products without notice.
- **HSMC semiconductor products are not warranted to be suitable for use in Life-Support Applications, or systems.**
- HSMC assumes no liability for any consequence of customer product design, infringement of patents, or application assistance.

**Head Office And Factory :**

- **Head Office** (Hi-Sincerity Microelectronics Corp.) : 10F.,No. 61, Sec. 2, Chung-Shan N. Rd. Taipei Taiwan R.O.C.  
 Tel : 886-2-25212056 Fax : 886-2-25632712, 25368454
- **Factory 1** : No. 38, Kuang Fu S. Rd., Fu-Kou Hsin-Chu Industrial Park Hsin-Chu Taiwan. R.O.C  
 Tel : 886-3-5983621~5 Fax : 886-3-5982931