



44 FARRAND STREET
BLOOMFIELD, NJ 07003
(973) 748-5089

NTE2956
MOSFET
N-Channel, Enhancement Mode
High Speed Switch

Applications:

- Servo Motor Drive
- Robot
- UPS
- Inverter
- Fluorescent Lamp

Absolute Maximum Ratings: ($T_C = +25^\circ\text{C}$ unless otherwise specified)

Drain–Source Voltage ($V_{GS} = 0\text{V}$), V_{DSS}	300V
Gate–Source Voltage ($V_{DS} = 0\text{V}$), V_{GS}	$\pm 30\text{V}$
Drain Current, I_D	
Continuous	14A
Pulsed	42A
Source Current, I_S	
Continuous	14A
Pulsed	42A
Maximum Power Dissipation, P_D	40W
Channel Temperature Range, T_{ch}	$-55^\circ\text{ to }+150^\circ\text{C}$
Storage Temperature Range, T_{stg}	$-55^\circ\text{ to }+150^\circ\text{C}$
Thermal Resistance, Channel-to-Case, $R_{th(ch-c)}$	3.13°C/W
Isolation Voltage, V_{ISO}	2000V

Electrical Characteristics: ($T_{ch} = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Drain–Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{DS} = 0\text{V}$, $I_D = 1\text{mA}$	500	—	—	V
Gate–Source Breakdown Voltage	$V_{(BR)GSS}$	$V_{DS} = 0\text{V}$, $I_G = \pm 100\mu\text{A}$	± 30	—	—	V
Gate–Source Leakage	I_{GSS}	$V_{GS} = \pm 25\text{V}$, $V_{DS} = 0\text{V}$	—	—	± 10	μA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS} = 500\text{V}$, $V_{GS} = 0$	—	—	1.0	mA
Gate Threshold Voltage	$V_{GS(th)}$	$V_{DS} = 10\text{V}$, $I_D = 1\text{mA}$	2.0	3.0	4.0	V
Static Drain–Source ON Resistance	$R_{DS(on)}$	$V_{GS} = 10\text{V}$, $I_D = 7\text{A}$	—	0.63	0.80	Ω
Drain–Source On–State Voltage	$V_{DS(on)}$	$V_{GS} = 10\text{V}$, $I_D = 7\text{A}$	—	4.41	5.60	V
Forward Transfer Admittance	$ y_{fs} $	$V_{GS} = 10\text{V}$, $I_D = 7\text{A}$	4.5	7.0	—	S

Electrical Characteristics (Cont'd): ($T_{ch} = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Input Capacitance	C_{iss}	$V_{GS} = 0\text{V}, V_{DS} = 25\text{V}, f = 1\text{MHz}$	—	1500	—	pF
Output Capacitance	C_{oss}		—	180	—	pF
Reverse Transfer Capacitance	C_{rss}		—	30	—	pF
Turn-On Delay Time	$t_{d(on)}$	$V_{DD} = 200\text{V}, I_D = 7\text{A}, V_{GS} = 10\text{V}, R_{GEN} = R_{GS} = 50\Omega$	—	30	—	ns
Rise Time	t_r		—	50	—	ns
Turn-Off Delay Time	$t_{d(off)}$		—	130	—	ns
Fall Time	t_f		—	50	—	ns
Diode Forward Voltage	V_{SD}	$I_S = 7\text{A}, V_{GS} = 0\text{V}$	—	1.5	2.0	V
Reverse Recovery Time	t_{rr}	$I_S = 15\text{A}, dI_F/dt = 100\text{A}/\mu\text{s}$	—	—	150	ns

