



## T-1 1/4 Subminiature Lamps

| Line No. | Part No. Wire Lead | Part No. Miniature Flanged | Part No. Bi-Pin | Volts | Amps  | M.S.C.P. | Filament Type | Life Hours |
|----------|--------------------|----------------------------|-----------------|-------|-------|----------|---------------|------------|
| 13       | 2135               | 7302                       | 7306            | 1.3   | 0.030 | 0.006    | S-2           | 100        |
| 14       | 8631               | 8636                       | 7636            | 1.35  | 0.060 | 0.006    | C-2R          | 500        |
| 15       | <b>8655</b>        | <b>8656</b>                | <b>7307</b>     | 2.5   | 0.400 | 0.55     | C-2R          | 30         |
| 16       | 324                | 8637                       | <b>7637</b>     | 3.0   | 0.190 | 0.25     | C-2R          | 350        |
| 17       | 8816               | 7305                       | <b>7308</b>     | 4.5   | 0.285 | 0.80     | C-2R          | 100        |
| 18       | 580                | 3582                       | 7580            | 5.0   | 0.060 | 0.03     | C-2R          | 100,000    |
| 19       | <b>583</b>         | 3585                       | <b>7583</b>     | 5.0   | 0.060 | 0.05     | C-2R          | 100,000    |
| 20       | <b>515</b>         | 3518                       | <b>7515</b>     | 5.0   | 0.115 | 0.15     | C-2R          | 40,000     |
| 21       | 8661               | 8660                       | <b>7660</b>     | 6.0   | 0.040 | 0.06     | C-2R          | 1,000      |
| 22       | 2114               | 8541                       | <b>7309</b>     | 6.0   | 0.060 | 0.13     | C-2R          | 3,000      |
| 23       | <b>634</b>         | <b>8628</b>                | <b>7628</b>     | 6.0   | 0.200 | 0.63     | C-2R          | 1,000      |
| 24       | <b>8610</b>        | 8551                       | <b>7310</b>     | 6.3   | 0.200 | 0.55     | C-2R          | 5,000      |
| 25       | 8608               | 8609                       | 7311            | 10.0  | 0.070 | 0.14     | C-2F          | 10,000     |
| 26       | <b>8640</b>        | 8646                       | <b>7646</b>     | 14.0  | 0.080 | 0.50     | C-2F          | 1,000      |
| 27       | <b>8627</b>        | 8632                       | <b>7632</b>     | 28.0  | 0.040 | 0.32     | C-2F          | 1,000      |

