


TOSHIBA POWER MOS FET MODULE SILICON N CHANNEL MOS TYPE (L²-π-MOS V 4 IN 1)

MP4210

HIGH POWER, HIGH SPEED SWITCHING APPLICATIONS
 FOR PRINTER HEAD PIN DRIVER AND PULSE MOTOR DRIVER
 FOR SOLENOID DRIVER

INDUSTRIAL APPLICATIONS
 Unit in mm

- 4 V Gate Drive Available
- Small Package by Full Molding (SIP 10 Pin)
- High Drain Power Dissipation (4 Devices Operation)
 : P_T = 4 W (T_a = 25°C)
- Low Drain-Source ON Resistance : R_{DS(ON)} = 0.12 Ω (typ.)
- High Forward Transfer Admittance : |Y_{fs}| = 5.0 S (typ.)
- Low Leakage Current : I_{GSS} = ±10 μA (max.) (V_{GS} = ±16 V)
 I_{DSS} = 100 μA (max.) (V_{DS} = 60 V)
- Enhancement-Mode : V_{th} = 0.8~2.0 V
 (V_{DS} = 10 V, I_D = 1 mA)




MAXIMUM RATINGS (T_a = 25°C)

CHARACTERISTIC	SYMBOL	RATING	UNIT
Drain-Source Voltage	V _{DSS}	60	V
Drain-Gate Voltage (R _{GS} = 20 kΩ)	V _{DGR}	60	V
Gate-Source Voltage	V _{GSS}	±20	V
Drain Current	DC	I _D	5
	Pulse	I _{DP}	20
Drain Power Dissipation (1 Device Operation, T _a = 25°C)	P _D	2.0	W
Drain Power Dissipation (4 Devices Operation, T _a = 25°C)	P _D T	4.0	W
Single Pulse Avalanche Energy*	E _{AS}	129	mJ
Avalanche Current	I _{AR}	5	A
Repetitive Avalanche Energy**	1 Device Operation	E _{AR}	0.2
	4 Devices Operation	E _{ART}	0.4
Channel Temperature	T _{ch}	150	°C
Storage Temperature Range	T _{stg}	-55~150	°C

Weight : 2.1 g (typ.)

ARRAY CONFIGURATION



Note ;

- * Avalanche energy (single pulse) applied condition
 V_{DD} = 25 V, Starting T_{ch} = 25°C, L = 7 mH, R_G = 25 Ω, I_{AR} = 5 A
- ** Repetitive rating ; Pulse Width Limited by maximum channel temperature.

This transistor is an electrostatic sensitive device. Please handle with caution.


961001EAA2

- TOSHIBA is continually working to improve the quality and the reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to observe standards of safety, and to avoid situations in which a malfunction or failure of a TOSHIBA product could cause loss of human life, bodily injury or damage to property. In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent products specifications. Also, please keep in mind the precautions and conditions set forth in the TOSHIBA Semiconductor Reliability Handbook.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA CORPORATION for any infringements of intellectual property or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any intellectual property or other rights of TOSHIBA CORPORATION or others.
- The information contained herein is subject to change without notice.

THERMAL CHARACTERISTICS

CHARACTERISTIC	SYMBOL	MAX.	UNIT
Thermal Resistance of Channel to Ambient (4 Devices Operation, Ta = 25°C)	$\Sigma R_{th(ch-a)}$	31.2	°C / W
Maximum Lead Temperature for Soldering Purposes (3.2 mm from Case for t = 10 s)	T _L	260	°C

MARKING















ELECTRICAL CHARACTERISTICS (Ta = 25°C)






CHARACTERISTIC		SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Gate Leakage Current		I _{GSS}	V _{GS} = ±16 V, V _{DS} = 0 V	—	—	±10	μA
Drain Cut-off Current		I _{DSS}	V _{DS} = 60 V, V _{GS} = 0 V	—	—	100	μA
Drain-Source Breakdown Voltage		V(BR)DSS	I _D = 10 mA, V _{GS} = 0 V	60	—	—	V
Gate Threshold Voltage		V _{th}	V _{DS} = 10 V, I _D = 1 mA	0.8	—	2.0	V
Drain-Source ON Resistance		R _{DSON}	V _{GS} = 4 V, I _D = 2.5 A V _{GS} = 10 V, I _D = 2.5 A	—	0.21 0.12	0.32 0.16	Ω
Forward Transfer Admittance		Y _{fs}	V _{DS} = 10 V, I _D = 2.5 A	3.0	5.0	—	S
Input Capacitance		C _{iss}	V _{DS} = 10 V, V _{GS} = 0 V f = 1 MHz	—	370	—	pF
Reverse Transfer Capacitance		C _{rss}		—	60	—	
Output Capacitance		C _{oss}		—	180	—	
Switching Time	Rise Time	t _r		—	18	—	ns
	Turn-on Time	t _{on}		—	25	—	
	Fall Time	t _f		—	55	—	
	Turn-off Time	t _{off}		—	170	—	
Total Gate Charge (Gate-Source Plus Gate-Drain)		Q _g	V _{DD} = 48 V, V _{GS} = 10 V I _D = 5 A	—	12	—	nC
Gate-Source Charge		Q _{gs}		—	8	—	
Gate-Drain ("Miller") Charge		Q _{gd}		—	4	—	

SOURCE-DRAIN DIODE RATINGS AND CHARACTERISTICS (Ta = 25°C)

CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Continuous Drain Reverse Current	I _{DR}	—	—	—	5	A
Pulse Drain Reverse Current	I _{DRP}	—	—	—	20	A
Diode Forward Voltage	V _{DSF}	I _{DR} = 5 A, V _{GS} = 0 V	—	—	-1.7	V
Reverse Recovery Time	t _{rr}	I _{DR} = 5 A, V _{GS} = 0 V	—	70	—	ns
Reverse Recovery Charge	Q _{rr}	dI _{DR} / dt = 50 A / μs	—	0.1	—	μC







Peak $I_{AR} = 5 \text{ A}$, $R_G = 25 \Omega$
 $V_{DD} = 25 \text{ V}$, $L = 7 \text{ mH}$

$$E_{AS} = \frac{1}{2} \cdot L \cdot I^2 \cdot \left(\frac{BVDSS}{BVDSS - V_{DD}} \right)$$