




## AO6604, AO6604L ( Green Product ) Complementary Enhancement Mode Field Effect Transistor

General Description	Features	
The AO6604 uses advanced trench technology to provide excellent $R_{DS(ON)}$ and low gate charge. The complementary MOSFETs form a high-speed power inverter, suitable for a multitude of applications. AO6604L( Green Product ) is offered in a lead-free package.	n-channel	p-channel
	$V_{DS} (V) = 20V$	-20V
	$I_D = 3.4A$	-2.5A
	$R_{DS(ON)}$	
	< 60mΩ	< 110mΩ ( $V_{GS} = 4.5V$ )
	< 75mΩ	< 140mΩ ( $V_{GS} = 2.5V$ )
	< 100mΩ	< 200mΩ ( $V_{GS} = 1.8V$ )



Absolute Maximum Ratings $T_A=25^\circ C$ unless otherwise noted				
Parameter	Symbol	Max n-channel	Max p-channel	Units
Drain-Source Voltage	$V_{DS}$	20	-20	V
Gate-Source Voltage	$V_{GS}$	$\pm 8$	$\pm 8$	V
Continuous Drain Current <sup>A</sup>	$I_D$	3.4	-2.5	A
$T_A=70^\circ C$		2.7	-2.0	
Pulsed Drain Current <sup>B</sup>	$I_{DM}$	15	-15	
Power Dissipation	$P_D$	1.15	1.15	W
$T_A=70^\circ C$		0.73	0.73	
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	-55 to 150	°C

Thermal Characteristics: n-channel and p-channel				
Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient <sup>A</sup>	$R_{\theta JA}$	78	110	°C/W
Maximum Junction-to-Ambient <sup>A</sup>		106	150	°C/W
Maximum Junction-to-Lead <sup>C</sup>	$R_{\theta JL}$	64	80	°C/W

**N-channel MOSFET Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$	20			V
$I_{\text{DSS}}$	Zero Gate Voltage Drain Current	$V_{DS}=16\text{V}, V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$			1 5	$\mu\text{A}$
$I_{\text{GSS}}$	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}=\pm 8\text{V}$			100	nA
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	0.4	0.6	1	V
$I_{\text{D(ON)}}$	On state drain current	$V_{GS}=4.5\text{V}, V_{DS}=5\text{V}$	15			A
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{GS}=4.5\text{V}, I_D=3.4\text{A}$ $T_J=125^\circ\text{C}$		46 63	60 80	$\text{m}\Omega$
		$V_{GS}=2.5\text{V}, I_D=3\text{A}$		57	75	$\text{m}\Omega$
		$V_{GS}=1.8\text{V}, I_D=2\text{A}$		72	100	$\text{m}\Omega$
$g_{\text{FS}}$	Forward Transconductance	$V_{DS}=5\text{V}, I_D=3.4\text{A}$		10		S
$V_{\text{SD}}$	Diode Forward Voltage	$I_S=1\text{A}, V_{GS}=0\text{V}$		0.76	1	V
$I_S$	Maximum Body-Diode Continuous Current				2	A
<b>DYNAMIC PARAMETERS</b>						
$C_{\text{iss}}$	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=10\text{V}, f=1\text{MHz}$		436	570	pF
$C_{\text{oss}}$	Output Capacitance			66		pF
$C_{\text{rss}}$	Reverse Transfer Capacitance			44		pF
$R_g$	Gate resistance	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$		3	4	$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g$	Total Gate Charge	$V_{GS}=4.5\text{V}, V_{DS}=10\text{V}, I_D=3.4\text{A}$		6.2	8.1	nC
$Q_{\text{gs}}$	Gate Source Charge			1.6		nC
$Q_{\text{gd}}$	Gate Drain Charge			0.5		nC
$t_{\text{D(on)}}$	Turn-On Delay Time	$V_{GS}=5\text{V}, V_{DS}=10\text{V}, R_L=3\Omega, R_{\text{GEN}}=3\Omega$		5.5		ns
$t_r$	Turn-On Rise Time			6.3		ns
$t_{\text{D(off)}}$	Turn-Off Delay Time			40		ns
$t_f$	Turn-Off Fall Time			12.7		ns
$t_{\text{rr}}$	Body Diode Reverse Recovery Time	$I_F=3.4\text{A}, dI/dt=100\text{A}/\mu\text{s}$		12.3	16	ns
$Q_{\text{rr}}$	Body Diode Reverse Recovery Charge	$I_F=3.4\text{A}, dI/dt=100\text{A}/\mu\text{s}$		3.5		nC

A: The value of  $R_{\text{0JA}}$  is measured with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The value in any given application depends on the user's specific board design. The current rating is based on the  $\leq 10\text{s}$  thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The  $R_{\text{0JA}}$  is the sum of the thermal impedance from junction to lead  $R_{\text{0UL}}$  and lead to ambient.

D. The static characteristics in Figures 1 to 6 are obtained using 80 $\mu\text{s}$  pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The SOA curve provides a single pulse rating.

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

### N-CHANNEL TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

### N-CHANNEL TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Figure 7: Gate-Charge Characteristics




Figure 8: Capacitance Characteristics




Figure 9: Maximum Forward Biased Safe Operating Area (Note E)




Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note E)




Figure 11: Normalized Maximum Transient Thermal Impedance

**P-channel MOSFET Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$\text{BV}_{\text{DSS}}$	Drain-Source Breakdown Voltage	$I_D=-250\mu\text{A}, V_{GS}=0\text{V}$	-20			V
$I_{\text{DSS}}$	Zero Gate Voltage Drain Current	$V_{DS}=-16\text{V}, V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$			-1 -5	$\mu\text{A}$
$I_{\text{GSS}}$	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}=\pm 8\text{V}$			$\pm 100$	nA
$V_{\text{GS(th)}}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=-250\mu\text{A}$	-0.3	-0.55	-1	V
$I_{\text{D(ON)}}$	On state drain current	$V_{GS}=-4.5\text{V}, V_{DS}=-5\text{V}$	-15			A
$R_{\text{DS(ON)}}$	Static Drain-Source On-Resistance	$V_{GS}=-4.5\text{V}, I_D=2.5\text{A}$ $T_J=125^\circ\text{C}$		86	110	$\text{m}\Omega$
		$V_{GS}=-2.5\text{V}, I_D=2\text{A}$		116	145	$\text{m}\Omega$
		$V_{GS}=-1.8\text{V}, I_D=1\text{A}$		113	140	$\text{m}\Omega$
$g_{\text{FS}}$	Forward Transconductance	$V_{DS}=-5\text{V}, I_D=3\text{A}$	4	6		S
$V_{\text{SD}}$	Diode Forward Voltage	$I_S=-1\text{A}, V_{GS}=0\text{V}$		-0.78	-1	V
$I_S$	Maximum Body-Diode Continuous Current				-2	A
<b>DYNAMIC PARAMETERS</b>						
$C_{\text{iss}}$	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=-10\text{V}, f=1\text{MHz}$		540	700	pF
$C_{\text{oss}}$	Output Capacitance			72		pF
$C_{\text{rss}}$	Reverse Transfer Capacitance			49		pF
$R_g$	Gate resistance	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$		12	15.6	$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g$	Total Gate Charge	$V_{GS}=-4.5\text{V}, V_{DS}=-10\text{V}, I_D=-2.5\text{A}$		6.1	8	nC
$Q_{\text{gs}}$	Gate Source Charge			0.6		nC
$Q_{\text{gd}}$	Gate Drain Charge			1.6		nC
$t_{\text{D(on)}}$	Turn-On Delay Time	$V_{GS}=-4.5\text{V}, V_{DS}=-10\text{V}, R_L=3.9\Omega, R_{\text{GEN}}=3\Omega$		10		ns
$t_r$	Turn-On Rise Time			12		ns
$t_{\text{D(off)}}$	Turn-Off Delay Time			44		ns
$t_f$	Turn-Off Fall Time			22		ns
$t_{\text{rr}}$	Body Diode Reverse Recovery Time	$I_F=-2.5\text{A}, dI/dt=100\text{A}/\mu\text{s}$		21	28	ns
$Q_{\text{rr}}$	Body Diode Reverse Recovery Charge	$I_F=-2.5\text{A}, dI/dt=100\text{A}/\mu\text{s}$		7.5		nC

A: The value of  $R_{\theta JA}$  is measured with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The value in any given application depends on the user's specific board design. The current rating is based on the  $t \leq 10\text{s}$  thermal resistance rating.

B: Repetitive rating, pulse width limited by junction temperature.

C. The  $R_{\theta JA}$  is the sum of the thermal impedance from junction to lead  $R_{\theta JL}$  and lead to ambient.

D. The static characteristics in Figures 1 to 6, 12, 14 are obtained using 80  $\mu\text{s}$  pulses, duty cycle 0.5% max.

E. These tests are performed with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The SOA curve provides a single pulse rating.

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

### P-CHANNEL TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS




Fig 1: On-Region Characteristics




Figure 2: Transfer Characteristics




Figure 3: On-Resistance vs. Drain Current and Gate Voltage




Figure 4: On-Resistance vs. Junction Temperature




Figure 5: On-Resistance vs. Gate-Source Voltage




Figure 6: Body-Diode Characteristics

### P-CHANNEL TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS

