


## T-1 1/4 Subminiature Lamps

Line No.	Part No. Wire Lead	Part No. Miniature Flanged	Part No. Bi-Pin	Volts	Amps	M.S.C.P.	Filament Type	Life Hours
13	2135	7302	7306	1.3	0.030	0.006	S-2	100
14	8631	8636	7636	1.35	0.060	0.006	C-2R	500
15	<b>8655</b>	<b>8656</b>	<b>7307</b>	2.5	0.400	0.55	C-2R	30
16	324	8637	<b>7637</b>	3.0	0.190	0.25	C-2R	350
17	8816	7305	<b>7308</b>	4.5	0.285	0.80	C-2R	100
18	580	3582	7580	5.0	0.060	0.03	C-2R	100,000
19	<b>583</b>	3585	<b>7583</b>	5.0	0.060	0.05	C-2R	100,000
20	<b>515</b>	3518	<b>7515</b>	5.0	0.115	0.15	C-2R	40,000
21	8661	8660	<b>7660</b>	6.0	0.040	0.06	C-2R	1,000
22	2114	8541	<b>7309</b>	6.0	0.060	0.13	C-2R	3,000
23	<b>634</b>	<b>8628</b>	<b>7628</b>	6.0	0.200	0.63	C-2R	1,000
24	<b>8610</b>	8551	<b>7310</b>	6.3	0.200	0.55	C-2R	5,000
25	8608	8609	7311	10.0	0.070	0.14	C-2F	10,000
26	<b>8640</b>	8646	<b>7646</b>	14.0	0.080	0.50	C-2F	1,000
27	<b>8627</b>	8632	<b>7632</b>	28.0	0.040	0.32	C-2F	1,000



This datasheet has been download from:

[www.datasheetcatalog.com](http://www.datasheetcatalog.com)

Datasheets for electronics components.