



4A002MH5

2-Input NOR Gate

Features

- 2-input NOR gate.
- Enable to 25 voltage operation.
- Low power-loss.
- High speed operation.

Truth Table

INA	INB	OUT
L	L	H
L	H	L
H	L	L
H	H	L

H : High level voltage

L : Low level voltage

Specifications

Absolute Maximum Ratings at Ta=25°C

Parameter	Symbol	Conditions	Ratings	Unit
DC Supply Voltage	V _{DD}		-0.3 to +25	V
Input Voltage	V _{IN}		GND-0.3 to V _{DD} +0.3	V
Output Voltage	V _{OUT}		GND-0.3 to V _{DD} +0.3	V
Input Current	I _{IN}		±10	mA
Output Current	I _{OUT}		±75	mA
Allowable Power Dissipation	P _D	Mounted on a ceramic board (600mm ² X0.8mm)	0.8	W
Storage Temperature	T _{stg}		-55 to +150	°C

Recommended Operating Conditions at Ta=25°C


Parameter	Symbol	Conditions	Ratings	Unit
DC Supply Voltage	V _{DD}		3 to +25	V
Input Voltage	V _{IN}		0 to V _{DD}	V
Output Voltage	V _{OUT}		0 to V _{DD}	V
Output Current	I _{OUT}	V _{DD} =25V	±50	mA
Input Rise And Fall Time	Δt / Δv	V _{DD} <5V	≤100	ns / V
		V _{DD} ≥5V	20	ns / V
Operating Temperature	T _{opr}		-40 to +85	°C

Marking : XB

Package Dimensions

unit : mm

2216



■ Any and all SANYO products described or contained herein do not have specifications that can handle applications that require extremely high levels of reliability, such as life-support systems, aircraft's control systems, or other applications whose failure can be reasonably expected to result in serious physical and/or material damage. Consult with your SANYO representative nearest you before using any SANYO products described or contained herein in such applications.

■ SANYO assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all SANYO products described or contained herein.

4A002MH5


DC Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
High-level Input Voltage	V _{IH}	V _{DD} =5V	3.5			V
		V _{DD} =10V	7.0			V
		V _{DD} =15V	11.0			V
		V _{DD} =25V	18.0			V
Low-level Input Voltage	V _{IL}	V _{DD} =5V			1.5	V
		V _{DD} =10V			3.0	V
		V _{DD} =15V			4.0	V
		V _{DD} =25V			7.0	V
Input Leakage Current	I _{IN}	V _{DD} =25V, V _{IN} =25V			0.1	μA
		V _{DD} =25V, V _{IN} =0			0.1	μA
High-level Output Voltage	V _{OH}	V _{DD} =5V, I _O =1mA	4.5			V
		V _{DD} =10V, I _O =2.5mA	9.0			V
		V _{DD} =15V, I _O =5.0mA	13.5			V
		V _{DD} =25V, I _O =10mA	22.5			V
Low-level Output Voltage	V _{OL}	V _{DD} =5V, I _O =1mA			0.5	V
		V _{DD} =10V, I _O =2.5mA			1.0	V
		V _{DD} =15V, I _O =5.0mA			1.5	V
		V _{DD} =25V, I _O =10mA			2.5	V
Supply Current	I _{DD}	V _{DD} =5V, V _{IN} =V _{DD} , GND			0.25	μA
		V _{DD} =10V, V _{IN} =V _{DD} , GND			0.5	μA
		V _{DD} =15V, V _{IN} =V _{DD} , GND			1.0	μA
		V _{DD} =25V, V _{IN} =V _{DD} , GND			2.0	μA


AC Characteristics at Ta=25°C

Parameter	Symbol	Conditions	Ratings			Unit
			min	typ	max	
Output Transition Time	t _{TLH}	V _{DD} =5V		14		ns
		V _{DD} =10V		8		ns
		V _{DD} =15V		7		ns
		V _{DD} =25V		6		ns
	t _{THL}	V _{DD} =5V		14		ns
		V _{DD} =10V		8		ns
		V _{DD} =15V		7		ns
		V _{DD} =25V		6		ns
Propagation Delay Time	t _{PLH}	V _{DD} =5V		40		ns
		V _{DD} =10V		20		ns
		V _{DD} =15V		15		ns
		V _{DD} =25V		12		ns
	t _{PHL}	V _{DD} =5V		40		ns
		V _{DD} =10V		20		ns
		V _{DD} =15V		15		ns
		V _{DD} =25V		12		ns
Input Capacitance	C _{IN}			8	pF	








Block Diagram











Switching Time Test Circuit






Switching Time Wave Form



4A002MH5



4A002MH5



- Specifications of any and all SANYO products described or contained herein stipulate the performance, characteristics, and functions of the described products in the independent state, and are not guarantees of the performance, characteristics, and functions of the described products as mounted in the customer's products or equipment. To verify symptoms and states that cannot be evaluated in an independent device, the customer should always evaluate and test devices mounted in the customer's products or equipment.
- SANYO Electric Co., Ltd. strives to supply high-quality high-reliability products. However, any and all semiconductor products fail with some probability. It is possible that these probabilistic failures could give rise to accidents or events that could endanger human lives, that could give rise to smoke or fire, or that could cause damage to other property. When designing equipment, adopt safety measures so that these kinds of accidents or events cannot occur. Such measures include but are not limited to protective circuits and error prevention circuits for safe design, redundant design, and structural design.
- In the event that any or all SANYO products(including technical data, services) described or contained herein are controlled under any of applicable local export control laws and regulations, such products must not be exported without obtaining the export license from the authorities concerned in accordance with the above law.
- No part of this publication may be reproduced or transmitted in any form or by any means, electronic or mechanical, including photocopying and recording, or any information storage or retrieval system, or otherwise, without the prior written permission of SANYO Electric Co., Ltd.
- Any and all information described or contained herein are subject to change without notice due to product/technology improvement, etc. When designing equipment, refer to the "Delivery Specification" for the SANYO product that you intend to use.
- Information (including circuit diagrams and circuit parameters) herein is for example only ; it is not guaranteed for volume production. SANYO believes information herein is accurate and reliable, but no guarantees are made or implied regarding its use or any infringements of intellectual property rights or other rights of third parties.

This catalog provides information as of December, 2003. Specifications and information herein are subject to change without notice.