

Square Type

3.0 mm × 7.0 mm Series

Conventional Part No.	Global Part No.	Lighting Color
LN216RPH	LNG216RFR	Red
LN316GPH	LNG316GFG	Green
LN416YPH	LNG416YFX	Amber
LN816RPH	LNG816RFD	Orange

■ Absolute Maximum Ratings ($T_a = 25^\circ\text{C}$)

Lighting Color	P_D (mW)	I_F (mA)	I_{FP} (mA)*	V_R (V)	T_{opr} ($^\circ\text{C}$)	T_{stg} ($^\circ\text{C}$)
Red	70	25	150	4	-25 ~ +85	-30 ~ +100
Green	90	30	150	4	-25 ~ +85	-30 ~ +100
Amber	90	30	150	4	-25 ~ +85	-30 ~ +100
Orange	90	30	150	3	-25 ~ +85	-30 ~ +100

* I_{FP} の条件は $\text{duty } 10\%$ $\text{Pulse width } 1 \text{ msec}$. The condition of I_{FP} is $\text{duty } 10\%$, $\text{Pulse width } 1 \text{ msec}$

■ Electro-Optical Characteristics ($T_a = 25^\circ\text{C}$)

Conventional Part No.	Lighting Color	Lens Color	I_O		I_F	V_F		λ_P	$\Delta\lambda$	I_F	I_R	
			Typ	Min		Typ	Max				Typ	Max
LN216RPH	Red	Red Diffused	0.5	0.2	15	2.2	2.8	700	20	20	5	4
LN316GPH	Green	Green Diffused	1.5	0.6	20	2.2	2.8	565	30	20	10	4
LN416YPH	Amber	Amber Diffused	1.5	0.6	20	2.2	2.8	590	30	20	10	4
LN816RPH	Orange	Red Diffused	2.5	1.0	20	2.1	2.8	630	40	20	10	3
Unit	—	—	mcd	mcd	mA	V	V	nm	nm	mA	μA	V

