


**N-CHANNEL ENHANCEMENT MODE FIELD EFFECT TRANSISTOR**

**Features**

- Low On-Resistance
- Low Gate Threshold Voltage
- Low Input Capacitance
- Fast Switching Speed
- Low Input/Output Leakage
- Lead Free/RoHS Compliant (Note 2)**

**Mechanical Data**

- Case: SOT-23
- Case Material: Molded Plastic. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020C
- Terminal Connections: See Diagram
- Terminals: Solderable per MIL-STD-202, Method 208
- Lead Free Plating (Matte Tin Finish annealed over Alloy 42 leadframe).
- Marking (See Page 2): K70
- Ordering & Date Code Information: See Page 2
- Weight: 0.008 grams (approximate)



SOT-23		
Dim	Min	Max
A	0.37	0.51
B	1.20	1.40
C	2.30	2.50
D	0.89	1.03
E	0.45	0.60
G	1.78	2.05
H	2.80	3.00
J	0.013	0.10
K	0.903	1.10
L	0.45	0.61
M	0.085	0.180
	0	8
All Dimensions in mm		

**Maximum Ratings** @ T<sub>A</sub> = 25 C unless otherwise specified

Characteristic	Symbol	BS870	Units
Drain-Source Voltage	V <sub>DSS</sub>	60	V
Drain-Gate Voltage R <sub>GS</sub> 1.0M	V <sub>DGR</sub>	60	V
Gate-Source Voltage	V <sub>GSS</sub>	20	V
Drain Current (Note 1)	I <sub>D</sub>	250	mA
Total Power Dissipation (Note 1)	P <sub>d</sub>	300	mW
Thermal Resistance, Junction to Ambient	R <sub>JA</sub>	417	K/W
Operating and Storage Temperature Range	T <sub>j</sub> , T <sub>STG</sub>	-55 to +150	C

- Note: 1. Device mounted on FR-5 PCB 1.0 x 0.75 x 0.062 inch pad layout as shown on Diodes, Inc. suggested pad layout AP02001, which can be found on our website at <http://www.diodes.com/datasheets/ap02001.pdf>.  
2. No purposefully added lead.

## Electrical Characteristics @ T<sub>A</sub> = 25 C unless otherwise specified


Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
<b>OFF CHARACTERISTICS (Note 3)</b>						
Drain-Source Breakdown Voltage	BV <sub>DSS</sub>	60	80		V	V <sub>GS</sub> = 0V, I <sub>D</sub> = 100 A
Zero Gate Voltage Drain Current	I <sub>DSS</sub>			0.5	μA	V <sub>DS</sub> = 25V, V <sub>GS</sub> = 0V
Gate-Body Leakage	I <sub>GSS</sub>			10	nA	V <sub>GS</sub> = 15V, V <sub>DS</sub> = 0V
<b>ON CHARACTERISTICS (Note 3)</b>						
Gate Threshold Voltage	V <sub>GS(th)</sub>	1.0	2.0	3.0	V	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = 250 A
Static Drain-Source On-Resistance	R <sub>DS(ON)</sub>		3.5	5.0		V <sub>GS</sub> = 10V, I <sub>D</sub> = 0.2A
On-State Drain Current	I <sub>D(ON)</sub>		1.0	0.5	A	V <sub>GS</sub> = 10V, V <sub>DS</sub> = 7.5V
Forward Transconductance	g <sub>FS</sub>	80			mS	V <sub>DS</sub> = 10V, I <sub>D</sub> = 0.2A
<b>DYNAMIC CHARACTERISTICS</b>						
Input Capacitance	C <sub>iss</sub>		22	50	pF	V <sub>DS</sub> = 10V, V <sub>GS</sub> = 0V f = 1.0MHz
Output Capacitance	C <sub>oss</sub>		11	25	pF	
Reverse Transfer Capacitance	C <sub>rss</sub>		2.0	5.0	pF	
<b>SWITCHING CHARACTERISTICS</b>						
Turn-On Delay Time	t <sub>D(ON)</sub>		2.0	20	ns	V <sub>ES</sub> = 10V, R <sub>L</sub> = 150 Ω , V <sub>DS</sub> = 10V, R <sub>D</sub> = 100 Ω
Turn-Off Delay Time	t <sub>D(OFF)</sub>		5.0	20	ns	

## Ordering Information (Note 4)

Device	Packaging	Shipping
BS870-7-F	SOT-23	3000/Tape & Reel

- Notes: 3. Short duration test pulse used to minimize self-heating effect.  
4. For Packaging Details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.


## Marking Information




K70 = Product Type Marking Code  
YM = Date Code Marking  
Y = Year ex: N = 2002  
M = Month ex: 9 = September

### Date Code Key


<b>Year</b>	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009
<b>Code</b>	J	K	L	M	N	P	R	S	T	U	V	W
<b>Month</b>	Jan	Feb	March	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
<b>Code</b>	1	2	3	4	5	6	7	8	9	O	N	D




$V_{DS}$ , DRAIN-SOURCE VOLTAGE (V)  
Fig. 1 On-Region Characteristics




$I_D$ , DRAIN CURRENT (A)  
Fig. 2 On-Resistance vs Drain Current



$T_J$ , JUNCTION TEMPERATURE ( $^\circ\text{C}$ )  
Fig. 3 On-Resistance vs Junction Temperature



$V_{GS}$ , GATE TO SOURCE VOLTAGE (V)  
Fig. 4 On-Resistance vs. Gate-Source Voltage



$T_A$ , AMBIENT TEMPERATURE ( $^\circ\text{C}$ )  
Fig. 5, Max Power Dissipation vs Ambient Temperature

**IMPORTANT NOTICE**

Diodes, Inc. and its subsidiaries reserve the right to make changes without further notice to any product herein to make corrections, modifications, enhancements, improvements, or other changes. Diodes, Inc. does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

**LIFE SUPPORT**

The products located on our website at [www.diodes.com](http://www.diodes.com) are not recommended for use in life support systems where a failure or malfunction of the component may directly threaten life or cause injury without the expressed written approval of Diodes Incorporated.