

2.4W LMT2608 50.0:1 Transformer
DESCRIPTION


This document describes and specifies the electrical and mechanical characteristics of the SGE2671-1G high voltage transformer for CCFL inverter power supplies. SGE2671-1G is the RoHS compliant and Lead free transformer. For Reliability and Safety Specification, refer to SGE2606-4.

ELECTRICAL CHARACTERISTICS

Items	Inductance (@ 10Khz, 0.1V)			Items	DC. Resistance		
	Min	Nom	Max		Min	Nom	Max
L1-2, L2-3 (μH)	39	47.8	56	R _{DC} 1-2, R _{DC} 2-3(mΩ)	138	145	153
L4-5 (mH)	367	441.4	515	R _{DC} 4-5 (Ω)	470	496	510
L _{LKG1-2} , L _{LKG2-3} (μH)	Inductance (@ 100KHz, 1V)			R _{DC} 1-2 / R _{DC} 2-3	0.96	1	1.04
	47	48.5	51				
L _{LKG4-5} (mH)	NA	NA	NA	Secondary Self Capacitance (HP4192A 1MHz C meter, 30mVrms)			
				C _{4.5} (pF)	1.9	2.2	3
Rating				Dielectric Voltage Withstand			
Note: Max output power varies depend on operating condition.				60Hz, Arc-detect enabled, 5 sec. min. 200μA max. leakage current			
Max Open Output Voltage	1200V _{RMS} , 3sec.			Secondary to Core	1500V _{RMS} min. (60sec)		
Max Output Voltage	850V _{RMS}			Primary to Core	750V _{RMS} min.		
Max Output Power	2.4W			Primary to Secondary	750V _{RMS} min.		

WINDING SPECIFICATIONS

	Primary		Secondary
	Pin 1 – 2	Pin 2 – 3	Pin 4 – 5
Winding Sequence	1S – 2F	2S – 3F	4S – 5F
Wire Size & Type	0.18φ, Single Insulation, 180°C	0.18φ, Single Insulation, 180°C	0.03φ, Triple Insulation, 180°C
Number of Turns	16	16	1600
Winding Method	Bifilar		

PHYSICAL SPECIFICATIONS & WIRING DIAGRAM


Note : This transformer is design for single ended application. Pin 5 must to be connected to low voltage side or ground.

PART MARKING

SGE□□□□-□G XYZD A – SGE2671-1G: MSC PN, XYZ: Datecode (X:YR, YZ=WK), D: Plant Code, A: Rev.#

PACKAGING SPEC AND ORDER INFORMATION

Packaging Order Information – SGE2671-1GTR (Tape and Reel)

TAPE & REEL : Refer to SGE2604-4 specification



Microsemi[®]

Specification Number
SGE2671-1G
Revision. A (090605)

2.4W LMT2608 50.0:1 Transformer

NOTES

PRODUCTION DATA – Information contained in this document is proprietary to Microsemi and is current as of publication date. This document may not be modified in any way without the express written consent of Microsemi. Product processing does not necessarily include testing of all parameters. Microsemi reserves the right to change the configuration and performance of the product and to discontinue product at any time.