

VI TELEFILTER**Filter Specification****TFS 70H11****1/5****1. Measurement condition :**

Ambient temperature T_A : 25 °C.
 Input power level: 0 dBm.
 Terminating impedances in f_C :
 for input: 50 Ω | 0 pF.
 for output: 50 Ω | 0 pF.

2. Characteristics :

Remark:

Reference level for the relative attenuation a_{rel} of the **TFS 70H11** is the minimum of the pass band attenuation a_{min} . The minimum of the pass band attenuation a_{min} is defined as the insertion loss a_e . The reference frequency f_C is the arithmetic mean value of the upper and lower frequencies at the 20 dB filter attenuation level relative to the insertion loss a_e . The temperature coefficient of frequency T_C is valid both for the reference frequency f_C and the frequency response of the filter in the operating temperature range. The frequency shift of the filter in the operating temperature range is not included in the production tolerance scheme.

Data		typ. value	tolerance / limit
Insertion loss (Reference level)	a_e	21,5 dB	max. 23 dB
Centre frequency at ambient temperature (f_{CTA})	f_C	70,0 MHz	70,0 \pm 0,1 MHz
Pass band :	PB		f_C \pm 3,5 MHz
Amplitude ripple in $f_C \pm 3$ MHz:		0,5 dB	
Bandwidth at ambient temperature T_A :	BW		
1 dB		6,7 MHz	min. 6,5 MHz
3 dB		7,1 MHz	min. 7,0 MHz
10 dB		8,7 MHz	
20 dB		9,1 MHz	
40 dB		9,2 MHz	max. 9,7 MHz
Relative attenuation	a_{rel}		
f_C $f_C \pm 3,25$ MHz	-	max. 1 dB
$f_C \pm 3,25$ MHz $f_C \pm 3,5$ MHz	-	max. 3 dB
$f_C \pm 4,85$ MHz $f_C \pm 15$ MHz	47 dB	min. 40 dB
$f_C \pm 15$ MHz $f_C \pm 60$ MHz	55 dB	min. 50 dB
Group delay (mean value in PB):		1,85 μ s	
Group delay ripple in PB (p-p):		45 ns	max. 100 ns
Deviation from linear phase in PB :		3°	max. 4°
Triple transit attenuation compared to main signal Crosstalk		50 dB	
		65 dB	
Temperature coefficient of frequency (T_C):		-87 ppm/K ²	
Frequency deviation of f_C over temperature :		$\Delta f_C(\text{Hz}) = T_C(\text{ppm/K}) \times (T - T_0) \times f_{CTA} (\text{MHz})$	
Operating temperature range		- 25 °C ... + 80 °C	
Storage temperature range		- 40 °C ... + 85 °C	

Generated:

E.Chilla

Checked/Approved:

B. Wall

VI TELEFILTER

Potsdamer Straße 18

D 14 513 TELTOW / Germany



Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30

E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information


3. Construction and pin connection :

(All dimensions in mm)




Date-code: Year+week
 M 2000
 N 2001
 P 2002

Date-code



Pin 14 **Input**
 Pin 1 Input RF Return
 Pin 8 **Output**
 Pin 7 Output RF Return
 Pin 2, 9 Package Ground

4. 50 Ω matching network :



VI TELEFILTER
 Potsdamer Straße 18
 D 14 513 TELTOW / Germany
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30
 E-Mail: tft@telefilter.com

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information

5. Stability characteristics :

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 18 ms, half sine wave, 3 shocks each plane;
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5g respectively, 1 octave per min, 10 cycles per plan, 3 plans;
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: twice max. ;
for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;

6. Air reflow temperature conditions :

1st and 2nd air reflow profile

Name:	pre-heating periods	main-heating periods	peak temperature
Temperature:	150 °C - 170 °C	over 200 °C	255 °C ± 5 °C
Time:	60 sec. - 90 sec.	20 sec. - 25 sec.	

Air reflow profile




Table for temperature vs. time during the air reflow process

Tolerance of temperatures: ± 5 °C

time / sec.	temperature / °C	time / sec.	temperature / °C
0	23	140	160
10	34	150	161
20	46	160	164
30	60	170	170
40	80	180	180
50	103	190	205
60	121	195	230
70	134	200	255
80	143	205	230
90	150	210	205
100	154	215	180
110	156	220	165
120	158	230	140
130	159	240	120

VI TELEFILTER**Filter Specification****TFS 70H11****5/5****History**

Version	Reason of changes	Name	Date
1.0	Generate preliminary specification .	Chilla	23.05.2002
1.1	Generate filter specification . add typical filter values;	Chilla	14.08.2002
1.2	change level for insertion loss.	Chilla	19.11.2002

VI TELEFILTER**Potsdamer Straße 18****D 14 513 TELTOW / Germany****Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30****E-Mail: tft@telefilter.com**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information