

# 2MBI200NB-120-01

IGBT Module

## 1200V / 200A 2 in one-package

### ■ Features

- VCE(sat) classified for easy parallel connection
- High speed switching
- Voltage drive
- Low inductance module structure

### ■ Applications

- Inverter for Motor drive
- AC and DC Servo drive amplifier
- Uninterruptible power supply
- Industrial machines, such as Welding machines



### ■ Maximum ratings and characteristics

#### ● Absolute maximum ratings (at Tc=25°C unless otherwise specified)

Item	Symbol	Rating	Unit
Collector-Emitter voltage	V <sub>CES</sub>	1200	V
Gate-Emitter voltage	V <sub>GES</sub>	±20	V
Collector current	Continuous	I <sub>c</sub>	200
	1ms	I <sub>c</sub> pulse	400
		-I <sub>c</sub>	200
	1ms	-I <sub>c</sub> pulse	400
Max. power dissipation	P <sub>c</sub>	1500	W
Operating temperature	T <sub>j</sub>	+150	°C
Storage temperature	T <sub>stg</sub>	-40 to +125	°C
Isolation voltage	V <sub>is</sub>	AC 2500 (1min.)	V
Screw torque	Mounting *1	3.5	N·m
	Terminals *2	4.5	N·m

\*1 : Recommendable value : 2.5 to 3.5 N·m (M5) or (M6)

\*2 : Recommendable value : 3.5 to 4.5 N·m (M6)

#### ● Electrical characteristics (at Tj=25°C unless otherwise specified)


Item	Symbol	Characteristics			Conditions	Unit
		Min.	Typ.	Max.		
Zero gate voltage collector current	I <sub>CE0</sub>	—	—	2.0	V <sub>GE</sub> =0V, V <sub>CE</sub> =1200V	mA
Gate-Emitter leakage current	I <sub>GES</sub>	—	—	30	V <sub>CE</sub> =0V, V <sub>GE</sub> =±20V	μA
Gate-Emitter threshold voltage	V <sub>GE(th)</sub>	4.5	—	7.5	V <sub>CE</sub> =20V, I <sub>c</sub> =200mA	V
Collector-Emitter saturation voltage	V <sub>CE(sat)</sub>	—	—	3.3	V <sub>GE</sub> =15V, I <sub>c</sub> =200A	V
Input capacitance	C <sub>ies</sub>	—	32000	—	V <sub>GE</sub> =0V	pF
Output capacitance	C <sub>oes</sub>	—	11600	—	V <sub>CE</sub> =10V	pF
Reverse transfer capacitance	C <sub>res</sub>	—	10320	—	f=1MHz	
Turn-on time	t <sub>on</sub>	—	0.65	1.2	V <sub>CC</sub> =600V	μs
	t <sub>r</sub>	—	0.25	0.6	I <sub>c</sub> =200A	
Turn-off time	t <sub>off</sub>	—	0.85	1.5	V <sub>GE</sub> =±15V	μs
	t <sub>f</sub>	—	0.35	0.5	R <sub>G</sub> =4.7ohm	
Diode forward on voltage	V <sub>F</sub>	—	—	3.0	I <sub>F</sub> =200A, V <sub>GE</sub> =0V	V
Reverse recovery time	t <sub>rr</sub>	—	—	0.35	I <sub>F</sub> =200A	μs

#### ● Thermal resistance characteristics

Item	Symbol	Characteristics			Conditions	Unit
		Min.	Typ.	Max.		
Thermal resistance	R <sub>th(j-c)</sub>	—	—	0.085	IGBT	°C/W
	R <sub>th(j-c)</sub>	—	—	0.18	Diode	°C/W
	R <sub>th(c-f)*</sub>	—	0.025	—	the base to cooling fin	°C/W

\* : This is the value which is defined mounting on the additional cooling fin with thermal compound







### ■ Equivalent Circuit Schematic



#### ● VCE(sat) classification


Rank	Length	Conditions
F	2.25 to 2.50V	I <sub>c</sub> = 200A V <sub>GE</sub> = 15V T <sub>j</sub> = 25°C
A	2.40 to 2.65V	
B	2.65 to 2.80V	
C	2.70 to 2.95V	
D	2.85 to 3.10V	
E	3.00 to 3.30V	

■ Characteristics (Representative)




保守禁止 予定機種  
Not recommend for new design.


Switching time vs. RG  
Vcc=600V, Ic=200A, VGE=±15V, Tj=25°C




Dynamic input characteristics  
Tj=25°C




Forward current vs. Forward voltage  
VGE=0V




Reverse recovery characteristics  
trr, Irr, vs. IF





Transient thermal resistance





Reversed biased safe operating area  
+VGE=15V, -VGE ≤ 15V, Tj ≤ 125°C, RG ≥ 4.7ohm





■ Outline Drawings, mm



Mass : 370g

保守廃止予定機種  
 Not recommend for new design.