



SKYPER™

IGBT Driver Core

SKYPER 32PRO

Preliminary Data

Features

- Two output channels
- Integrated potential free power supply
- Under voltage protection
- Drive interlock top / bottom
- Dynamic short circuit protection DSCP
- Halt logic signal
- Failure management
- Soft turn-off
- External error input (secondary side)
- IEC 60068-1 (climate) 40/085/56
- Coated with varnish

Typical Applications

- Driver for IGBT modules in bridge circuits in choppers, inverter drives, UPS and welding inverters
- DC bus voltage up to 1200V

1) with external high voltage diode

2) according to EN50178

3) according to VDE 0110-20

Isolation coordination in compliance with
EN50178 PD2

Degree of protection: IP00

Technical Explanations to the driver core
are available at www.semikron.com

Absolute Maximum Ratings		Values	Units
Symbol	Conditions		
V_S	Supply voltage primary	16	V
V_{IH}	Input signal voltage (High)	$V_S + 0,3$	V
V_{IL}	Input signal voltage (Low)	GND - 0,3	V
$I_{out,PEAK}$	Output peak current	15	A
$I_{out,AVmax}$	Output average current	50	mA
f_{max}	max. switching frequency	50	kHz
V_{CE}	Collector emitter voltage sense across the IGBT ¹⁾	1700	V
dv/dt	Rate of rise and fall of voltage secondary to primary side	50	kV/μs
V_{isolIO}	Isolation test voltage input - output (AC, rms, 2s) ²⁾	4000	V
V_{isolPD}	Partial discharge extinction voltage, rms, $Q_{PD} \leq 10\text{pC}$ ³⁾	1500	V
V_{isol12}	Isolation test voltage output 1 - output 2 (AC, rms, 2s) ²⁾	1500	V
R_{Gonmin}	Minimum rating for R_{Gon}	1,5	Ω
$R_{Goffmin}$	Minimum rating for R_{Goff}	1,5	Ω
$Q_{out/pulse}$	Max. rating for output charge per pulse	6,3	μC
T_{op}	Operating temperature	- 40 ... + 85	°C
T_{stg}	Storage temperature	- 40 ... + 85	°C

Characteristics		$T_a = 25^\circ\text{C}$, unless otherwise specified		
Symbol	Conditions	min.	typ.	max.
V_S	Supply voltage primary side	14,4	15	15,6
I_{SO}	Supply current primary side (no load)	80		500
	Supply current primary side (max.)			mA
V_i			15 / 0	V
V_{iT+}	Input signal voltage on/off			V
V_{iT-}	Input threshold voltage (High)			12,3
R_{in}	Input threshold voltage (Low)	4,6		V
	Input resistance (switching signals, HALT signal)		100	kΩ
$V_{G(on)}$	Turn on gate voltage output		+ 15	V
$V_{G(off)}$	Turn off gate voltage output		- 7	V
f_{ASIC}	Asic system switching frequency		8	MHz
$t_{d(on)IO}$	Input-output turn-on propagation time		1,2	μs
$t_{d(off)IO}$	Input-output turn-off propagation time		1,2	μs
$t_{d(err)}$	Error input-output propagation time	3,1		μs
$t_{d(err)ext}$	External error (secondary side) input-output propagation time		6,1	μs
$t_{pERRRESET}$	Error reset time		9	μs
t_{TD}	Top-Bot Interlock Dead Time	no interlock		4,3
V_{CEsat}	Reference voltage for V_{CE} -monitoring		10	μs
C_{ps}	Coupling capacitance primary secondary		12	pF
w	weight		34	g
$MTBF$	Mean Time Between Failure @ $T_a=40^\circ\text{C}$, max. load		1,3	10^6 h

This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.