

Part Number: SL15 33004

Ordering Different Lead Types:

| | |
|----------------------|---------------------------------------|
| Inside Kinked Leads | Use -A after Ametherm's part # |
| Outside Kinked Leads | Use -B after Ametherm's part # |

For example: to order an inside kinked lead use part number SL15 33004-A



Electrical Specifications:

| | |
|---|--------------------------|
| Resistance @ 25°C | 33.0 Ω \pm 20% |
| Max Steady State Current Up to 65°C | 4.0 A |
| Max Recommended Energy Rating (Joules) | 55.0 J |
| Actual Failure Point of Instantaneous Energy (Joules) | 110.0 J |
| Resistance @ 100% of Max Current | 0.280 Ω |
| Resistance @ 50% of Max Current | 0.600 Ω |
| Body Temperature @ 100% Current Rating | 164 °C |
| Dissipation Constant | 15.0Mw/°C |
| Thermal Time Constant | 54 seconds |
| Material Type | "I" |
| Max Capacitance @ 120VAC/240VAC | 3600 μ F/900 μ F |

Mechanical Specifications:

| | |
|--|-------------------|
| D | 15.0 mm Max |
| T | 5.0 mm Max |
| Lead Diameter | 0.8 mm Nom |
| S | 7.8 mm Nom |
| L | 38.0 mm Min |
| Straight Leads | Standard |
| B | 7.50 \pm 0.7 mm |
| Coating Run Down on the Straight Leads | 5.00 \pm 0.5 mm |