

Part Number: SL22 10008

### Ordering Different Lead Types:

Inside Kinked Leads	Use <b>-A</b> after Ametherm's part #
Outside Kinked Leads	Use <b>-B</b> after Ametherm's part #

For example: to order an inside kinked lead use part number SL22 10008-A



### Electrical Specifications:

Resistance @ 25°C	10.0 $\Omega$ $\pm$ 20%
Max Steady State Current Up to 65°C	8.0 A
Max Recommended Energy Rating (Joules)	90.0 J
Actual Failure Point of Instantaneous Energy (Joules)	200.0 J
Resistance @ 100% of Max Current	0.095 $\Omega$
Resistance @ 50% of Max Current	0.193 $\Omega$
Body Temperature @ 100% Current Rating	182 °C
Dissipation Constant	32.4mW/°C
Thermal Time Constant	122 seconds
Material Type	"H"
Max Recommended Capacitance @120/265/440 VAC	6000 $\mu$ F/ 1250 $\mu$ F/ 450 $\mu$ F

### Mechanical Specifications:

D	20.0 $\pm$ 1.0 mm
T	5.0 $\pm$ 0.5 mm
Lead Diameter	1.0 $\pm$ 0.1 mm
S	7.5 $\pm$ 0.80 mm
L	38.0 $\pm$ 9.0 mm
Straight Leads Coating Run Down	5.0 $\pm$ 1.0 mm
B	9.35 $\pm$ 0.85 mm
C	3.82 $\pm$ 1.0 mm