

TOSHIBA Phototransistor Silicon NPN Epitaxial Planar

TPS622(F)

Lead(Pb)-Free


Opto-electronic Switch

Optical Mouse

Optical Touch Switch

- Compact side view epoxy resin package
- High response speed: $t_r, t_f = 6\mu s$ (typ.)
- Half value angle: $\theta_{1/2} = \pm 15^\circ$ (typ.)
- Visible light cut type (black package)
- Optimum in combination with infrared LED TLN117(F) with identical external dimensions.

Unit in : mm



Weight: 0.1 g (typ.)

Absolute Maximum Ratings (Ta = 25°C)

Characteristic	Symbol	Rating	Unit
Collector-emitter voltage	V_{CEO}	30	V
Emitter-collector voltage	V_{ECO}	5	V
Collector current	I_C	50	mA
Collector power dissipation	P_C	75	mW
Collector power dissipation derating (Ta > 25°C)	$\Delta P_C / ^\circ C$	-1	mW / °C
Operating temperature range	T_{opr}	-25~85	°C
Storage temperature range	T_{stg}	-40~100	°C
Soldering temperature (5s)	T_{sol}	260 (Note 1)	°C

Note: Using continuously under heavy loads (e.g. the application of high temperature/current/voltage and the significant change in temperature, etc.) may cause this product to decrease in the reliability significantly even if the operating conditions (i.e. operating temperature/current/voltage, etc.) are within the absolute maximum ratings.

Please design the appropriate reliability upon reviewing the Toshiba Semiconductor Reliability Handbook ("Handling Precautions"/"Derating Concept and Methods") and individual reliability data (i.e. reliability test report and estimated failure rate, etc).

Note 1: Soldering portion of lead: At least 2mm from the body of the device.

Opto-electrical Characteristics (Ta = 25°C)


Characteristic	Symbol	Test Condition	Min.	Typ.	Max.	Unit
Dark current	$I_D(I_{CEO})$	$V_{CE} = 24V, E = 0$	—	0.005	0.1	μA
Light current	I_L	$E = 0.1mW / cm^2,$ $V_{CE} = 3V$ (Note 2,3)	27	70	—	μA
Collector-emitter saturation voltage	$V_{CE(sat)}$	$E = 0.1mW / cm^2,$ $I_L = 15\mu A$	—	0.15	0.4	V
Peak sensitivity wavelength	λ_P	—	—	870	—	nm
Half value angle	$\theta_{\frac{1}{2}}$	—	—	± 15	—	°
Switching time	Rise time	$V_{CC} = 5V, I_C = 2mA$ $R_L = 100\Omega$	—	6	—	μs
	Fall time		—	6	—	

Note 2: Color temperature = 2870K standard tungsten lamp

Note 3: I_L classification

Rank	I_L (μ A)
(A)	27~80
(B)	55~165
—	27min.

Pin Connection









Precaution


Take particular care with the following:

1. Lead forming should be carried out at least 2 mm from the body of the device without applying forming stress to the plastic.


Soldering should be performed after lead forming.




Switching Characteristics (saturated operation) (typ.)




$I_D(I_{CEO}) - T_a$ (typ.)




Switching Time Test Circuit



Relative $I_L - T_a$ (typ.)



Coupling Characteristics with TLN117(F)



RESTRICTIONS ON PRODUCT USE

20070701-EN GENERAL

- The information contained herein is subject to change without notice.
- TOSHIBA is continually working to improve the quality and reliability of its products. Nevertheless, semiconductor devices in general can malfunction or fail due to their inherent electrical sensitivity and vulnerability to physical stress. It is the responsibility of the buyer, when utilizing TOSHIBA products, to comply with the standards of safety in making a safe design for the entire system, and to avoid situations in which a malfunction or failure of such TOSHIBA products could cause loss of human life, bodily injury or damage to property.
In developing your designs, please ensure that TOSHIBA products are used within specified operating ranges as set forth in the most recent TOSHIBA products specifications. Also, please keep in mind the precautions and conditions set forth in the "Handling Guide for Semiconductor Devices," or "TOSHIBA Semiconductor Reliability Handbook" etc.
- The TOSHIBA products listed in this document are intended for usage in general electronics applications (computer, personal equipment, office equipment, measuring equipment, industrial robotics, domestic appliances, etc.). These TOSHIBA products are neither intended nor warranted for usage in equipment that requires extraordinarily high quality and/or reliability or a malfunction or failure of which may cause loss of human life or bodily injury ("Unintended Usage"). Unintended Usage include atomic energy control instruments, airplane or spaceship instruments, transportation instruments, traffic signal instruments, combustion control instruments, medical instruments, all types of safety devices, etc.. Unintended Usage of TOSHIBA products listed in this document shall be made at the customer's own risk.
- The products described in this document shall not be used or embedded to any downstream products of which manufacture, use and/or sale are prohibited under any applicable laws and regulations.
- The information contained herein is presented only as a guide for the applications of our products. No responsibility is assumed by TOSHIBA for any infringements of patents or other rights of the third parties which may result from its use. No license is granted by implication or otherwise under any patents or other rights of TOSHIBA or the third parties.
- Please contact your sales representative for product-by-product details in this document regarding RoHS compatibility. Please use these products in this document in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances. Toshiba assumes no liability for damage or losses occurring as a result of noncompliance with applicable laws and regulations.