


16 x 1 Character LCD



FEATURES	5
----------	---

- 5 x 8 dots includes cursor
- Built in controller (KS 0066 or Equivalent)
- + 5V power supply (Also available for + 3V)
- 1/16 duty cycle
- LED can be driven by pin 1, pin 2, pin 15 or A and K
- N.V. optional for + 3V power supply

MECHANICAL DATA								
ITEM	STANDARD VALUE	UNIT						
Module Dimension	122.0 x 33.0	mm						
Viewing Area	99.0 x 13.0	mm						
Mounting Hole	115.0 x 25.2	mm						
Character Size	4.84 x 8.06	mm						

ABSOLUTE MAXIMUM RATING										
ITEM	SYMBOL	STANDARD VALUE UN								
		MIN.	TYP.	MAX.						
Power Supply	VDD-VSS	- 0.3	-	7.0	V					
Input Voltage	VI	- 0.3	_	VDD	V					

NOTE: VSS = 0 Volt, VDD = 5.0 Volt

ELECTRICAL SPECIFICATIONS									
ITEM	SYMBOL	CONDITION	S	UNIT					
			MIN. TYP.		MAX.				
Input Voltage	VDD	VDD = + 5V	4.7	5.0	5.3	V			
Supply Current	IDD	VDD = +5V	-	1.2	1.4	mA			
		- 20 °C	4.9	5.1	5.5				
Recommended LC Driving	VDD - V0	0°C	4.5	4.8	5.1	V			
Voltage for Normal Temp.		25°C	4.1	4.5	4.7				
Version Module		50°C	3.8	4.2	4.4	-			
		70°C	3.5	3.9	4.1				
LED Forward Voltage	VF	25°C	-	4.2	4.6	V			
LED Forward Current	IF	25°C	-	160	_	mA			

DISPLAY CHARACTER ADDRESS CODE:																
Display Position	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
DD RAM Address	00	01						07	40	41						47
											•					


LCD-016M001L

Vishay

16 x 1 Character LCD



PIN NUMBER	SYMBOL	FUNCTION				
1	Vss	GND				
2	Vdd	+ 5V				
3	Vo	Contrast Adjustment				
4	RS	H/L Register Select Signal				
5	R/W	H/L Read/Write Signal				
6	E	H →L Enable Signal				
7	DB0	H/L Data Bus Line				
8	DB1	H/L Data Bus Line				
9	DB2	H/L Data Bus Line				
10	DB3	H/L Data Bus Line				
11	DB4	H/L Data Bus Line				
12	DB5	H/L Data Bus Line				
13	DB6	H/L Data Bus Line				
14	DB7	H/L Data Bus Line				
15	A/Vee	+ 4.2V for LED (RA = 0)/Negative Voltage Output				
16	К	Power Supply for B/L (0V)				





Vishay

Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.