

# DEC

## UF4001 THRU UF4007


CURRENT 1.0 Ampere  
VOLTAGE 50 to 1000 Volts

### Features

- Plastic package has Underwriters Laboratory Flammability Classification 94V-0
- Low forward voltage drop
- High current capability
- High reliability
- Low power loss, high efficiency
- High surge current capability
- High speed switching
- Low leakage

### Mechanical Data

- Case : JEDEC DO-41 molded plastic body
- Epoxy : UL94V-0 rate flame retardant
- Lead : Plated axial lead solderable per MIL-STD-750, method 2026
- Polarity : Color band denotes cathode end
- Mounting Position : Any
- Weight : 0.012 ounce, 0.33 gram



Dimensions in inches and (millimeters)

### Maximum Ratings And Electrical Characteristics

(Ratings at 25 °C ambient temperature unless otherwise specified, Single phase, half wave 60Hz, resistive or inductive load. For capacitive load, derate by 20%)

	Symbols	UF 4001	UF 4002	UF 4003	UF 4004	UF 4005	UF 4006	UF 4007	Units				
Maximum recurrent peak reverse voltage	V <sub>RRM</sub>	50	100	200	400	600	800	1000	Volts				
Maximum RMS voltage	V <sub>RMS</sub>	35	70	140	280	420	560	700	Volts				
Maximum DC blocking voltage	V <sub>DC</sub>	50	100	200	400	600	800	1000	Volts				
Maximum average forward rectified current 0.375"(9.5mm) lead length at T <sub>A</sub> =50 °C	I <sub>(AV)</sub>	1.0							Amp				
Peak forward surge current 8.3ms single half sine-wave superimposed on rated load (JEDEC method)	I <sub>FSM</sub>	30.0							Amps				
Maximum instantaneous forward voltage at 1.0A	V <sub>F</sub>	1.0		1.3	1.7				Volts				
Maximum DC reverse current at rated DC blocking voltage	I <sub>R</sub>	5.0							μ A				
Maximum full load reverse current full cycle average. 0.375"(9.5mm) lead length at T <sub>L</sub> =55 °C		100											
Maximum reverse recovery time (Note 1)	T <sub>rr</sub>	50		75				ns					
Typical junction capacitance (Note 2)	C <sub>J</sub>	20		10				pF					
Operating junction and storage temperature range	T <sub>J</sub> T <sub>STG</sub>	-65 to +150							°C				

#### Notes:

- Test conditions: I<sub>F</sub>=0.5A, I<sub>R</sub>=1.0A, I<sub>rr</sub>=0.25A.
- Measured at 1MHz and applied reverse voltage of 4.0 Volts.

# DEC

## RATINGS AND CHARACTERISTIC CURVES UF4001 THRU UF4007

FIG.1-TEST CIRCUIT DIAGRAM AND REVERSE RECOVERY TIME CHARACTERISTIC




FIG.2-TYPICAL FORWARD CURRENT DERATING CURVE




FIG.3-TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4-TYPICAL REVERSE CHARACTERISTICS




FIG.5-MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG6-TYPICAL JUNCTION CAPACITANCE

