


Inductors

Commercial, Molded



INDUCTANCE RANGE AND MILITARY STANDARD		
MODEL	INDUCTANCE RANGE	
	FROM	TO
IM-1	0.10 μ H	100 μ H
IM-2	0.022 μ H	0.082 μ H
	0.10 μ H	1 μ H
	1.2 μ H	27 μ H
	33 μ H	1000 μ H
IM-4	0.15 μ H	4.7 μ H
	5.6 μ H	33 μ H
	36 μ H	240 μ H
	270 μ H	1800 μ H
IM-6	0.10 μ H	2.7 μ H
	3.3 μ H	27 μ H
	33 μ H	220 μ H
	270 μ H	1000 μ H
IM-8	1100 μ H	3600 μ H
IM-9	68 μ H	150 μ H
IM-10	3900 μ H	10000 μ H

DIMENSIONS in inches [millimeters]					
					
MODEL		A (Dia.)	B	C (Typ.)	D (Dia.)
IM-1	Max.	0.086 [2.18]	0.210 [5.33]	1.62 [41.15]	0.0215 [0.546]
	Min.	0.070 [1.78]	0.190 [4.83]	1.38 [35.05]	0.0185 [0.470]
IM-2	Max.	0.105 [2.67]	0.260 [6.60]	1.63 [41.40]	0.0215 [0.546]
	Min.	0.085 [2.16]	0.240 [6.10]	1.25 [31.75]	0.0185 [0.470]
IM-4	Max.	0.165 [4.19]	0.385 [9.78]	1.63 [41.40]	0.027 [0.686]
	Min.	0.145 [3.68]	0.365 [9.27]	1.25 [31.75]	0.023 [0.584]
IM-6	Max.	0.200 [5.08]	0.450 [11.43]	1.63 [41.40]	0.027 [0.686]
	Min.	0.180 [4.57]	0.430 [10.92]	1.25 [31.75]	0.023 [0.584]
IM-8	Max.	0.225 [5.72]	0.570 [14.48]	1.63 [41.40]	0.030 [0.762]
	Min.	0.205 [5.21]	0.550 [13.97]	1.25 [31.75]	0.026 [0.660]
IM-9	Max.	0.260 [6.60]	0.570 [14.48]	1.63 [41.40]	0.027 [0.686]
	Min.	0.240 [6.10]	0.550 [13.97]	1.25 [31.75]	0.023 [0.584]
IM-10	Max.	0.250 [6.35]	0.750 [19.05]	1.63 [41.40]	0.034 [0.864]
	Min.	0.230 [5.84]	0.730 [18.54]	1.25 [31.75]	0.030 [0.762]

FEATURES

- Wide inductance range in small package
- Flame retardant coating
- Precision performance, excellent reliability, sturdy construction
- Epoxy molded construction provides superior moisture protection



RoHS
COMPLIANT

ELECTRICAL SPECIFICATIONS

Inductance Tolerance: $\pm 1\%$, $\pm 3\%$, $\pm 5\%$, $\pm 10\%$, $\pm 20\%$
Other tolerances available on request.

Insulation Resistance: 1000 Megohm minimum per MIL-STD-202, Method 302, Test Condition B

Dielectric Strength: Per MIL-STD-202, Method 301:
1000 VAC for IM-2, -4, -6, -8, -9 and -10. 200 VAC for IM-1

MECHANICAL SPECIFICATIONS

Terminal Strength: Per MIL-STD-202, Method 211,
Test Condition A: For IM-1, 3 pounds pull
For IM-2, -4, -6, -8, -9 and -10, 5 pounds pull and twist

Weight: IM-1 = 0.25 gram maximum

IM-2 = 0.30 gram maximum

IM-4 = 0.65 gram maximum

IM-6 = 0.95 gram maximum

IM-8 = 1.5 gram maximum

IM-9 = 2.0 gram maximum

IM-10 = 2.5 gram maximum

MATERIAL SPECIFICATIONS

Encapsulant: Epoxy

Standard Terminals: IM-1 and IM-2, 24 AWG; IM-4, IM-6 and IM-9, 22 AWG; IM-8, 21 AWG; and IM-10, 20 AWG, tinned copper

TEST EQUIPMENT*

- H/P 4342A Q-Meter
- Measurements Corporation Megacycle Meter, Model 59
- Wheatstone bridge

* Test procedures per MIL-PRF-15305

ENVIRONMENTAL PERFORMANCE		
TEST	CONDITIONS	SPECIFICATIONS
Barometric Pressure	Test Condition C	MIL-STD-202, Method 105
Thermal Shock	Test Condition A-1	MIL-STD-202, Method 107
Flammability	-	MIL-STD-202, Method 111
Overload	-	MIL-PRF-15305
Low Temperature Storage	-	MIL-PRF-15305
Resistance to Soldering Heat	Test Condition A	MIL-STD-202, Method 210
Resistance to Solvents	-	MIL-STD-202, Method 215



STANDARD ELECTRICAL SPECIFICATIONS								
MODEL	IND. (μH)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF-RESONANT* FREQ. MIN. (MHz)	DCR MAX. (Ohms)	RATED** DC CURRENT (mA)	
IM-1	0.10	± 10 %	35	25.0	680.0	0.13	895	PHENOLIC CORE
IM-1	0.12	± 10 %	35	25.0	650.0	0.15	835	
IM-1	0.15	± 10 %	35	25.0	560.0	0.18	760	
IM-1	0.18	± 10 %	35	25.0	540.0	0.21	705	
IM-1	0.22	± 10 %	30	25.0	500.0	0.25	645	
IM-1	0.27	± 10 %	30	25.0	440.0	0.38	525	
IM-1	0.33	± 10 %	25	25.0	410.0	0.49	460	
IM-1	0.39	± 10 %	25	25.0	380.0	0.59	420	
IM-1	0.47	± 10 %	25	25.0	340.0	0.62	410	
IM-1	0.56	± 10 %	40	25.0	250.0	0.18	510	IRON CORE
IM-1	0.68	± 10 %	40	25.0	215.0	0.20	485	
IM-1	0.82	± 10 %	40	25.0	200.0	0.22	465	
IM-1	1.0	± 10 %	40	25.0	190.0	0.25	435	
IM-1	1.2	± 10 %	35	7.9	170.0	0.28	410	
IM-1	1.5	± 10 %	40	7.9	150.0	0.49	310	
IM-1	1.8	± 10 %	40	7.9	135.0	0.56	290	
IM-1	2.2	± 10 %	45	7.9	130.0	0.72	257	
IM-1	2.7	± 10 %	45	7.9	110.0	0.85	236	
IM-1	3.3	± 10 %	45	7.9	100.0	1.2	198	
IM-1	3.9	± 10 %	50	7.9	95.0	1.5	178	
IM-1	4.7	± 10 %	55	7.9	88.0	2.1	150	
IM-1	5.6	± 10 %	55	7.9	78.0	2.8	130	
IM-1	6.8	± 10 %	55	7.9	69.0	3.2	122	
IM-1	8.2	± 10 %	45	7.9	52.0	4.4	104	
IM-1	10.0	± 10 %	45	7.9	47.0	5.2	95	
IM-1	12.0	± 10 %	40	2.5	31.0	3.0	126	
IM-1	15.0	± 10 %	40	2.5	26.0	3.4	118	
IM-1	18.0	± 10 %	40	2.5	23.0	3.8	112	
IM-1	22.0	± 10 %	45	2.5	20.0	4.3	105	
IM-1	27.0	± 10 %	45	2.5	17.0	4.7	100	
IM-1	33.0	± 10 %	45	2.5	15.0	5.2	95	
IM-1	39.0	± 10 %	45	2.5	13.5	6.8	83.5	
IM-1	47.0	± 10 %	45	2.5	12.5	8.2	76	
IM-1	56.0	± 10 %	45	2.5	11.5	10.0	69	
IM-1	68.0	± 10 %	45	2.5	10.5	11.5	64	
IM-1	82.0	± 10 %	45	2.5	10.0	16.0	54.5	
IM-1	100.0	± 10 %	45	2.5	9.5	17.5	52	
IM-2	0.022	± 20 %	50	50.0	900.0	0.025	2400	PHENOLIC CORE
IM-2	0.027	± 10 %	40	25.0	875.0	0.03	2200	
IM-2	0.033	± 10 %	40	25.0	850.0	0.035	2000	
IM-2	0.039	± 10 %	40	25.0	825.0	0.04	1900	
IM-2	0.047	± 10 %	40	25.0	800.0	0.045	1800	
IM-2	0.056	± 10 %	40	25.0	775.0	0.05	1700	
IM-2	0.068	± 10 %	40	25.0	750.0	0.06	1500	
IM-2	0.082	± 10 %	40	25.0	725.0	0.07	1400	
IM-2	0.10	± 10 %	40	25.0	680.0	0.08	1350	PHENOLIC CORE
IM-2	0.12	± 10 %	40	25.0	640.0	0.09	1270	
IM-2	0.15	± 10 %	38	25.0	600.0	0.10	1200	
IM-2	0.18	± 10 %	35	25.0	550.0	0.12	1105	
IM-2	0.22	± 10 %	33	25.0	510.0	0.14	1025	
IM-2	0.27	± 10 %	33	25.0	430.0	0.16	960	
IM-2	0.33	± 10 %	30	25.0	410.0	0.22	815	
IM-2	0.39	± 10 %	30	25.0	365.0	0.30	700	
IM-2	0.47	± 10 %	30	25.0	330.0	0.35	650	
IM-2	0.56	± 10 %	30	25.0	300.0	0.50	545	
IM-2	0.68	± 10 %	28	25.0	275.0	0.60	495	
IM-2	0.82	± 10 %	28	25.0	250.0	0.85	415	
IM-2	1.0	± 10 %	25	25.0	230.0	1.0	385	
IM-2	1.2	± 10 %	25	7.9	150.0	0.18	590	IRON CORE
IM-2	1.5	± 10 %	28	7.9	140.0	0.22	535	
IM-2	1.8	± 10 %	30	7.9	125.0	0.30	455	
IM-2	2.2	± 10 %	30	7.9	115.0	0.40	395	
IM-2	2.7	± 10 %	37	7.9	100.0	0.55	355	
IM-2	3.3	± 10 %	45	7.9	90.0	0.85	270	
IM-2	3.9	± 10 %	45	7.9	80.0	1.0	250	
IM-2	4.7	± 10 %	45	7.9	75.0	1.2	230	

* Measured with full length lead. **Rated DC current based on maximum temperature rise as shown in table.

STANDARD ELECTRICAL SPECIFICATIONS							
MODEL	IND. (μH)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF-RESONANT* FREQ. MIN. (MHz)	DCR MAX. (Ohms)	RATED** DC CURRENT (mA)
IM-2	5.6	± 10 %	50	7.9	65.0	1.8	185
IM-2	6.8	± 10 %	50	7.9	60.0	2.0	175
IM-2	8.2	± 10 %	55	7.9	55.0	2.7	155
IM-2	10.0	± 10 %	55	7.9	50.0	3.7	130
IM-2	12.0	± 10 %	45	2.5	40.0	2.7	155
IM-2	15.0	± 10 %	40	2.5	35.0	2.8	150
IM-2	18.0	± 10 %	50	2.5	30.0	3.1	145
IM-2	22.0	± 10 %	50	2.5	25.0	3.3	140
IM-2	27.0	± 10 %	50	2.5	20.0	3.5	135
IM-2	33.0	± 10 %	45	2.5	24.0	3.4	130
IM-2	39.0	± 10 %	45	2.5	22.0	3.6	125
IM-2	47.0	± 10 %	45	2.5	20.0	4.5	110
IM-2	56.0	± 10 %	45	2.5	18.0	5.7	100
IM-2	68.0	± 10 %	50	2.5	15.0	6.7	92
IM-2	82.0	± 10 %	50	2.5	14.0	7.3	88
IM-2	100.0	± 10 %	50	2.5	13.0	8	84
IM-2	120.0	± 10 %	30	0.79	12.0	13	66
IM-2	150.0	± 10 %	30	0.79	11.0	15	61
IM-2	180.0	± 10 %	30	0.79	10.0	17	57
IM-2	220.0	± 10 %	30	0.79	9.0	21	52
IM-2	270.0	± 10 %	30	0.79	8.0	25	47
IM-2	330.0	± 10 %	30	0.79	7.0	28	45
IM-2	390.0	± 10 %	30	0.79	6.5	35	40
IM-2	470.0	± 10 %	30	0.79	6.0	42	36
IM-2	560.0	± 10 %	30	0.79	5.0	46	35
IM-2	680.0	± 10 %	30	0.79	4.0	60	30
IM-2	820.0	± 10 %	30	0.79	3.8	65	29
IM-2	1000.0	± 10 %	30	0.79	3.4	72	28
IM-4	0.15	± 20 %	50	25	525.0	0.03	2450
IM-4	0.22	± 20 %	50	25	450.0	0.055	1810
IM-4	0.33	± 20 %	45	25	360.0	0.09	1400
IM-4	0.47	± 20 %	45	25	310.0	0.12	1225
IM-4	0.56	± 10 %	50	25	280.0	0.135	1150
IM-4	0.68	± 10 %	50	25	250.0	0.15	1100
IM-4	0.82	± 10 %	50	25	220.0	0.22	900
IM-4	1.0	± 10 %	50	25	200.0	0.29	785
IM-4	1.2	± 10 %	33	7.9	180.0	0.42	650
IM-4	1.5	± 10 %	33	7.9	160.0	0.50	600
IM-4	1.8	± 10 %	33	7.9	150.0	0.65	525
IM-4	2.2	± 10 %	33	7.9	135.0	0.95	435
IM-4	2.7	± 10 %	33	7.9	120.0	1.20	385
IM-4	3.3	± 10 %	33	7.9	110.0	2.0	300
IM-4	3.9	± 10 %	33	7.9	100.0	2.30	280
IM-4	4.7	± 10 %	33	7.9	90.0	2.60	260
IM-4	5.6	± 10 %	45	7.9	60.0	0.32	495
IM-4	6.8	± 10 %	50	7.9	55.0	0.50	395
IM-4	8.2	± 10 %	50	7.9	50.0	0.60	360
IM-4	10.0	± 10 %	55	7.9	45.0	0.90	290
IM-4	12.0	± 10 %	65	2.5	42.0	1.10	265
IM-4	15.0	± 10 %	65	2.5	40.0	1.40	240
IM-4	18.0	± 10 %	75	2.5	34.0	2.25	185
IM-4	22.0	± 10 %	75	2.5	30.0	2.50	175
IM-4	27.0	± 10 %	60	2.5	25.0	2.60	170
IM-4	33.0	± 10 %	65	2.5	19.0	3.0	165

* Measured with full length lead. **Rated DC current based on maximum temperature rise as shown in table.



STANDARD ELECTRICAL SPECIFICATIONS							
MODEL	IND. (μH)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF-RESONANT* FREQ. MIN. (MHz)	DCR MAX. (Ohms)	RATED** DC CURRENT (mA)
IM-4	36.0	± 5 %	60	2.5	15.5	2.50	180
IM-4	39.0	± 5 %	60	2.5	14.5	2.60	176
IM-4	43.0	± 5 %	60	2.5	13.7	2.70	172
IM-4	47.0	± 5 %	55	2.5	13.0	2.75	170
IM-4	51.0	± 5 %	55	2.5	12.7	2.85	167
IM-4	56.0	± 5 %	55	2.5	12.0	3.00	164
IM-4	62.0	± 5 %	55	2.5	11.5	3.15	160
IM-4	68.0	± 5 %	55	2.5	11.0	3.30	156
IM-4	75.0	± 5 %	55	2.5	10.5	3.70	147
IM-4	82.0	± 5 %	50	2.5	10.3	3.90	143
IM-4	91.0	± 5 %	50	2.5	10.0	4.30	136
IM-4	100.0	± 5 %	50	2.5	9.5	4.50	133
IM-4	110.0	± 5 %	60	0.79	8.9	4.90	128
IM-4	120.0	± 5 %	65	0.79	8.7	5.20	124
IM-4	130.0	± 5 %	65	0.79	8.5	5.45	121
IM-4	150.0	± 5 %	65	0.79	8.0	6.05	114
IM-4	160.0	± 5 %	65	0.79	7.5	6.40	111
IM-4	180.0	± 5 %	65	0.79	7.0	6.75	108
IM-4	200.0	± 5 %	65	0.79	6.5	7.10	106
IM-4	220.0	± 5 %	65	0.79	6.2	7.45	103
IM-4	240.0	± 5 %	65	0.79	5.9	7.80	101
IM-4	270.0	± 5 %	65	0.79	5.7	11.0	129
IM-4	300.0	± 5 %	65	0.79	5.4	11.5	125
IM-4	330.0	± 5 %	65	0.79	5.1	12.0	123
IM-4	360.0	± 5 %	65	0.79	4.8	15.5	108
IM-4	390.0	± 5 %	65	0.79	4.5	16.3	105
IM-4	430.0	± 5 %	65	0.79	4.2	17.1	102
IM-4	470.0	± 5 %	65	0.79	3.9	17.9	100
IM-4	510.0	± 5 %	65	0.79	3.7	18.8	98
IM-4	560.0	± 5 %	65	0.79	3.5	24.7	85
IM-4	620.0	± 5 %	65	0.79	3.3	25.9	83
IM-4	680.0	± 5 %	55	0.79	3.1	27.2	81
IM-4	750.0	± 5 %	55	0.79	2.9	28.6	79
IM-4	820.0	± 5 %	55	0.79	2.7	30.0	77
IM-4	910.0	± 5 %	55	0.79	2.5	31.5	76
IM-4	1000.0	± 5 %	55	0.79	2.3	33.1	74
IM-4	1100.0	± 5 %	30	0.25	2.1	43.5	64
IM-4	1200.0	± 5 %	30	0.25	2.0	45.7	63
IM-4	1300.0	± 5 %	30	0.25	1.9	49.0	61
IM-4	1500.0	± 5 %	30	0.25	1.8	52.5	59
IM-4	1600.0	± 5 %	30	0.25	1.7	54.0	58
IM-4	1800.0	± 5 %	30	0.25	1.6	56.7	56
IM-6	0.10	± 20 %	55	25.0	510.0	0.020	3600
IM-6	0.12	± 20 %	55	25.0	510.0	0.025	3300
IM-6	0.15	± 20 %	55	25.0	510.0	0.030	3000
IM-6	0.18	± 20 %	55	25.0	450.0	0.030	2900
IM-6	0.22	± 20 %	50	25.0	415.0	0.035	2800
IM-6	0.27	± 20 %	50	25.0	380.0	0.050	2400
IM-6	0.33	± 20 %	50	25.0	350.0	0.065	2000
IM-6	0.39	± 20 %	50	25.0	320.0	0.080	1800
IM-6	0.47	± 20 %	50	25.0	300.0	0.085	1700
IM-6	0.56	± 10 %	50	25.0	270.0	0.125	1450
IM-6	0.68	± 10 %	45	25.0	250.0	0.150	1300
IM-6	0.82	± 10 %	40	25.0	210.0	0.205	1100
IM-6	1.0	± 10 %	40	25.0	200.0	0.290	930
IM-6	1.2	± 10 %	30	7.9	180.0	0.400	785
IM-6	1.5	± 10 %	30	7.9	170.0	0.485	700
IM-6	1.8	± 10 %	30	7.9	150.0	0.740	580
IM-6	2.2	± 10 %	30	7.9	140.0	0.970	505
IM-6	2.7	± 10 %	30	7.9	120.0	1.20	460

IRON CORE

PHENOLIC CORE

* Measured with full length lead. **Rated DC current based on maximum temperature rise as shown in table.



STANDARD ELECTRICAL SPECIFICATIONS							
MODEL	IND. (µH)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF-RESONANT* FREQ. MIN. (MHz)	DCR MAX. (Ohms)	RATED** DC CURRENT (mA)
				LT10K			
IM-6	3.3	± 10 %	30	7.9	70.0	0.140	990
IM-6	3.9	± 10 %	30	7.9	65.0	0.155	870
IM-6	4.7	± 10 %	30	7.9	60.0	0.210	745
IM-6	5.6	± 10 %	30	7.9	50.0	0.280	645
IM-6	6.8	± 10 %	30	7.9	50.0	0.375	560
IM-6	8.2	± 10 %	30	7.9	48.0	0.440	540
IM-6	10.0	± 10 %	30	7.9	42.0	0.605	440
IM-6	12.0	± 10 %	50	2.5	36.0	1.05	370
IM-6	15.0	± 10 %	55	2.5	30.0	1.20	310
IM-6	18.0	± 10 %	60	2.5	30.0	1.95	255
IM-6	22.0	± 10 %	60	2.5	24.0	2.20	240
IM-6	27.0	± 10 %	65	2.5	22.0	2.75	205
IM-6	33.0	± 10 %	75	2.5	20.0	3.5	185
IM-6	39.0	± 10 %	75	2.5	18.0	3.8	176
IM-6	47.0	± 10 %	75	2.5	16.0	4.0	170
IM-6	56.0	± 10 %	75	2.5	15.0	4.4	164
IM-6	68.0	± 10 %	75	2.5	12.0	4.7	156
IM-6	82.0	± 10 %	75	2.5	10.0	5.3	143
IM-6	100.0	± 10 %	65	2.5	8.0	6.0	133
IM-6	120.0	± 10 %	65	0.79	6.0	5.0	124
IM-6	150.0	± 10 %	65	0.79	5.4	5.8	118
IM-6	180.0	± 10 %	65	0.79	5.0	6.6	114
IM-6	220.0	± 10 %	65	0.79	4.7	7.4	112
IM-6	270.0	± 5 %	65	0.79	5.6	8.2	110
IM-6	300.0	± 5 %	65	0.79	5.3	8.7	107
IM-6	330.0	± 5 %	65	0.79	5.0	9.1	105
IM-6	360.0	± 5 %	65	0.79	4.7	9.6	102
IM-6	390.0	± 5 %	65	0.79	4.5	10.0	100
IM-6	430.0	± 5 %	65	0.79	4.3	10.6	97
IM-6	470.0	± 5 %	65	0.79	4.0	11.1	95
IM-6	510.0	± 5 %	65	0.79	3.8	11.6	93
IM-6	560.0	± 5 %	65	0.79	3.6	12.3	91
IM-6	620.0	± 5 %	60	0.79	3.5	13.0	88
IM-6	680.0	± 5 %	60	0.79	3.4	13.7	85
IM-6	750.0	± 5 %	60	0.79	3.3	14.4	83
IM-6	820.0	± 5 %	60	0.79	3.1	15.1	81
IM-6	910.0	± 5 %	60	0.79	2.9	15.8	79
IM-6	1000.0	± 5 %	60	0.79	2.8	16.5	78
IM-8	1100.0	± 5 %	60	0.25	2.8	21.0	78
IM-8	1200.0	± 5 %	60	0.25	2.7	22.0	76
IM-8	1300.0	± 5 %	60	0.25	2.6	23.0	75
IM-8	1500.0	± 5 %	65	0.25	2.4	25.0	72
IM-8	1600.0	± 5 %	65	0.25	2.3	26.0	70
IM-8	1800.0	± 5 %	65	0.25	2.2	28.0	68
IM-8	2000.0	± 5 %	65	0.25	2.1	29.0	67
IM-8	2200.0	± 5 %	70	0.25	2.0	30.0	66
IM-8	2400.0	± 5 %	70	0.25	1.9	31.0	64
IM-8	2700.0	± 5 %	70	0.25	1.8	33.0	62
IM-8	3000.0	± 5 %	70	0.25	1.7	35.0	61
IM-8	3300.0	± 5 %	70	0.25	1.6	38.0	58
IM-8	3600.0	± 5 %	70	0.25	1.5	40.0	57

IRON CORE

IRON CORE

IRON CORE

* Measured with full length lead. **Rated DC current based on maximum temperature rise as shown in table.



STANDARD ELECTRICAL SPECIFICATIONS							
MODEL	IND. (μH)	TOL.	Q MIN.	TEST FREQ. L & Q (MHz)	SELF-RESONANT* FREQ. MIN. (MHz)	DCR MAX. (Ohms)	RATED** DC CURRENT (mA)
IM-9	68.0	± 10%	70	2.5	13.0	3.3	168
IM-9	82.0	± 10%	65	2.5	11.7	3.5	162
IM-9	100.0	± 10%	65	2.5	10.7	3.8	155
IM-9	120.0	± 10%	75	0.79	9.3	4.7	142
IM-9	150.0	± 10%	75	0.79	8.3	5.3	132
IM-10	3900.0	± 5%	80	0.25	1.45	44.0	61
IM-10	4300.0	± 5%	80	0.25	1.40	46.0	59
IM-10	4700.0	± 5%	80	0.25	1.35	48.0	58
IM-10	5000.0	± 5%	80	0.25	1.30	50.0	57
IM-10	5600.0	± 5%	80	0.25	1.25	53.0	56
IM-10	6200.0	± 5%	80	0.25	1.20	56.0	54
IM-10	6800.0	± 5%	80	0.25	1.15	59.0	52
IM-10	7500.0	± 5%	80	0.25	1.10	62.0	51
IM-10	8200.0	± 5%	80	0.25	1.05	65.0	50
IM-10	9100.0	± 5%	80	0.25	1.00	68.0	49
IM-10	10000.0	± 5%	80	0.25	0.95	72.0	47

* Measured with full length lead. **Rated DC current based on maximum temperature rise as shown in table.

MAXIMUM TEMPERATURE RISE		
		OPERATING TEMPERATURE RANGE
IM-1	0.10 μH to .47 μH = 35 °C at + 90 °C ambient	- 55 °C to + 125 °C
	0.56 μH to 1000 μH = 15 °C at + 90 °C ambient	- 55 °C to + 105 °C
IM-2	0.022 μH to 1.0 μH = 35 °C at + 90 °C ambient	- 55 °C to + 125 °C
	1.2 μH to 27 μH = 15 °C at + 90 °C ambient	- 55 °C to + 105 °C
	33 μH to 1000 μH = 15 °C at + 90 °C ambient	- 55 °C to + 105 °C
IM-4	0.15 μH to 4.7 μH = 35 °C at + 90 °C ambient	- 55 °C to + 125 °C
	5.6 μH to 33 μH = 15 °C at + 90 °C ambient	- 55 °C to + 105 °C
	36 μH to 240 μH = 15 °C at + 90 °C ambient	- 55 °C to + 105 °C
	270 μH to 1800 μH = 35 °C at + 90 °C ambient	- 55 °C to + 125 °C
IM-6	0.1 μH to 2.7 μH = 35 °C at + 90 °C ambient	- 55 °C to + 125 °C
	3.3 μH to 1000 μH = 15 °C at + 90 °C ambient	- 55 °C to + 105 °C
IM-8, IM-9, IM-10	= 15 °C at + 90 °C ambient	- 55 °C to + 105 °C

DESCRIPTION				
MODEL	INDUCTANCE VALUE	INDUCTANCE TOLERANCE	PACKAGE CODE	JEDEC LEAD (Pb)-FREE STANDARD
IM-2	10 μH	± 10 %	ER	e2

GLOBAL PART NUMBER INFORMATION			
<div style="display: flex; justify-content: space-around;"> I M 0 2 </div> <p>MODEL</p>	<div style="display: flex; justify-content: space-around;"> E R </div> <p>PACKING CODE</p>	<div style="display: flex; justify-content: space-around;"> 1 0 0 </div> <p>INDUCTANCE VALUE</p>	<div style="display: flex; justify-content: space-around;"> K </div> <p>TOL.</p>



Disclaimer

All product specifications and data are subject to change without notice.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained herein or in any other disclosure relating to any product.

Vishay disclaims any and all liability arising out of the use or application of any product described herein or of any information provided herein to the maximum extent permitted by law. The product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein, which apply to these products.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications unless otherwise expressly indicated. Customers using or selling Vishay products not expressly indicated for use in such applications do so entirely at their own risk and agree to fully indemnify Vishay for any damages arising or resulting from such use or sale. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

Product names and markings noted herein may be trademarks of their respective owners.