


SKS 4015F B6U 4060 V24



SEMISTACK Diode

Three-phase uncontrolled bridge rectifier

SKS 4015F B6U 4060 V24
Preliminary Data

Features

N4/250F heatsink


Typical Applications

- Industrial rectifiers

Options

- Fuse
- RC
- Reverse blocking voltage test
- Functional test
- Dielectric / isolation test

No. 08757274



B6U

Characteristics					
Symbol	Conditions	min.	typ.	max.	Unit
Electrical Data					
I_d	$T_{amb} = 35^\circ\text{C}$	no overload		4015	A
		150 % overload, 60s every 10 min.	2927	4319	A
		200 % overload, 60s every 10 min.	2496	4993	A
V_{CES}				2400	V
V_{DC}	DC voltage applied to the capacitor bank			1050	V
V_{AC}	network voltage (line side), -20% / +15%			760	V
V_{isol}	50 Hz / 1 min.		2500		V
i^2t	$T_{vj} = 25^\circ\text{C}$			-	kA^2s
	$T_{vj} = 175^\circ\text{C}$			3920	kA^2s
$(di/dt)_{cr}$					$\text{A}/\mu\text{s}$
$(dv/dt)_{cr}$					$\text{V}/\mu\text{s}$
V_{GT}					V
I_{GT}					mA
P_{tot}	$T_{amb} = 35^\circ\text{C}$		11702		W
R_{thja}	per component		0.072		K/W
T_{vj}		-40		+175	$^\circ\text{C}$
Fuse	No fuse				A
RC	No RC				Ω
RC	No RC				μF
Thermal trip	normally closed		112		$^\circ\text{C}$
Mechanical Data					
dv/dt_{AIR}					m^3/h
w	approx. total weight		130		kg
Size	Width x Depth x Height (with fan)	706	472	781	mm
T_{stg}		5		60	$^\circ\text{C}$
T_{amb}		5		60	$^\circ\text{C}$
Altitude	Installation height w/o derating			1000	m
Protection			IP00		
Pollution	EN 50178		2		
Fan Data					
Fan	included in the stack (YES)				
Type	2x SKF N4-230-01				
V_{Fan}	Fan voltage		230		V
f_{FAN}	Fan frequency		50		Hz
I_{FAN}	Fan current		2.1		A
P_{FAN}	Fan power		430		W




Fig. 1 Maximal overload factor vs nom current and ovl duration, $T_{amb} = 35^\circ\text{C}$




Fig. 2 Maximal overload factor vs nom current and ovl duration, $T_{amb} = 45^\circ\text{C}$




Fig. 3 Maximal overload duration vs nom current and ovl factor, $T_{amb} = 35^\circ\text{C}$




Fig. 4 Maximal overload duration vs nom current and ovl factor, $T_{amb} = 45^\circ\text{C}$




Fig. 5 Power losses





Fig. 6 Thermal impedance $Z_{th}(j-a)$

SKS 4015F B6U 4060 V24



Note: Stack design may vary depending upon the version. Please contact SEMIKRON for further details.

This technical information specifies semiconductor devices but promises no characteristics. No warranty or guarantee expressed or implied is made regarding delivery, performance or suitability.