

RF AMPLIFIER

MODEL *TM6570*

Available as: TM6570, 4 Pin TO-8 (T4)
 TN6570, 4 Pin Surface Mount (SM3)
 FP6570, 4 Pin Flatpack (FP4)
 PN6570, Reduced Size Surface Mount (SM11)
 BX6570, Connectorized Housing (H1)

Features

- Low Noise Figure: <2.5 dB Typical
- High Output Power: >+17.5 dBm Typical
- Operating Temp. - 55 °C to +85 °C
- Environmental Screening Available

Specifications

CHARACTERISTIC	TYPICAL Ta= 25 °C	MIN/MAX Ta = -55 °C to +85 °C
Frequency	10 - 500 MHz	10 - 500 MHz
Gain (dB)	8.0	7.0 Min.
Power @ 1 dB Comp. (dBm)	>+17.5	+17.5 Min.
Reverse Isolation (dB)	-11	-9.5 Max.
VSWR In	<1.85:1	2.0:1 Max.
Out	<1.5:1	2.0:1 Max.
Noise figure (dB)	<2.5	3.0 Max.
Power Vdc	+15	+15
mA	35	40 Max.

Note: Care should always be taken to effectively ground the case of each unit.


Typical Intermodulation Performance at 25 ° C

Second Order Harmonic Intercept Point +51 dBm (Typ.)
 Second Order Two Tone Intercept Point +46 dBm (Typ.)
 Third Order Two Tone Intercept Point +35 dBm (Typ.)

Maximum Ratings

Ambient Operating Temperature -55°C to + 100 °C
 Storage Temperature -62°C to + 125 °C
 Case Temperature + 125 °C
 DC Voltage + 18 Volts
 Continuous RF Input Power + 13 dBm
 Short Term RF Input Power 50 Milliwatts (1 Minute Max.)
 Maximum Peak Power 0.5 Watt (3 μsec Max.)

Typical Performance Data



Legend ——— + 25 °C - - - - + 85 °C ······ -55 °C

Linear S-Parameters

FREQ. MHz	S11		S21		S12		S22	
	Mag	Deg	Mag	Deg	Mag	Deg	Mag	Deg
5	.13	148	2.56	12	.29	12	.13	150
50	.09	-160	2.63	- 12	.29	- 12	.07	-175
100	.13	-151	2.62	- 26	.29	- 25	.08	-167
200	.20	-157	2.60	- 52	.28	- 52	.11	-170
300	.25	-176	2.59	- 79	.27	- 79	.13	176
400	.27	163	2.59	-106	.26	-107	.11	155
500	.26	141	2.58	-136	.25	-137	.07	148
600	.24	117	2.53	-167	.25	-170	.06	140



Spectrum Microwave · 2144 Franklin Drive N.E. · Palm Bay, Florida 32905 · PH (888) 553-7531 · Fax (888) 553-7532 4/2/04

www.spectrummicrowave.com Spectrum Microwave (Europe) · 2707 Black Lake Place · Philadelphia, Pa. 19154 · PH (215) 464-4000 · Fax (215) 464-4001