

**TRIPLE DIFFUSED PLANER TYPE  
ULTRA HIGH  $\beta$  TRANSISTOR  
INDUSTRIAL USE POWER SUPPLY**


■ **Features**

- Ultra high  $\beta$
- Excellent linearity in hFE
- Excellent safe operating area
- High reliability

■ **Applications**

- Color & B/W TV power supply
- Active power filter
- Industrial use power supply (Series regulator)
- General purpose power amplifiers

■ **Outline Drawings**



■ **Maximum ratings and characteristics**

- **Absolute maximum ratings (Tc=25°C unless otherwise specified)**

Item	Symbol	Ratings	Unit
Collector-Base voltage	V <sub>CB0</sub>	200	V
Collector-Emitter voltage	V <sub>CE0</sub>	180	V
Emitter-Base voltage	V <sub>EB0</sub>	6	V
Collector current	I <sub>C</sub>	5	A
Base current	I <sub>B</sub>	0.5	A
Collector power dissipation	P <sub>C</sub>	80	W
Operating junction temperature	T <sub>j</sub>	+150	°C
Storage temperature	T <sub>stg</sub>	-55 to +150	°C

- **Electrical characteristics (Tc =25°C unless otherwise specified)**

Item	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Collector-Base voltage	V <sub>CB0</sub>	I <sub>CBO</sub> = 1mA	200			V
Collector-Emitter voltage	V <sub>CE0</sub>	I <sub>CEO</sub> = 10mA	180			V
Emitter-Base voltage	V <sub>EB0</sub>	I <sub>EBO</sub> = 1mA	6			V
Collector-Base leakage current	I <sub>CBO</sub>	V <sub>CB0</sub> = 200V			1.0	mA
Emitter-Base leakage current	I <sub>EBO</sub>	V <sub>EB0</sub> = 6V			1.0	mA
D.C. current gain	h <sub>FE</sub>	I <sub>C</sub> = 1A, V <sub>CE</sub> = 4V	700			
Collector-Emitter saturation voltage	V <sub>CE(Sat)</sub>	I <sub>C</sub> = 1.5A, I <sub>B</sub> = 50mA			1.5	V
Base-Emitter saturation voltage	V <sub>BE(Sat)</sub>				2.0	V

- **Thermal characteristics**

Item	Symbol	Test Conditions	Min.	Typ.	Max.	Units
Thermal resistance	R <sub>th(j-c)</sub>	Junction to case			1.55	°C/W

Characteristics

