

# 400 W C-Band Helix TWT Series

400 W, CW Helix TWT Series, 5.85 GHz to 6.65 GHz, Periodic-Permanent, Magnet Focused, Coaxial Input, Waveguide Output, and Conduction Cooled.

Custom configurations are also available. These variations in the performance and configuration include: mechanical configuration, electrical and RF connections, & dual stage depressed collector.



Model Number	Frequency (GHz)	Power Output (Min.)
VTC-6265E1	5.85 – 6.65	400 W

## Operating Parameters

### Features

- 400 Watts
- 5.85 GHz – 6.65 GHz
- PPM Focusing
- Coaxial Input
- Waveguide Output
- Any Mounting Position
- Weight: 7.5 lbs. Max
- Conduction Cooled

	Heater Voltage	Heater Surge Current	Helix Voltage	Collector Voltage 1	Collector Voltage 2	Cathode Current
<b>Parameters:</b>	Ef	If (Surge)	Ew	Eb1	Eb2	Ik
<b>Units:</b>	V	A	kVdc	kVdc	kVdc	mAdc
<b>Maximum:</b>	6.3	5.0	9.3	0.52 Ew	0.34 Ew	310
<b>Minimum:</b>	5.9	---	8.6	0.48 Ew	0.30 Ew	---
<b>Typical:</b>						

  

	Helix Current	Drive Power	Cathode Warm-up Time	Load VSWR	Baseplate Temperature
<b>Parameters:</b>	Iw	Pd	tk	VSWR	Temperature
<b>Units:</b>	mAdc	mW	Minutes		°C
<b>Maximum:</b>	15	10	---	1.5:1	120
<b>Minimum:</b>	---	---	3	---	---
<b>Typical:</b>					

The values listed above represent specified limits for the product and are subject to change. The data should be used for basic information only. Formal, controlled specifications may be obtained from CPI for use in equipment design.