
THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, MITHOUT PRIOR WRITTEN PERMISSION OF PROJECTS UNLIMITED, INC. IS PROHIBITED.

© 2005, Projects Unlimited Inc.

SPECIFICATIONS

,		
PARAMETERS	VALUES	UNITS
DIRECTIVITY	NOISE CANCELLING	_
SENSITIVITY	-51±4	dB
STANDARD OPERATING VOLTAGE	2	Vdc
MAX OPERATING VOLTAGE	10	Vdc
CURRENT CONSUMPTION (MAX)	0.5	mA
IMPEDANCE	2.2	KOhm
SIGNAL TO NOISE RATIO (MIN.)	55	dB
MAXIMUM SOUND INPUT	110	dB
OPERATING TEMPERATURE	−20 ~ +70	•c
STORAGE TEMPERATURE	-40 ~ +85	•c
TERMINAL	SOLDER PADS	-
INTERNAL CAPACITOR	N/A	pF

		REVISIONS		
	LTR	DESCRIPTION	DATE	APPROVED
	-	RELEASED FROM ENGINEERING	1/30/06	
	Α	ADDED TERMINAL POLARITY	2/1/07	D.F.
	В	REVISED ELECTRICAL PARAMETERS	2/4/10	B.R.



NOTES:

- 1. ALL DIMENSIONS ARE IN MILLIMETERS.
- 2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.
- 3. THIS PART IS RoHS 2002/95/EC COMPLIANT.

FILE NAME PNM-2751L-R.DWG

projects ® unlimited UNLESS OTHERWISE SPECIFIED:
DIMENSIONS ARE IN
MILLIMETERS, TOLERANCES ARE ±0.5 AND
ANGLES ARE ±3°. Dayton , Ohio MICROPHONE APPROVALS DATE DRAWN J.A.F. 1/06 DRAWING NO. CHECKED SIZE E.P. 1/06 PNM-2751L-R APPROVED B.R. 1/06 SHEET 1 OF DO NOT SCALE DRAWING SCALE: N.T.S.