



KDMIX Series

HDMI(™) Mini Connector, Right Angle SMT

Features

- Supports Deep Color over HDMI(™)
- 19 Position receptacle
- Smaller, more compact form than the traditional HDMI(™) counterpart
- Provides low impedance mismatch

Performance Specifications

Materials and Finish

Housing : High Temp Thermoplastic, UL94V-0 Rated, Color-Black

Contacts : Phosphor Bronze

Shield : Nickel plated

Plating : Standard - 30μ" Gold in front contacts and Gold flash in solder area

Electrical Characteristics

Insulation Resistance : 100 Megohms Min.

Dielectric Withstanding Voltage : 500V AC RMS for 1 min.

Operating Rating : 0.5 Max.

Operating Temperature : -25°C to 85°C

KDMIX

KDMIX Series

Ordering Information

KDMIX	-	NS3		A	-	WS	-	B		TR
Series		Shield Option		Board Lock Option		Top Spring		Insulator Option		Packaging Option

Series

KDMIX- HDMI(™) Mini Connector

Shield Option

NS3 -Through hole shield tabs with even length pegs and no flange

Board Lock Option

A - Standard Straight B - Indented



Top Spring

WS - With Top Spring

Insulator Option

B - Black

Packaging Option

TR - Tape and Reel

KDMIX-NS3X-WS-BTR

