


PANDUIT® REEL SMART™ Termination System



Fork Terminals, Nylon Insulated

- Funnel Entry
- Metal Insulation Grip Sleeve



PANDUIT® Part Number	Wire Range	Color Code	Max. Ins.	Stud Size	Dimensions (In.)				CA9 Series Crimp Die	CA-800 Series Crimp Die	Pieces Per Reel
					A	W	C	G			
PNF18-6F-3K	22-18 .03 Stock	Red	.145	#6	.78	.30	.19	.64	CD9-1A	CD-800-1	3000
PNF18-6FN-3K				#6	.77	.24	.19	.64			3000
PNF18-8F-3K				#8	.83	.32	.22	.67			3000
PNF18-10F-3K				#10	.85	.35	.24	.69			3000
PNF18-14F-3K				1/4"	1.02	.44	.33	.78			3000
PNF14-6F-3K	16-14 .03 Stock	Blue	.162	#6	.78	.28	.19	.64	CD9-2A	CD-800-2	3000
PNF14-6FN-3K				#6	.78	.24	.19	.64			3000
PNF14-8F-3K				#8	.84	.31	.23	.68			3000
PNF14-10F-3K				#10	.86	.34	.24	.70			3000
PNF10-6F-2K	12-10 .04 Stock	Yellow	.225	#6	.99	.31	.24	.78	CD9-3B	CD-800-3	2000
PNF10-8F-2K				#8	1.00	.37	.24	.78			2000


Order number of pieces required, in multiples of standard reel quantity. *Prime items appear in BOLD.*

Flanged Fork Terminals, Nylon Insulated

- Funnel Entry
- Metal Insulation Grip Sleeve



LISTED 587H CERTIFIED




PANDUIT Part Number	Wire Range	Color Code	Max. Ins.	Stud Size	Dimensions (In.)				CA9 Series Crimp Die	CA-800 Series Crimp Die	Pieces Per Reel
					A	W	C	G			
PNF18-6FF-3K	22-18 .03 Stock	Red	.145	#6	.80	.28	.19	.64	CD9-1A	CD-800-1	3000
PNF18-8FF-3K				#8	.87	.31	.23	.68			3000
PNF18-10FF-3K				#10	.86	.35	.23	.68			3000
PNF14-6FF-3K	16-14 .03 Stock	Blue	.162	#6	.80	.28	.19	.64	CD9-2A	CD-800-2	3000
PNF14-8FF-3K				#8	.87	.31	.23	.68			3000
PNF14-10FF-3K				#10	.87	.35	.23	.68			3000
PNF10-8FF-2K	12-10 .04 Stock	Yellow	.225	#8	1.03	.38	.24	.78	CD9-3B	CD-800-3	2000
PNF10-10FF-2K				#10	1.03	.38	.24	.78			2000

Order number of pieces required, in multiples of standard reel quantity. *Prime items appear in BOLD.*

Fork Terminals, Nylon Insulated

- Metal Insulation Grip Sleeve



PANDUIT Part Number	Wire Range	Color Code	Max. Ins.	Stud Size	Dimensions (In.)				CA9 Series Crimp Die	CA-800 Series Crimp Die	Pieces Per Reel
					A	W	C	G			
PN18-6F-3K	22-18 .03 Stock	Red	.145	#6	.78	.30	.20	.64	CD9-1A	CD-800-1	3000
PN18-6FN-3K				#6	.78	.25	.20	.64			3000
PN18-8F-3K				#8	.85	.32	.23	.68			3000
PN18-10F-3K				#10	.86	.35	.25	.70			3000
PN18-10FN-3K				#10	.86	.31	.25	.70			3000
PN18-14F-3K	1/4"	1.03	.44	.33	.78	3000					
PN14-6F-3K	16-14 .03 Stock	Blue	.162	#6	.78	.28	.19	.64	CD9-2A	CD-800-2	3000
PN14-6FN-3K				#6	.78	.24	.19	.61			3000
PN14-8F-3K				#8	.84	.31	.23	.68			3000
PN14-10F-3K				#10	.86	.34	.24	.70			3000
PN14-10FN-3K				#10	.86	.31	.24	.70			3000
PN14-14F-3K	1/4"	1.03	.44	.33	.78	3000					
PN10-6F-2K	12-10 .04 Stock	Yellow	.225	#6	.98	.31	.24	.79	CD9-3B	CD-800-3	2000
PN10-8F-2K				#8	1.01	.37	.24	.79			2000
PN10-10F-2K				#10	1.02	.37	.24	.79			2000
PN10-14F-2K				1/4"	1.12	.49	.32	.88			2000


Order number of pieces required, in multiples of standard reel quantity. *Prime items appear in BOLD.*

Flanged Fork Terminals, Nylon Insulated

- Metal Insulation Grip Sleeve



LISTED 587H CERTIFIED



PANDUIT Part Number	Wire Range	Color Code	Max. Ins.	Stud Size	Dimensions (In.)				CA9 Series Crimp Die	CA-800 Series Crimp Die	Pieces Per Reel
					A	W	C	G			
PN18-6FF-3K	22-18 .03 Stock	Red	.136	#6	.80	.28	.19	.64	CD9-1A	CD-800-1	3000
PN18-8FF-3K				#8	.87	.31	.23	.68			3000
PN18-10FF-3K				#10	.87	.35	.23	.68			3000
PN14-6FF-3K	16-14 .03 Stock	Blue	.162	#6	.80	.28	.19	.64	CD9-2A	CD-800-2	3000
PN14-8FF-3K				#8	.87	.31	.23	.68			3000
PN14-10FF-3K				#10	.87	.35	.23	.68			3000
PN10-8FF-2K	12-10 .04 Stock	Yellow	.225	#8	1.03	.38	.22	.78	CD9-3B	CD-800-3	2000
PN10-10FF-2K				#10	1.03	.38	.22	.78			2000

Order number of pieces required, in multiples of standard reel quantity. *Prime items appear in BOLD.*