

Model 888, 887 18 & 20 Pin Dual In-Line Thick Film Resistor Network

Electrical

Standard Resistance Range, Ohms	22 to 2.2 Meg
Standard Resistance Tolerance at 25°C	-1, -3 Circuits ±2% -5 Circuits ±5% (≤33 Ohms = ±2 Ohms)
Operating Temperature Range, °C	-55° to 125°
Temperature Coefficient of Resistance, ppm/°C	±100 (<100 Ohms = ±250)
Temperature Coefficient of Resistance, Tracking, ppm/°C	50
Maximum Operating Voltage, Vdc	100V or √PR
Insulation Resistance, Ohms (Minimum)	10,000 Meg

Mechanical


Lead Material	Copper Alloy, 60/40 Tin-Lead Plating
Substrate Material	Alumina
Resistor Material	Cermet

Environmental (Per MIL-R-83401)

Thermal Shock Plus Power Conditioning	(ΔR) ±0.70%
Short Time Overload	(ΔR) ±0.50%
Terminal Strength	(ΔR) ±0.25%
Moisture Resistance	(ΔR) ±0.50%
Mechanical Shock	(ΔR) ±0.25%
Vibration Shock	(ΔR) ±0.25%
Low Temperature Storage	(ΔR) ±0.25%
High Temperature Exposure	(ΔR) ±0.50%
Load Life, 1,000 Hours	(ΔR) ±1.00%
Resistance to Soldering Heat (Per MIL-STD-202, Method 210, Cond. B)	(ΔR) ±0.25%
Dielectric Withstanding Voltage, RMS	200V for 1 Minute
Marking Permanency	Per Paragraph 4.6.7
Lead Solderability	Per Paragraph 4.6.6
Flammability	UL-94V-0 Rated
Storage	-55°C to 125°C

Specifications subject to change without notice.

Power Derating Curve



Power (Watts) Dissipation @ 70°C

Model	Package	Resistor (Per Circuit)		
		-1	-3	-5
887	2.50	.125	.250	.125
888	2.25	.125	.250	.125

Ordering Information

Model Series	88 7 -5- R220 / 330 F	Tolerance Code (If other than standard) F = ±1% G = ±2% J = ±5%
Number of Leads	8 = 18 Leads 7 = 20 Leads	
Circuit Type	1 = Bussed 3 = Isolated 5 = Dual Terminator	R2 Resistance Value Add for -5 circuit only
Resistance Value		

Applicable Documents

MIL-R-83401	— Resistor Networks, Fixed, Film, General Specification
MIL-STD-202	— Test Methods for Electronics and Electrical Component Parts


Approved to British Standard Specification BS9450 F0001.

Model 888, 887

BECKMAN INDSTL/ ELEC TECH 44E D

1336610 0002927 1 BIC T-62-05

Outline Dimensions inches mm




Note: Unless otherwise specified, tolerances are $\pm \frac{.005}{0.13}$


Schematics: Standard

888: N = 18 Leads
887: N = 20 Leads


— 3 Circuit
Isolated
Resistors




— 1 Circuit
Bussed
Resistors




— 5 Circuit
Dual
Terminator



— 6 Circuit
SCSI
Terminator



Typical Part Marking





Packaging

Standard: Magazine
All units oriented with lead #1 to the same side.
Magazine: Material = Anti-Static Plastic
Capacity, Units = 20

Custom Capabilities

Circuits shown are representative of our custom circuit capability. Consult factory for additional applications.



WORLDWIDE HEADQUARTERS
Beckman Industrial Corp.
Affiliate of Emerson Electric Co.
4141 Palm Street
Fullerton, CA 92635-1025
Telephone: (714) 447-2345
Fax: (714) 447-2500

EUROPEAN HEADQUARTERS
Beckman Industrial Ltd.
Queensway, Glenrothes, Fife
Scotland KY7 5PU
Telephone: (44) 592 753811
Fax: (44) 592 756443

FAR EASTERN HEADQUARTERS
Beckman Industrial Japan, Ltd.
Kakumaru Bldg.
1-10, Toyo 7-Chome
Koto-Ku, Tokyo, Japan
Telephone: Tokyo (03) 3615-1811
Fax: (03) 3647-2443