

**VI TELEFILTER**

**Filter specification**

**TFS 90B**

**1/5**

**Measurement condition**

Ambient temperature:	23	°C
Input power level:	0	dBm
Terminating impedance: *		
Input:	1000 Ω	-18,0 pF
Output:	900 Ω	-17,9 pF

**Characteristics**

Remark:

The nominal frequency  $f_N$  is fixed at 90,0 MHz. The insertion loss  $a_e$  is defined as loss value determined at  $f_N$ . Reference level for the relative attenuation  $a_{rel}$  of the TFS 90B is the insertion loss  $a_e$ . The centre frequency  $f_C$  is the arithmetic mean value of the upper and lower frequencies at the 2 dB filter attenuation level relative to the insertion loss  $a_e$ . All specified data are met within the operating temperature range.

D a t a		typ. value		tolerance / limit	
<b>Insertion loss</b> (reference level)		$a_e$	10,9 dB	max.	13,0 dB
<b>Nominal frequency</b>		$f_N$	-		90,0 MHz
<b>Centre frequency</b>		$f_C$	90,0 MHz		-
<b>Passband</b>		PB	-	$f_N \pm$	1,8 MHz
<b>Pass band ripple</b>		p-p	0,7 dB	max.	2 dB
<b>Bandwidth</b>					
1	dB		3,8 MHz		-
3	dB		4,2 MHz		-
<b>Relative attenuation</b>					
		$a_{rel}$			
$f_N$		... $f_N \pm$	1,5 MHz	0,3 dB	max. 0,6 dB
$f_N \pm$	1,5 MHz	... $f_N \pm$	1,8 MHz	0,6 dB	max. 2,5 dB
$f_N -$	80 MHz	... $f_N -$	15 MHz	48 dB	min. 40 dB
$f_N \pm$	15 MHz	... $f_N \pm$	10 MHz	38 dB	min. 30 dB
$f_N \pm$	10 MHz	... $f_N \pm$	6 MHz	30 dB	min. 25 dB
$f_N \pm$	6 MHz	... $f_N \pm$	2,5 MHz	13 dB	min. 6,5 dB
$f_N +$	15 MHz	... $f_N +$	80 MHz	44 dB	min. 40 dB
$f_N +$	80 MHz	... $f_N +$	910 MHz	38 dB	min. 30 dB
<b>Group delay</b>		at $f_N$		0,65 μs	max. 0,75 μs
<b>Group delay variation in <math>f_N \pm 1,2</math> MHz</b>		p-p		80 ns	max. 120 ns
<b>Group delay variation in PB</b>		p-p		100 ns	max. 180 ns
<b>Intermodulation **</b>				42 dBm	min. 30 dBm
<b>Input power level</b>				-	max. 6 dBm
<b>Operating temperature range</b>		OTR		-	-40 °C..... +85 °C
<b>Storage temperature range</b>				-	-55 °C..... +85 °C
<b>Temperature coefficient of frequency</b>		$TC_f$ ***	-33 ppm/K		-

\*) The terminating impedances depend on parasitics and q-values of matching elements and the board used, and are to be understood as reference values only. Should there be additional questions do not hesitate to ask for an application note or contact our design team.

\*\*)  $f_{in1} = 89,4$  MHz;  $f_{in2} = 89,7$  MHz;  $P_{in} = 0$  dBm  $f_{measurement} = 90,0$  MHz

\*\*\*)  $\Delta f_C(\text{Hz}) = TC_f(\text{ppm/K}) \times (T - T_o) \times f_{T_o}(\text{MHz})$ .



**Generated:**

**Checked / Approved:**

Tele Filter GmbH  
 Potsdamer Straße 18  
 D 14 513 TELTOW / Germany  
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30  
 E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)


VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

**Filter characteristic**



**Construction and pin connection**


(All dimensions in mm)



- 1 Input
- 2 Input RF Return
- 3 Ground
- 4 Ground
- 5 Ground
- 6 Ground
- 7 Output
- 8 Output RF Return
- 9 Ground
- 10 Ground
- 11 Ground
- 12 Ground

Date code: Year + week  
 U 2006  
 V 2007  
 W 2008  
 ...

**50 Ohm Test circuit**



**Tele Filter GmbH**  
 Potsdamer Straße 18  
 D 14 513 TELTOW / Germany  
 Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30  
 E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

**Stability characteristics, reliability**

After the following tests the filter shall meet the whole specification:

1. Shock: 500g, 1 ms, half sine wave, 3 shocks each plane;  
DIN IEC 68 T2 - 27
2. Vibration: 10 Hz to 500 Hz, 0,35 mm or 5 g respectively, 1 octave per min, 10 cycles per plan, 3 plans;  
DIN IEC 68 T2 - 6
3. Change of temperature: -55 °C to 125°C / 30 min. each / 10 cycles  
DIN IEC 68 part 2 – 14 Test N
4. Resistance to solder heat (reflow): reflow possible: three times max.;  
for temperature conditions refer to the attached "Air reflow temperature conditions" on page 4;

This filter is RoHS compliant (2002/95/EG, 2005/618/EG)


**Packing**

Tape & Reel: IEC 286 – 3, with exception of value for N and minimum bending radius;  
tape type II, embossed carrier tape with top cover tape on the upper side;

max. pieces of filters per reel:	3000
reel of empty components at start:	min. 300 mm
reel of empty components at start including leader:	min. 500 mm
trailer:	min. 300 mm


**Tape (all dimensions in mm)**

- W : 16,00 ± 0,3
- Po : 4,00 ± 0,1
- Do : 1,50 +0,1/-0
- E : 1,75 ± 0,1
- F : 7,50 ± 0,1
- G(min) : 0,60
- P2 : 2,00 ± 0,1
- P1 : 8,00 ± 0,1
- D1(min) : 1,50
- Ao : 5,50 ± 0,1
- Bo : 7,50 ± 0,1
- Ct : 13,5 ± 0,1



**Reel (all dimensions in mm)**

- A : 330
- W1 : 16,4 +2/-0
- W2(max) : 22,4
- N(min) : 50
- C : 13,0 +0,5/-0,2



The minimum bending radius is 45 mm.


**Tele Filter GmbH**  
**Potsdamer Straße 18**  
**D 14 513 TELTOW / Germany**  
**Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30**  
**E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

**Air reflow temperature conditions**

<b>Conditions</b>	<b>Exposure</b>
Average ramp-up rate (30°C to 217°C)	less than 3°C/second
> 100°C	between 300 and 600 seconds
> 150°C	between 240 and 500 seconds
> 217°C	between 30 and 150 seconds
Peak temperature	max. 260°C
Time within 5°C of actual peak temperature	between 10 and 30 seconds
Cool-down rate (Peak to 50°C)	less than 6°C/second
Time from 30°C to Peak temperature	no greater than 300 seconds

**Chip-mount air reflow profile**



**Tele Filter GmbH**  
**Potsdamer Straße 18**  
**D 14 513 TELTOW / Germany**  
**Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30**  
**E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.

**VI TELEFILTER****Filter specification****TFS 90B****5/5****History**

<b>Version</b>	<b>Reason of Changes</b>	<b>Name</b>	<b>Date</b>
1.0	- generation of development specification	Strehl	12.05.2006
1.1	- extend of storage temperature range	Strehl	17.05.2006
1.2	- terminating impedances, typical values, filter characteristics and matching configuration added - frequencies of input signals for intermodulation measurements corrected	Pfeiffer	29.08.2006
1.3	- temperature coefficient of frequency and typical values corrected - change of relative attenuations	Pfeiffer	31.08.2006

---

**Tele Filter GmbH**  
**Potsdamer Straße 18**  
**D 14 513 TELTOW / Germany**  
**Tel: (+49) 3328 4784-0 / Fax: (+49) 3328 4784-30**  
**E-Mail: [tft@telefilter.com](mailto:tft@telefilter.com)**

VI TELEFILTER reserves the right to make changes to the product(s) and/or information contained herein without notice. No liability is assumed as a result of their use or application. No rights under any patent accompany the sale of any such product(s) or information.