

Family



Asym degrees

92 %

Available

Available



Ordering number CA12238

Description CA12238_Strada-FW-tape

Type Lens LED MX-6

Strada-Forward

Color Transparent
Diameter 19.6+15.3 mm
Height 10.9 mm
Style Rectangular
Optic Material PMMA

Holder Material -Fastening Tape Status Ready

Ordering number C12226

Description C12226_Strada-FW

Family Strada-Forward FWHM Asym degrees

FWHM

cd/lm

Efficiency

Gerber File

Gerber File

Type Lens Efficiency 92 % LED MX-6 cd/lm -

Color Transparent
Diameter 19.6+15.3 mm
Height 10.9 mm
Style Rectangular
Optic Material PMMA
Holder Material -

Fastening Glue
Status Ready

ence will be changed by different color, chip size and chip position divergence is the full angle measured where the luminous intensity

is half of the peak value.





GENERAL INFORMATION

- Product series especially designed & optimized for MX-6 series of LEDs.
- Special care taken to make light distribution as uniform as possible.
- Lens material optical grade PMMA with high UV and temperature resistance (105 degrees of Celcius / 220 degrees of Fahrenheit). Allows use of high current and temperature conditions.

Please find more information about used material from below:

http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20UL94_Yellow%20Card.pdf http://ledil.fi/sites/default/files/Documents/Technical/Material/PMMA%208N%20PLEXIGLAS-Datasheet.pdf

- Fastening to heat sink with a PU foam adhesive tape of automotive grade. Please find fastening details by clicking link: http://www.ledil.com/datasheets/DataSheet_TAPE.pdf
- Fastening to PCB with appropriate adhesive. By clicking link below you can find Ledil recommended glue options.

http://www.ledil.com/datasheets/DataSheet GLUES.pdf

NOTE 1: We advise customer to ensure the suitability and sufficiency of the bond in the end product. For example, mechanical stress, vibration and holes on the surface of the circuit boar weaken the strength of the tape.

NOTE 2: Assembly to the surface must be made straight, so the tape bonds constant and balanced with fastening surface. Slanted assembly might cause unbalanced bond to the surface. All surfaces where tape is applied must be clean, dry and free from grease and dirt.

If cleaning of PCB surfaces is needed, please follow strictly the cleaning instructions of your LED manufacturer - this is important as cleaning shall under no circumstances damage LEDs or other electronics components on the PCB.

Further note that optical components shall not be cleaned with any chemicals - only micro fiber cloth may be used to remove fingerprints or other traces from handling.

NOTE 1: We advise customer to ensure the suitability and sufficiency of the bond in the end product. For example, mechanical stress, vibration and holes on the surface of the circuit boar weaken the strength of the glue.

NOTE 2: All surfaces where glue is applied must be clean, dry and free from grease and dirt. If cleaning of PCB surfaces is needed, please follow strictly the cleaning instructions of your LED manufacturer -this is important as cleaning shall under no circumstances damage LEDs or other electronics components on the PCB.

Further note that optical components shall not be cleaned with any chemicals - only micro fiber cloth may be used to remove fingerprints or other traces from handling.





22

19

240


200


160

120

80


Luminaire: Ledil Oy C12226_Strada-FW_N083 C12226_Strada-FW_N083 Lamps: 1 x Nichia N083 6chip white







21

Luminaire: Ledil Oy C12226_Strada-FW_N083 C12226_Strada-FW_N083 Lamps: 1 x Nichia N083 6chip white



Luminaire: Ledil Oy C12226_Strada-FW_N083 C12226_Strada-FW_N083 Lamps: 1 x Nichia N083 6chip white





October 6th 2011 23:09 Copyright Ledil Oy - Subject to change without prior notice - Page 3/8 40


Ledil Oy Salorankatu 10.00 24240 SALO η = 85% Finland C180


http://www.ledil.com email: ledil@ledil.com FAX: +358-2-733 8001





Luminaire: Ledil Oy C12086_Strada-FW-XP (XP-E) Lamps: 1 x Cree XP-E 250mA 74,8 lm







13

Finland


Luminaire: Ledil Oy C12086_Strada-FW-XP-G (XP-G) Lamps: 1 x Cree XP-G 86.9 Im @ 250mA




16 Luminaire: Ledil Oy C12086_Strada-FW-XP (XP-E) Lamps: 1 x Cree XP-E 250mA 74,8 lm



Luminaire: Ledil Oy C12086_Strada-FW-XP-G (XP-G) Lamps: 1 x Cree XP-G 86.9 lm @ 250mA





October 6th 2011 23:09 Copyright Ledil Oy - Subject to change without prior notice - Page 4/8

Ledil Oy Salorankatu 10.00 22.5° 67.5° 24240 SALO _______ c90 - c270

email: ledil@ledil.com FAX: +358-2-733 8001


http://www.ledil.com




CREE

Polar-C12086


Luminaire: Ledil Oy C12086_Strada-FW-XP (XP-E) Lamps: 1 x Cree XP-E 250mA 74,8 lm





10

Luminaire: Ledil Oy C12086_Strada-FW-XP-G (XP-G) Lamps: 1 x Cree XP-G 86.9 lm @ 250mA




22.5°


67.5°


Linear-C12086

Luminaire: Ledil Oy C12086_Strada-FW-XP (XP-E) Lamps: 1 x Cree XP-E 250mA 74,8 lm



Luminaire: Ledil Oy C12086_Strada-FW-XP-G (XP-G) Lamps: 1 x Cree XP-G 86.9 Im @ 250mA





October 6th 2011 23:09 Copyright Ledil Oy - Subject to change without prior notice - Page 5/8


Ledil Oy

Finland


http://www.ledil.com email: ledil@ledil.com FAX: +358-2-733 8001








Luminaire: Ledil Oy C12049_Strada-FT-OSL C12049_Strada-FT-OSL Lamps: 1 x LED Module




24240 SALO


Finland




Luminaire: Ledil Oy C12049_Strada-FT-OSL C12049_Strada-FT-OSL Lamps: 1 x LED Module



Luminaire: Ledil Oy C12049_Strada-FT-XP C12049_Strada-FT-XP Lamps: 1 x Cree XP-E












Luminaire: Ledil Oy C12049-Strada-FT-RE C12049-Strada-FT-RE Lamps: 1 x LAMP]Luxeon Rebel 250mA 87lm




linear


Luminaire: Ledil Oy C12049-Strada-FT-RE C12049-Strada-FT-RE Lamps: 1 x LAMP]Luxeon Rebel 250mA 87lm












Luminaire: Ledil Oy C12049_Strada-FT-OSL C12049_Strada-FT-OSL Lamps: 1 x LED Module





67.5° 22.5° cd/klm C90 - C270

http://www.ledil.com 67.5 email: ledil@ledil.com

24240 SALO_ C90 - C270 Finland

FAX: +358-2-733 8001


45.0°






polar

Luminaire: Ledil Oy C12049_Strada-FT-XP C12049_Strada-FT-XP Lamps: 1 x Cree XP-E





Linear

Luminaire: Ledil Oy C12049_Strada-FT-XP C12049_Strada-FT-XP Lamps: 1 x Cree XP-E

