

## 250 W Outdoor TWT Power Amplifier for Satellite Communications

**Ka-Band**

### The T02KO Series

250 watt peak  
power TWT  
Amplifier—  
Environmentally  
sealed compact  
design for outdoor  
operation



### Plays in the Rain

Rugged, compact and lightweight amplifier designed for outdoor use.

### Efficient and Cost Effective

Mounting at the antenna improves performance through minimized cable losses and saves cost in system design. Employs a high efficiency helix traveling wave tube, reducing operating costs.

### Simple to Operate

User-friendly microprocessor-controlled logic with integrated RS422/485 computer interface. Digital metering is standard.

### Easy to Maintain

Modular design and built-in fault diagnostic capability via remote monitor and control.

### Global Applications

Meets International Safety Standard EN-60215, Electromagnetic Compatibility 89/336/EEC and Harmonic Standard EN-61000-3-2 to satisfy worldwide requirements.

### Worldwide Support

Backed by over three decades of satellite communications experience, and CPI's worldwide 24-hour customer support network that includes fifteen regional factory Service Centers.

**satcom**  **division**

811 Hansen Way  
P.O. Box 51625, Palo Alto, CA 94303

**tel:** +1 (650) 846-3803

**fax:** +1 (650) 424-1744

**e-mail:** [marketing@satcom.cpii.com](mailto:marketing@satcom.cpii.com)  
[www.cpii.com/satcom](http://www.cpii.com/satcom)

**Ka-Band**

**250 W Outdoor TWT Power Amplifier**

## SPECIFICATIONS

### T02KO Series

#### Electrical

|  |   |
|--|---|
| Frequency  | User-specified frequency range within the 27.5 to 31.0 GHz band, as limited by bandwidth capability of amplifier <sup>1</sup> |
| Output Power                                       | 250 W (53.98 dBm) peak  |
| Average Power (TWT)                                | 120 W (50.8 dBm) or 175 W (52.4 dBm)  |
| CW Power (Flange)                                  | 100 W (50.0 dBm) or 145 W (51.6 dBm)  |
| Bandwidth  | 1000 - 2500 MHz, depending on desired frequency range <sup>1</sup>  |
| Gain   |   |
| at rated power                                     | 70 dB min.  |
| at small signal                                    | 75 dB min. (SSIPA can be removed as an option. SSG without SSIPA is 50 dB min.)   |
| RF Level Adjust Range                              | 0 to 25 dB  |
| Attenuator Step Size                               | 0.1 dB  |
| Small Signal Gain Slope                            | ±0.04 dB/MHz max.   |
| Small Signal Gain Variation                        | 1.0 dB pk-pk max. across any 40 MHz segment; 2.5 dB pk-pk max. across passband  |
| Gain Stability (at constant drive and temperature) | ± 0.25 dB/24 hours max. (after 30 minute warm-up)<br>±1.0 dB over temperature range   |
| VSWR   |   |
| Input  | 1.3:1   |
| Output   | 1.3:1   |
| Load   | 1.5:1 max. full spec. compliance; 2.0:1 max. continuous; any value for operation without damage                               |
| Phase Noise  | 12 dB below IESS 308 continuous mask  |
| AM/PM Conversion                                   | 2.5° /dB max. for a single carrier up to 6 dB OBO(1.0°/dB max. up to 3 dB OBO with optional linearizer)                       |
| Noise Power Density                                | <-150 dBW/4 kHz, below 21.2 GHz<br><-70 dBW/4 kHz, transmit band (<-65 dBW/4 kHz, transmit band with linearizer)              |
| Noise Figure                                       | 10 dB max. (12 dB max. with linearizer)   |
| Intermodulation                                    | -23 dBc or better with 2 equal carriers at total power level 50 W or 72.5 W CW (100 W or 140 W with linearizer)               |
| Group Delay  | In any 40 MHz band  |
| Linear   | 0.01 nsec/MHz max.  |
| Parabolic  | 0.001 nsec/MHz sq. max.   |
| Ripple   | 0.5 nsec pk-pk max.   |
| Primary Power                                      | 100-240 VAC ±10%, single phase, 47-63 Hz  |
| Power Consumption                                  | 800 VA max., 650 VA typ.  |
| Power Factor                                       | 0.95 min.   |

#### Environmental (operating)

|                     |   |
|---------------------|---|
| Ambient Temperature | -40° to +60° C, with extra margin for solar loading             |
| Relative Humidity   | 100% condensing   |
| Altitude            | 10,000 ft with standard adiabatic derating of 2° C/1000 ft      |
| Shock and Vibration | 20 g pk, 11 msec, 1/2 sine / 2.1 g <sub>rms</sub> , 5 to 500 Hz |

#### Mechanical

|                      |  |
|----------------------|--|
| Cooling              | Forced air with integral blower              |
| RF Input Connection  | WR-28F                                       |
| RF Output Connection | WR-34G (WR-28G optional)                     |
| RF Output Monitor    | 2.9 mm SMA Female                            |
| Dimensions (WxHxD)   | 10.25 x 9.5 x 20 inches (261 x 242 x 508 mm) |
| Weight               | 52 lbs. (23.6 kg) max.                       |

#### Heat and Acoustic

|                  |   |
|------------------|---|
| Heat Dissipation | 500 W max.                                    |
| Acoustic         | 65 dBA typ. (as measured at 3 feet from unit) |

**Note 1:** Please consult CPI representative to confirm that desired bandwidth is available over desired frequency range.

Mounting hardware is provided with each amplifier.

#### OPTIONS:

- 1 RU Remote Control Panel
- Internal Switch Control and Drive
- Redundant or Power Combined Subsystems
- Integral Linearized Solid State IPA (LIPA)
- Integral Block Upconverter (refer to T02KO B-Series TWTA)
- Ethernet Interface



**KEEPING YOU ON THE AIR**  
not up in the air



For more detailed information, please refer to the corresponding CPI Technical Description.

**Note:** Specifications may change without notice as a result of additional data or product refinement.

Please contact CPI before using this information for system design.

**satcom** division