


SWITCHING TYPE POWER SUPPLY APPLICATION.  
CONVERTER & CHOPPER APPLICATION.

### FEATURES

- Average Output Rectified Current  
:  $I_O=5A$  ( $T_c=115^\circ C$ ).
- Repetitive Peak Reverse Voltage  
:  $V_{RRM}=60V$ .
- Fast Reverse Recovery Time :  $t_{rr}=35ns$ .
- Low Peak Forward Voltage :  $0.50V(Typ.)$

### MAXIMUM RATING ( $T_a=25^\circ C$ )

CHARACTERISTIC	SYMBOL	RATING	UNIT
Repetitive Peak Reverse Voltage	$V_{RRM}$	60	V
Average Output Rectified Current ( $T_c=115^\circ C$ )	$I_O$	5	A
Peak One Cycle Surge Forward Current (Non-Repetitive 60Hz)	$I_{FSM}$	100	A
Junction Temperature	$T_j$	-40 ~ 150	$^\circ C$
Storage Temperature Range	$T_{stg}$	-55 ~ 150	$^\circ C$




### ELECTRICAL CHARACTERISTICS ( $T_a=25^\circ C$ )


CHARACTERISTIC	SYMBOL	TEST CONDITION	MIN.	TYP.	MAX.	UNIT
Peak Forward Voltage	$V_{FM}$	$I_{FM}=5A, T_c=25^\circ C$	-	0.50	0.55	V
Repetitive Peak Reverse Current	$I_{RRM}$	$V_{RRM}=\text{Rated}$	-	-	0.5	mA
Reverse Recovery Time	$t_{rr}$	$I_F=1.0A, di/dt=-20A/\mu s$	-	-	35	ns
Thermal Resistance	$R_{th(j-c)}$	Juction to Case	-	-	4.5	$^\circ C/W$

# B5A60VI


$I_F - V_F$




$I_R - V_R$



CURRENT DERATING (CASE)



CURRENT DERATING (AMBIENT)



$P_{F(AV)} - I_{F(AV)}$

