



SILICON EXPITAXIAL SCHOTTKY BARRIER DIODES

FEATURES

- * Low Forward Voltage Drop
- * Flat Lead SOD-523 Small Outline Plastic Package
- * Surface Device Type Mounting
- * Moisture Sensitivity Level 1
- * Clip Bonding Construction, Good Thermal Capability
- * Pb Free Version and ROHS Compliant
- * Matte Tin(Sn) Lead Finish with Nicke(Ni) Underplate
- * Band Indicates Cathode
- * Ultra Small Mold Type, Low Forward Voltage, High Reliability



SOD-323



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.
resistive or inductive load.

Absolute Maximum Ratings (@ TA=25 °C unless otherwise noted)

RATINGS	SYMBOL	RB521S-40	UNITS
Repetitive Peak Reverse Voltage	V _R RRM	45	Volts
Continuous Reverse Voltage	V _R	40	Volts
Mean Rectifying Current	I _O	200	mAmps
Peak Forward Surge Current(60 Hz or Cyc.)	I _{FSM}	1	Amps
Junction Temperature	T _J	150	°C
Operating and Storage Junction Temperature	T _{STG}	-55 to + 150	°C

ELECTRICAL CHARACTERISTICS (@TA=25 °C unless otherwise noted)

CHARACTERISTICS	SYMBOL	MIN	TYP	MAX	UNITS	
Forward Voltage	V _F	@I _F =10mA	0.16	-	0.30	Volts
		@I _F =100mA	0.31	-	0.45	
		@I _F =200mA	0.41	-	0.54	
Reverse Voltage Leakage Current	I _R	@V _R =10V	-	-	20	uAmps
		@V _R =40V	-	-	90	

Note: "Fully ROHS Compliant", "100% Sn Plating (Pb-free)".

VD 2010-01
REV:O

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.