


High-Reliability Chip Inductors ML312RAA


Small size, exceptional Q and high SRFs make these inductors ideal for high frequency applications where size is at a premium. They also have excellent DCR and current carrying characteristics.

This robust version of Coilcraft's standard 0603CS series features high temperature materials that allow operation in ambient temperatures up to 155°C.



Typical L vs Frequency



Typical Q vs Frequency



Current Derating



A max	B max	C max	D ref	E	F	G	H	I	J
0.071	0.044	0.040	0.015	0.030	0.013	0.034	0.040	0.025	0.025
1,80	1,12	1,02	0,38	0,76	0,33	0,86	1,02	0,64	0,64

Core material Ceramic

Terminations Silver-palladium-platinum-glass frit

Ambient temperature -55°C to +125°C with I_{max} current, +125°C to +155°C with derated current

Storage temperature Component: -55°C to +155°C. Packaging: -55°C to +80°C

Resistance to soldering heat Max three 40 second reflows at +260°C, parts cooled to room temperature between cycles

Temperature Coefficient of Inductance (TCL) +25 to +155 ppm/°C

Moisture Sensitivity Level (MSL) 1 (unlimited floor life at <30°C / 85% relative humidity)

Enhanced crush-resistant packaging 2000 per 7" reel
Paper tape: 8 mm wide, 1.0 mm thick, 4 mm pocket spacing



1102 Silver Lake Road
Cary, IL 60013
Phone 800-981-0363

Fax 847-639-1508
Email cps@coilcraft.com
www.coilcraft-cps.com

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specifications subject to change without notice. Please check our web site for latest information.

ML312RAA Series (0603)

Part number ¹	Inductance ² (nH)	Percent tolerance	Q min ³	900 MHz		1.7 GHz		SRF min ⁴ (MHz)	DCR max ⁵ (Ohms)	Imax (mA)	Color code
				L typ	Q typ	L typ	Q typ				
ML312RAA1N6JLZ	1.6 @ 250 MHz	5	26	1.67	49	1.65	63	>5000	0.022	700	Red
ML312RAA1N8JLZ	1.8 @ 250 MHz	5	21	1.83	35	1.86	50	>5000	0.045	700	Black
ML312RAA3N3_LZ	3.3 @ 250 MHz	5,2	35	3.31	75	3.38	88	>5000	0.045	700	Blue
ML312RAA3N6_LZ	3.6 @ 250 MHz	5,2	18	3.72	53	3.71	65	>5000	0.063	700	Red
ML312RAA3N9_LZ	3.9 @ 250 MHz	5,2	20	3.95	49	3.96	67	>5000	0.080	700	Brown
ML312RAA4N3_LZ	4.3 @ 250 MHz	5,2	29	4.32	50	4.33	70	>5000	0.063	700	Orange
ML312RAA4N7_LZ	4.7 @ 250 MHz	5,2	18	4.72	47	4.75	57	>5000	0.116	605	Violet
ML312RAA5N1_LZ	5.1 @ 250 MHz	5,2	20	4.93	47	4.95	56	>5000	0.140	510	Green
ML312RAA5N6_LZ	5.6 @ 250 MHz	5,2,1	25	5.77	63	6.05	80	4760	0.075	700	Black
ML312RAA6N8_LZ	6.8 @ 250 MHz	5,2,1	28	6.75	60	7.10	81	4660	0.110	700	Red
ML312RAA7N5_LZ	7.5 @ 250 MHz	5,2,1	23	7.70	60	7.82	65	4320	0.106	700	Brown
ML312RAA8N2_LZ	8.2 @ 250 MHz	5,2,1	26	8.25	82	8.37	87	3880	0.115	700	Orange
ML312RAA8N7_LZ	8.7 @ 250 MHz	5,2,1	27	8.86	62	9.32	58	3680	0.109	700	Yellow
ML312RAA9N5_LZ	9.5 @ 250 MHz	5,2,1	22	9.70	59	9.92	61	4100	0.135	700	Blue
ML312RAA10N_LZ	10 @ 250 MHz	5,2,1	28	10.0	66	10.6	83	3860	0.130	700	Orange
ML312RAA11N_LZ	11 @ 250 MHz	5,2,1	26	11.0	53	11.5	56	3640	0.130	700	Gray
ML312RAA12N_LZ	12 @ 250 MHz	5,2,1	29	12.3	72	13.5	83	3220	0.130	620	Yellow
ML312RAA15N_LZ	15 @ 250 MHz	5,2,1	28	15.4	64	16.8	89	3020	0.170	600	Green
ML312RAA16N_LZ	16 @ 250 MHz	5,2,1	29	16.2	55	17.3	52	3040	0.170	600	White
ML312RAA18N_LZ	18 @ 250 MHz	5,2,1	29	18.7	70	21.4	69	2680	0.170	600	Blue
ML312RAA22N_LZ	22 @ 250 MHz	5,2,1	31	22.8	73	26.1	71	2380	0.190	560	Violet
ML312RAA23N_LZ	23 @ 250 MHz	5,2,1	39	24.1	71	28.0	67	2380	0.190	560	Orange
ML312RAA24N_LZ	24 @ 250 MHz	5,2,1	36	24.5	45	28.7	39	2380	0.190	560	Black
ML312RAA27N_LZ	27 @ 250 MHz	5,2,1	32	29.2	74	34.6	65	2380	0.220	530	Gray
ML312RAA30N_LZ	30 @ 250 MHz	5,2,1	32	31.4	47	39.9	28	2240	0.220	500	Brown
ML312RAA33N_LZ	33 @ 250 MHz	5,2,1	33	36.0	67	49.5	42	1900	0.220	500	White
ML312RAA36N_LZ	36 @ 250 MHz	5,2,1	32	39.4	47	52.7	24	1960	0.250	460	Red
ML312RAA39N_LZ	39 @ 250 MHz	5,2,1	36	42.7	60	60.2	40	1740	0.250	460	Black
ML312RAA43N_LZ	43 @ 250 MHz	5,2,1	28	47.0	44	64.9	21	1580	0.280	440	Orange
ML312RAA47N_LZ	47 @ 200 MHz	5,2,1	35	52.2	62	77.2	35	1560	0.280	440	Brown
ML312RAA51N_LZ	51 @ 200 MHz	5,2,1	38	55.5	69	82.2	34	1560	0.270	420	Blue
ML312RAA56N_LZ	56 @ 200 MHz	5,2,1	37	62.5	56	97.0	26	1480	0.310	420	Red
ML312RAA68N_LZ	68 @ 200 MHz	5,2,1	35	80.5	54	168	21	1380	0.340	410	Orange
ML312RAA72N_LZ	72 @ 150 MHz	5,2,1	35	82.0	53	135	20	1360	0.490	340	Yellow
ML312RAA82N_LZ	82 @ 150 MHz	5,2,1	29	96.2	54	177	21	1300	0.540	340	Green
ML312RAAR10_LZ	100 @ 150 MHz	5,2,1	28	124	49	—	—	1140	0.580	310	Blue
ML312RAAR11_LZ	110 @ 150 MHz	5,2,1	30	138	43	—	—	1080	0.610	310	Violet
ML312RAAR12_LZ	120 @ 150 MHz	5,2,1	28	166	39	—	—	1020	0.650	270	Gray
ML312RAAR15_LZ	150 @ 150 MHz	5,2,1	28	250	25	—	—	900	0.915	250	White
ML312RAAR18_LZ	180 @ 100 MHz	5,2,1	25	305	22	—	—	820	1.25	210	Black

1. When ordering, please specify **tolerance** and **testing** codes:

ML312RAAR39JLZ

Tolerance: F = 1% G = 2% J = 5%

Testing: Z = COTS

H = Screening per Coilcraft CP-SA-10001

N = Screening per Coilcraft CP-SA-10003

2. Inductance measured at 250 MHz using a Coilcraft SMD-A test fixture and Coilcraft-provided correlation pieces with an Agilent/HP 4286A impedance analyzer or equivalent.

3. Q measured at the same frequency as inductance using an Agilent/HP 4291A with an Agilent/HP 16197A test fixture or equivalents.

4. SRF measured using an Agilent/HP 8753ES network analyzer and a Coilcraft CCF1232 test fixture.

5. DCR measured on a Keithley 580 micro-ohmmeter and a Coilcraft CCF1010 test fixture.

6. Electrical specifications at 25°C.

Refer to Doc 362 "Soldering Surface Mount Components" before soldering.



CRITICAL PRODUCTS & SERVICES

1102 Silver Lake Road
Cary, IL 60013
Phone 800-981-0363

Fax 847-639-1508
Email cps@coilcraft.com
www.coilcraft-cps.com

Document ML195-2 Revised 11/06/12

This product may not be used in medical or high risk applications without prior Coilcraft approval. Specifications subject to change without notice. Please check our web site for latest information.