

BIF5

5-800 MHz Internally Matched IF Amplifier



Device Features

- OIP3 = 43.0 dBm @ 70 MHz
- Gain = 17.5 dB @ 70 MHz
- Output P1 dB = 20.5 dBm @ 70 MHz
- 50 Ω Cascadable
- Patented temperature compensation
- Patented over voltage protection
- Lead-free/RoHS-compliant SOT-89 SMT package




Product Description

BeRex's BIF5 is a high performance InGaP/ GaAs HBT MMIC amplifier, internally matched to 50 Ohms and uses a patented **temperature compensation** circuit to provide stable current over the operating temperature range without the need for external components and a patented **over voltage protection** circuit to protect a internal device. The BIF5 is designed for high linearity IF amplifier that requires excellent gain, high OIP3 and flatness. It is packaged in a RoHS-compliant with SOT-89 surface mount package.

Applications

- Base station Infrastructure/RFID
- Commercial/Industrial/Military wireless system

Applications Circuit



*C1, C2=100nF ± 5%; C3 = 100 pF ± 5%; C4 = 1000pF ±5%

*C5 = 10uF; L1 = 1uH ±5%

*C1, C2 = 100pF; L1 = 33nH ±5% for RF Bandwidth

Typical Performance¹

Parameter	Frequency					Unit
	70	140	250	500	800	
Gain	17.5	17.5	17.5	17.5	17.1	dB
S11	-15.8	-15.4	-15.5	-14.1	-18.3	dB
S22	-17.1	-19.1	-26.3	-16.1	-10.8	dB
OIP3 ²	43.0	42.5	41.0	40.0	37.0	dBm
P1dB	20.5	20.5	20.5	21.0	21.0	dBm
Noise Figure	4.0	4.1	4.2	4.3	4.3	dB

¹ Device performance _ measured on a BeRex evaluation board at 25°C, 50 Ω system.

² OIP3 _ measured with two tones at an output of 10 dBm per tone separated by 1 MHz.

	Min.	Typical	Max.	Unit
Bandwidth	5		800	MHz
I _c @ (V _c = 5V)	97	107	117	mA
V _c		5.0		V
dG/dT		-0.003		dB/°C
R _{TH}		50		°C/W

Absolute Maximum Ratings

Parameter	Rating	Unit
Operating Case Temperature	-40 to +85	°C
Storage Temperature	-55 to +155	°C
Junction Temperature	+220	°C
Operating Voltage	+6.0	V
Supply Current	160	mA
Input RF Power	23	dBm


Operation of this device above any of these parameters may result in permanent damage.

BIF5


5-800 MHz Internally Matched IF Amplifier



V-I Characteristics




BeRex SOT89 Evaluation Board



*Dielectric constant _ 4.2 *RF pattern width 52mil *31mil thick FR4 PCB

Typical Device Data

S-parameters (Vc=5V, Ic=107mA, T=25°C)




BIF5

5-800 MHz Internally Matched IF Amplifier



RF Bandwidth

S-parameters (Vc=5V, Ic=107mA, T=25°C)



BIF5



5-800 MHz Internally Matched IF Amplifier

S-Parameter

(V_{device} = 5.0V, I_{cc} = 107mA, T = 25 °C, calibrated to device leads)

Freq [MHz]	S11 [Mag]	S11 [Ang]	S21 [Mag]	S21 [Ang]	S12 [Mag]	S12 [Ang]	S22 [Mag]	S22 [Ang]
100	0.635	175.5	8.232	175.6	0.066	0.3	0.155	-12.0
500	0.627	157.0	7.315	159.7	0.072	-1.4	0.178	-62.9
1000	0.603	136.7	7.880	144.7	0.066	-1.8	0.235	-111.5
1500	0.580	118.0	6.733	131.1	0.070	2.4	0.322	-151.7
2000	0.491	99.4	6.895	114.4	0.069	-1.7	0.393	175.7
2500	0.471	86.3	6.953	104.4	0.071	5.1	0.470	147.9
3000	0.432	69.7	8.427	80.7	0.080	-0.9	0.549	119.3
3500	0.415	63.8	7.474	53.8	0.079	-0.9	0.608	97.8
4000	0.457	51.4	6.617	32.7	0.090	-8.8	0.640	68.7

Typical Performance (V_d = 5V, I_c = 107mA, T = 25°C)

Freq	MHz	70	140	250	*500	800
S21	dB	17.5	17.5	17.5	17.5	17.1
S11	dB	-15.8	-15.4	-15.5	-14.1	-18.3
S22	dB	-17.1	-19.1	-26.3	-16.1	-10.8
P1	dBm	20.5	20.5	20.5	21.0	21
OIP3	dBm	43	42.5	41.0	40.0	37
NF	dB	4.0	4.1	4.2	4.3	4.3

Typical Performance (V_d = 4.7V, I_c = 95mA, T = 25°C)

Freq	MHz	70	140	250	500	800
S21	dB	17.6	17.5	17.4	17.4	17.1
S11	dB	-15.1	-17.3	-18.1	-17.5	-18.7
S22	dB	-14.3	-13.7	-14.1	-14	-10.7
P1	dBm	19.6	20.2	20.1	20.4	20
OIP3	dBm	41	40.5	39.5	37	35.5
NF	dB	4.0	4.1	4.2	4.3	4.3

Typical Performance (V_d = 4.5V, I_c = 85mA, T = 25°C)

Freq	MHz	70	140	250	500	800
S21	dB	17.4	17.4	17.5	17.4	17
S11	dB	-15.3	-17.6	-18.3	-17.8	-18.9
S22	dB	-14.2	-13.5	-13.9	-13.9	-10.6
P1	dBm	19.2	19.0	19.2	19.4	19.4
OIP3	dBm	40.0	41.0	38.5	36.5	35
NF	dB	4.0	4.1	4.2	4.3	4.3

BIF5



5-800 MHz Internally Matched IF Amplifier

Typical Performance (Vd = 4V, Ic = 63mA, T = 25°C)

Freq	MHz	70	140	250	500	800
S21	dB	17.4	17.3	17.2	17.2	16.9
S11	dB	-16	-18.6	-19.5	-18.9	-20.1
S22	dB	-13.8	-13.1	-13.5	-13.5	-10.3
P1	dBm	17	17.5	17.7	17.5	17.2
OIP3	dBm	35.5	35.5	35	33	32
NF	dB	4.0	4.1	4.2	4.3	4.3

Typical Performance (Vd = 3.5V, Ic = 41mA, T = 25°C)

Freq	MHz	70	140	250	500	800
S21	dB	17.1	17.0	16.9	16.8	16.5
S11	dB	-17.9	-21.2	-22.6	-21.7	-23.1
S22	dB	-13.1	-12.3	-12.6	-12.6	-9.8
P1	dBm	13.7	14.6	14.6	14.5	14.2
OIP3	dBm	29	29	29	27.5	27.5
NF	dB	4.0	4.1	4.2	4.3	4.3


BIF5

5-800 MHz Internally Matched IF Amplifier




Device Performance


Pin-Pout-Gain




70MHz, 5V/107mA




140MHz, 5V/107mA




250MHz, 5V/107mA



500MHz, 5V/107mA



900MHz, 5V/107mA








BIF5

5-800 MHz Internally Matched IF Amplifier



OIP3








BIF5

5-800 MHz Internally Matched IF Amplifier



ACPR




BIF5





5-800 MHz Internally Matched IF Amplifier



ACLR



S-Parameters over Temperature




BIF5

5-800 MHz Internally Matched IF Amplifier



Package Outline Dimension




- NOTE:**
1. DIMENSIONS IN MILLIMETERS.
- ⚠ DIMENSION D DOES NOT INCLUDE MOLD FLASH, PROTRUSIONS OR GATE BURRS. MOLD FLASH, PROTRUSIONS OR GATE BURRS SHALL NOT EXCEED 0.5mm PER END. DIMENSION E1 DOES NOT INCLUDE INTERLEAD FLASH OR PROTRUSION. INTERLEAD FLASH OR PROTRUSION SHALL NOT EXCEED 0.5mm PER SIDE.
 - ⚠ DIMENSIONS D AND E1 ARE DETERMINED AT THE OUTMOST EXTREMES OF THE PLASTIC BODY EXCLUSIVE OF MOLD FLASH, TIE BAR BURRS, GATE BURRS AND INTERLEAD FLASH, BUT INCLUDING ANY MISMATCH BETWEEN THE TOP AND BOTTOM OF THE PLASTIC BODY.
 - ⚠ DATUMS A, B AND D TO BE DETERMINED 0.18mm FROM THE LEAD TIP.
 - ⚠ TERMINAL NUMBERS ARE SHOWN FOR REFERENCE ONLY.

SYMBOL	MILLIMETERS			NOTE
	MINIMUM	NOMINAL	MAXIMUM	
A	1.40	1.50	1.60	
A1	0.00	—	0.10	
b	0.38	0.42	0.48	
b1	0.48	0.52	0.58	
b2	1.79	1.82	1.87	
c	0.40	0.42	0.46	
D	4.40	4.50	4.70	2,3
E	3.70	4.00	4.30	
E1	2.40	2.50	2.70	2,3
E2	0.80	1.00	1.20	
E3	0.40	0.50	0.60	
e	1.50 TYP.			
φ	4° TYP.			
R	0.15 TYP.			
R1	—	—	0.20	
SYMBOL	TOLERANCES OF FORM AND POSITION		NOTE	
aaa	0.15			
bbb	0.20			
ccc	0.10			
ddd	0.10			

Suggested PCB Land Pattern and PAD Layout


PCB Land Pattern



Note : All dimension _ millimeters

PCB lay out _ on BeRex website

PCB Mounting




BIF5

5-800 MHz Internally Matched IF Amplifier



Tape & Reel



Packaging information:

Tape Width (mm): 12

Reel Size (inches): 7

Device Cavity Pitch (mm): 8

Devices Per Reel: 1000

Lead plating finish

100% Tin Matte finish

(All BeRex products undergoes a 1 hour, 150 degree C, Anneal bake to eliminate thin whisker growth concerns.)

MSL / ESD Rating

ESD Rating:	Class 1C
Value:	Passes <2000V
Test:	Human Body Model (HBM)
Standard:	JEDEC Standard JESD22-A114B
MSL Rating:	Level 1 at +265°C convection reflow
Standard:	JEDEC Standard J-STD-020

NATO CAGE code:

2	N	9	6	F
---	---	---	---	---