

IS3020
IS3021,IS3022



OPTICALLY COUPLED BILATERAL SWITCH NON-ZERO CROSSING TRIAC

DESCRIPTION


The IS3020, IS3021 and IS3022 are optically coupled isolators consisting of a Gallium Arsenide infrared emitting diode coupled with a light activated silicon bilateral switch performing the functions of a triac mounted in a standard 6 pin dual-in-line package.

FEATURE

- Options :-
10mm lead spread - add G after part no.
Surface mount - add SM after part no.
Tape&reel - add SMT&R after part no.
- High Isolation Voltage ($5.3\text{kV}_{\text{RMS}}, 7.5\text{kV}_{\text{PK}}$)
- 400V Peak Blocking Voltage
- All electrical parameters 100% tested
- Custom electrical selections available

APPLICATIONS

- CRTs
- Power Triac Driver
- Motors
- Consumer appliances
- Printers



ABSOLUTE MAXIMUM RATINGS (25 °C unless otherwise noted)

Storage Temperature	-40°C - +150°C
Operating Temperature	-40°C - +100°C
Lead Soldering Temperature	260°C (1.6mm from case for 10 seconds)
Input-to-output Isolation Voltage (Pk)	7500 Vac (60 Hz, 1sec. duration)

INPUT DIODE


Forward Current	50mA
Reverse Voltage	6V
Power Dissipation	70mW (derate linearly 1.33mW/°C above 25°C)

OUTPUT PHOTO TRIAC

Off-State Output Terminal Voltage	400V
Forward Current (Peak)	1A
Power Dissipation	300mW (derate linearly 4.0mW/°C above 25°C)

POWERDISSIPATION

Total Power Dissipation	330mW (derate linearly 4.4mW/°C above 25°C)
-------------------------	--



ISOCOM COMPONENTS LTD
Unit 25B, Park View Road West,
Park View Industrial Estate, Brenda Road
Hartlepool, Cleveland, TS25 1YD
Tel: (01429) 863609 Fax : (01429) 863581

ISOCOM INC
1024 S. Greenville Ave, Suite 240,
Allen, TX 75002 USA
Tel: (214) 495-0755 Fax: (214) 495-0901
e-mail info@isocom.com
<http://www.isocom.com>

ELECTRICAL CHARACTERISTICS ($T_A = 25^\circ\text{C}$ Unless otherwise noted)

PARAMETER		MIN	TYP	MAX	UNITS	TEST CONDITION
Input	Forward Voltage (V_F) Reverse Current (I_R)		1.2 100	1.5 μA	V μA	$I_F = 10\text{mA}$ $V_R = 6\text{V}$
Output	Peak Off-state Current (I_{DRM}) Peak Blocking Voltage (V_{DRM}) On-state Voltage (V_{TM}) Critical rate of rise of off-state Voltage (dv/dt) (note 1) Critical rate of rise of commutating Voltage (dv/dt) (note 1)	400	1.5	100 3.0	nA V V	$V_{DRM} = 400\text{V}$ (note 1) $I_{DRM} = 100\text{nA}$ $I_{TM} = 100\text{mA}$ (peak)
Coupled	Input Current to Trigger (I_{FT}) (note 2) IS3020 IS3021 IS3022 Holding Current , either direction (I_H) Input to Output Isolation Voltage V_{ISO}			10	V/ μs μs	I load = 15mA, $V_{IN} = 30\text{V}$ (fig 1.)
				30 15 10	mA mA mA	$V_D = 3\text{V}$ (note 2)
		5300 7500	100		V_{RMS} V_{PK}	See note 3 See note 3

Note 1. Test voltage must be applied within dv/dt rating.

Note 2. Guaranteed to trigger at an I_F value less than or equal to max. I_{FT} , recommended I_F lies between Rated I_{FT} and absolute max. I_{FT} .

Note 3. Measured with input leads shorted together and output leads shorted together.

FIGURE 1

