



- NOTES:
- FOR USE WITH BOEING BMS13-65 OF & ADAMS RUSSELL FC14Z CABLES.
 - FOR CABLING INSTRUCTIONS SEE 3-546-1.
 - FOR CRIMPING USE DIE KTH-2161.
 - INTERFACE PER MIL-STD-348, FIG. 313-2.
 - CENTER CONTACT (1-3999-4MA9) SUPPLIED UNASSEMBLED.
 - MARK PACKAGE: KINGS 122-37-9 (DATE CODE)
 - MATERIALS:
 - K-GRIP SLEEVE: COMMERCIAL BRONZE, ASTM B135
 - INSULATOR: TEFLON, ASTM-D-1710
 - CENTER CONTACT: BER. COPPER, ASTM-B-196
 - GASKET: SILICONE RUBBER, A-A-59588
 - LOCKWASHER: PHOSPHOR BRONZE, ASTM B103
 - ALL OTHER METAL PARTS: BRASS, ASTM-B16
 - FINISHES:
 - CENTER CONTACT: .000050 MIN GOLD PLATE, PER ASTM-B-488 OVER .000050 MIN. NICKEL PER AMS-QQ-N-290 (RoHS)
 - ALL OTHER METAL PARTS: .000050 MIN NICKEL PER AMS-QQ-N-290 OVER .000050 MIN COPPER PER ASTM B734 (RoHS)
 - ELECTRICAL CHARACTERISTICS:
 - NOMINAL IMPEDANCE: 50 OHMS
 - WORKING VOLTAGE: 500 VRMS
 - FREQUENCY RANGE: DC TO 11 GHz
 - WEIGHT: 21.1 GRAMS

122-37-9

REVISIONS

ISSUE	CHANGES
1	CN 34557 A KH 05/05/93
2	CN 35536 A KVH 04/26/94
D	REVISED PER DMF304 & ER33954 CY 07/18/11

CUSTOMER SALES DRAWING

THIS DRAWING, THE DESIGNS AND IDEAS EMBODIED IN THE DEVICE TO WHICH IT RELATES, AND THE METHOD OF PRODUCING THE DEVICE, ARE THE PROPERTY OF WINCHESTER ELECTRONICS CORPORATION AND SHALL NOT BE EMPLOYED, COPIED, OR DISCLOSED TO ANYONE, IN ANY MANNER WITHOUT THE CONSENT OF WINCHESTER ELECTRONICS CORPORATION.

SCALE 4:1

APPROX SURFACE AREA

WAS: E-17825

CAGE CODE: 91836

REF: BOEING

JACK, BULKHEAD, TNC

DRAWN JCA	DATE 01/27/93
DESIGN JT	DATE 01/28/93
APPR.	DATE

KINGS
by WINCHESTER ELECTRONICS

Winchester Electronics
82 Barnes Industrial
Road North
Wallingford, CT 06492

B
SIZE

122-37-9