


# NAIS

COMPACT ECONOMICAL  
POWER RELAYS

# JE-X RELAYS




mm inch

**UL File No.: E43028**  
**CSA File No.: LR26550**


- Compact size - Height Max. 18.7 mm .736 inch lower than JY relay (22.5 mm) (.886 inch)
- High contact capacity — 5A 125 V AC
- Safety-oriented between coil and contact terminals
- All plastic materials: UL flame retardance 94V-0

## TERMINAL LAYOUT

Distance of 9.16 mm .360 inch between common and coil terminals and 8.9 mm .350 inch between contacts give room to the land diameter width when the relay is mounted on PC board, and allow design of patterns with insulation distances of 6 mm .236 inch between common and coil and 5.9 mm .232 inch between contacts.



- 3 mm .118 inch or more insulation distance for close mounting can be kept easily with JE-X relays.



## SPECIFICATIONS

### Contact

Arrangement	1 Form A	1 Form C
Initial contact resistance, max. (By voltage drop 6 V DC 1A)	100 mΩ	
Contact material	Silver alloy	
Rating (resistive load)	Nominal switching capacity	5 A 30 V DC, 5 A 125 V AC, 3A 250 V AC
	Max. switching power	750 VA, 150 W
	Max. switching voltage	250 V AC, 30 V DC
	Max. switching current	3A (AC) 5 A (DC)
UL/CSA rating	3 A, 1/10 HP 277 V AC 5 A, 1/10 HP 125 V AC 5 A 30 V DC	
VDE rating	5 A 125 V ~ (cosφ = 0.4)	
Expected life (min. operations)	Mechanical (at 180 cpm)	5×10 <sup>6</sup>
	Electrical (at 20 cpm) (at rated load)	10 <sup>5</sup>

### Coil

Minimum operating power	256 mW (196 mW for JE1aXN, JE1XN)
Nominal operating power	400 mW

### Remarks

- \*1 Measurement at same location as "Initial breakdown voltage" section
- \*2 Detection current: 10 mA
- \*3 Wave is standard shock voltage of ±1.2 × 50μs according to JEC-212-1981
- \*4 Excluding contact bounce time
- \*5 Half-wave pulse of sine wave: 6ms; detection time: 10μs
- \*6 Half-wave pulse of sine wave: 6ms
- \*7 Detection time: 10μs
- \*8 Refer to 5. Conditions for operation, transport and storage mentioned in AMBIENT ENVIRONMENT (Page 49)


### Characteristics (at 25°C 77°F)

Max. operating speed	20 cpm (at 70°C)	
Initial insulation resistance*1	Min. 100 MΩ (at 500 V DC)	
Initial breakdown voltage*2	Between open contacts	750 Vrms
	Between contacts and coil	1,500 Vrms
Surge voltage between coil and contact*3	Min. 5,000 V	
Operate time*4 (at nominal voltage)	Approx. 10 ms	
Release time(without diode)*4 (at nominal voltage)	Approx. 2 ms	
Temperature rise (at 70°C)	Max. 45°C with nominal coil voltage and at nominal switching capacity	
Shock resistance	Functional*5	Min. 98 m/s <sup>2</sup> {10 G}
	Destructive*6	Min. 980 m/s <sup>2</sup> {100 G}
Vibration resistance	Functional*7	98 m/s <sup>2</sup> {10 G}, 10 to 55 Hz at double amplitude of 1.6 mm
	Destructive	117.6 m/s <sup>2</sup> {12 G}, 10 to 55 Hz at double amplitude of 2.0 mm
Conditions for operation, transport and storage*8 (Not freezing and condensing at low temperature)	Ambient temp.	-40°C to +70°C -40°F to +158°F
	Humidity	5 to 85% R.H.
Unit weight	Approx. 9.2g .32 oz	

**TYPICAL APPLICATIONS**

- Home appliances  
Oven, range, dryer, heater,  
Air conditioner etc.
- Automotive
- Garage door opener
- Personal computer
- Programmable controller

**TYPICAL APPLICATIONS**



(Note) Standard packing: Carton 100 pcs. Case 500 pcs.


**TYPES**

Contact arrangement	Coil voltage	Pick-up 70% V type	
		Standard type	Flux-resistant type
1 Form A	5 V DC	JE1aXN-DC5V	JE1aXN-DC5V-H
	6 V DC	JE1aXN-DC6V	JE1aXN-DC6V-H
	9 V DC	JE1aXN-DC9V	JE1aXN-DC9V-H
	12 V DC	JE1aXN-DC12V	JE1aXN-DC12V-H
	24 V DC	JE1aXN-DC24V	JE1aXN-DC24V-H
	48 V DC	JE1aXN-DC48V	JE1aXN-DC48V-H
1 Form C	5 V DC	JE1XN-DC5V	JE1XN-DC5V-H
	6 V DC	JE1XN-DC6V	JE1XN-DC6V-H
	9 V DC	JE1XN-DC9V	JE1XN-DC9V-H
	12 V DC	JE1XN-DC12V	JE1XN-DC12V-H
	24 V DC	JE1XN-DC24V	JE1XN-DC24V-H
	48 V DC	JE1XN-DC48V	JE1XN-DC48V-H

**COIL DATA** at 20°C 68°F


Nominal voltage, V DC	Pick-up voltage, V DC (max.)	Drop-out voltage, V DC (min.)	Nominal operating current, mA (±10%)	Coil resistance, W (±10%)	Nominal operating power, mW	Maximum allowable voltage, V DC (at 70°C)
5	3.5	0.5	80	62.5	400	6.5
6	4.2	0.6	67	90	400	7.8
9	6.3	0.9	44	202	400	11.7
12	8.4	1.2	33	360	400	15.6
24	16.8	2.4	17	1,440	400	31.2
48	33.6	4.8	8.3	5,760	400	62.4

**DIMENSIONS**




mm inch

PC board pattern (Copper-side view)



Tolerance: ±0.1 ±.004

Schematic (BOTTOM VIEW)




Note: The above shows 1 form C type, and No. 5 terminal is eliminated on the 1 form A type.

Dimension	General tolerance
Max. 1mm .039 inch	±0.1 ±.004
1 to 3mm .039 to .118 inch	±0.2 ±.008
Min. 3mm .118 inch	±0.3 ±.012


# JE-X

## REFERENCE DATA


1. Max. switching power




2. Operate and release time



3. Coil temperature rise (at 30°C 86°F)



4. Coil temperature rise (Contact carrying current: 5 A)



## NOTE

Soldering should be carried out within 3 s to 350°C 662°F or within 5 s at 250°C 482°F.