

Super Low Distortion Multilayer Ceramic Capacitors (CFCAP(TM))

LMK212SD473KD-T



■ Features

- Item Summary
10V, 0.047 μ F, \pm 10%, 0805
- Lifecycle Stage
Mass Production
- Standard packaging quantity (minimum)
Taping paper 4000pcs

■ Products characteristics table

CaseSize (EIA/JIS)	0805/2012
Rated Voltage (max)	10V
Capacitance	0.047 μ F
Capacitance Tolerance	\pm 10%
Resistance	10,000 M Ω min.
Dielectric Loss Tangent	0.1%MAX
Temperature Range (EIA/JIS)	-55 to +125 $^{\circ}$ C/-55 to +125 $^{\circ}$ C
RoHS Compliance	Yes
Halogen Free	Yes
Soldering Method	Reflow

■ External Dimensions

L	2.0mm \pm 0.10
W	1.25mm \pm 0.10
T	0.85mm \pm 0.10
e	0.5mm \pm 0.25

2015.01.05

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.
 TAIYO YUDEN reserves the right to make change to the Date at any time without notice.
 Before making final selection, please check product specification.

Multi Layer Ceramic Capacitor






TAIYO YUDEN

-Electrical Characteristics Data- Jun-2011

RoHS compliance product

○ LMK212SD473KD

10V 2012 0.047uF +/-10% t=0.95mmMAX
10V 0805 0.047uF +/-10% t=0.037inchMAX



部品特性は設置環境、測定条件等により変化する場合があります。本データをご使用される際は実際の製品特性に対する参考データとしてご活用ください。また、本データは予告無く追加・削除及び変更を行う場合があります。ご注文の際は、納入仕様書のご確認をお願いします。

The data is reference only. Electrical characteristics vary depending on environment or measurement condition.

TAIYO YUDEN reserves the right to make change to the Date at any time without notice.

Before making final selection, please check product specification