

SINGLE AND DUAL TVS FOR ESD / TRANSIENT PROTECTION


This Single and Dual Transient Protector has been designed to protect Sensitive Equipment against ESD and prevent Latch-Up events. The single unidirectional and the dual used as bi-directional devices protect up to two data lines in a single package giving the advantage of board space savings where this is a premium.

SPECIFICATION FEATURES

- Working Peak Reverse Voltage Range - 5V to 36V
- Maximum Leakage Current of 5µA
- IEC61000-4-2 Compliance 15kV Air, 8kV Contact Discharge
- Industry Standard SOT23 Package
- 100% Tin Matte Finish (RoHS Compliant)

APPLICATIONS

- Data Transmission Line Ports
- Computer Monitor Interface Port Protection
- Portable Consumer Electronics
- Instrumentation Equipment



MAXIMUM RATINGS

Rating	Symbol	Value	Units
Peak Pulse Power 8/20µs Waveform	P_{pp}	500	W
ESD Voltage (HBM)	V_{ESD}	>25	kV
Operating Temperature Range	T_J	-55 to +150	°C
Storage Temperature Range	T_{stg}	-55 to +150	°C
Lead Soldering Temperature (max. 10 s)	T_L	260	°C

ELECTRICAL CHARACTERISTICS $T_j = 25^\circ\text{C}$

PJSOT05, PJSOT05C (Bi-directional)

Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	V_{WRM}				5	V
Reverse Breakdown Voltage	V_{BR}	$I_{BR} = 1\text{mA}$	6			V
Reverse Leakage Current	I_R	$V_R = 5\text{V}$			5	µA
Clamping Voltage (8/20µs)	V_C	$I_{pp} = 20\text{A}$			10	V
Maximum Peak Pulse Current	I_{pp}	8/20 µs Waveform			30	A
Off State Capacitance (Unidirectional)	C_j	0 Vdc Bias f = 1MHz			550	pF
Off State Capacitance (Bi-directional)	C_j	0 Vdc Bias f = 1MHz between pin 1 and 2			220	pF

ELECTRICAL CHARACTERISTICS $T_j = 25^\circ\text{C}$
PJSOT12, PJSOT12C (Bi-directional)

Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	V_{WRM}				12	V
Reverse Breakdown Voltage	V_{BR}	$I_{BR} = 1\text{mA}$	13.3			V
Reverse Leakage Current	I_R	$V_R = 12\text{V}$			5	μA
Clamping Voltage (8/20 μs)	V_C	$I_{pp} = 20\text{A}$			25	V
Maximum Peak Pulse Current	I_{pp}	8/20 μs Waveform			24	A
Off State Capacitance (Unidirectional)	C_j	0 Vdc Bias $f = 1\text{MHz}$			200	pF
Off State Capacitance (Bi-directional)	C_j	0 Vdc Bias $f = 1\text{MHz}$ between pin 1 and 2			100	pF

PJSOT15, PJSOT15C (Bi-directional)

Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	V_{WRM}				15	V
Reverse Breakdown Voltage	V_{BR}	$I_{BR} = 1\text{mA}$	16.7			V
Reverse Leakage Current	I_R	$V_R = 15\text{V}$			5	μA
Clamping Voltage (8/20 μs)	V_C	$I_{pp} = 20\text{A}$			30	V
Maximum Peak Pulse Current	I_{pp}	8/20 μs Waveform			20	A
Off State Capacitance (Unidirectional)	C_j	0 Vdc Bias $f = 1\text{MHz}$			170	pF
Off State Capacitance (Bi-directional)	C_j	0 Vdc Bias $f = 1\text{MHz}$ between pin 1 and 2			90	pF

PJSOT24, PJSOT24C (Bi-directional)



Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	V_{WRM}				24	V
Reverse Breakdown Voltage	V_{BR}	$I_{BR} = 1\text{mA}$	26.7			V
Reverse Leakage Current	I_R	$V_R = 24\text{V}$			5	μA
Clamping Voltage (8/20 μs)	V_C	$I_{pp} = 15\text{A}$			45	V
Maximum Peak Pulse Current	I_{pp}	8/20 μs Waveform			18	A
Off State Capacitance (Unidirectional)	C_j	0 Vdc Bias $f = 1\text{MHz}$			150	pF
Off State Capacitance (Bi-directional)	C_j	0 Vdc Bias $f = 1\text{MHz}$ between pin 1 and 2			80	pF



ELECTRICAL CHARACTERISTICS $T_j = 25^\circ\text{C}$

PJSOT36, PJSOT36C (Bi-directional)

Parameter	Symbol	Conditions	Min	Typical	Max	Units
Reverse Stand-Off Voltage	V_{WRM}				36	V
Reverse Breakdown Voltage	V_{BR}	$I_{BR} = 1\text{mA}$	40			V
Reverse Leakage Current	I_R	$V_R = 36\text{V}$				
Clamping Voltage (8/20 μs)	V_C	$I_{pp} = 7\text{A}$			72	V
Maximum Peak Pulse Current	I_{pp}	8/20 μs Waveform			9	A
Off State Capacitance (Unidirectional)	C_j	0 Vdc Bias $f = 1\text{MHz}$			80	
Off State Capacitance (Bi-directional)	C_j	0 Vdc Bias $f = 1\text{MHz}$ between pin 1 and 2			45	pF

www.DataSheet4U.com



PACKAGE AND SUGGESTED PAD LAYOUT


TVS	Marking Code
PJSOT05	2A
PJSOT12	4A
PJSOT15	5A
PJSOT24	6A
PJSOT36	SA
PJSOT05C	2AC
PJSOT12C	4AC
PJSOT15C	5AC
PJSOT24C	6AC
PJSOT36C	SAC

© Copyright PanJit International, Inc 2006

The information presented in this document is believed to be accurate and reliable. The specifications and information herein are subject to change without notice. Pan Jit makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. Pan Jit products are not authorized for use in life support devices or systems. Pan Jit does not convey any license under its patent rights or rights of others.