

High Intensity SMD LED


Description

This device have been designed to meet the increasing demand for white SMD LED.

The package of the TLMW3146 is the PLCC-2 (equivalent to a size B tantalum capacitor).

It consists of a lead frame which is embedded in a white thermoplast. The reflector inside this package is filled with a mixture of epoxy and TAG phosphor.

The TAG phosphor converts the blue emission partially to yellow, which mixes with the remaining blue to give white.



Features

- High efficient InGaN technology
- Chromaticity Coordinate categorized according to CIE1931 per packing unit
- Luminous intensity ratio in one packing unit $I_{Vmax}/I_{Vmin} \leq 1.75$
- Typical color temperature 5500 K
- ESD class 1
- EIA and ICE standard package
- Compatible with infrared, vapor phase and wave solder processes according to CECC
- Available in 8 mm tape reel
- Lead-free device

Applications

- Automotive: Backlighting in dashboards and switches
- Telecommunication: Indicator and backlighting in telephone and fax
- Backlighting for audio and video equipment
- Backlighting in office equipment
- Indoor and outdoor message boards
- Flat backlight for LCDs, switches and symbols
- Illumination purposes, alternative to incandescent lamps
- General use

Parts Table

Part	Color, Luminous Intensity	Angle of Half Intensity ($\pm\phi$)	Technology
TLMW3146	White, $I_V = 65$ mcd (typ.)	60 °	InGaN / TAG on SiC

Absolute Maximum Ratings

$T_{amb} = 25$ °C, unless otherwise specified

TLMW3146

Parameter	Test condition	Symbol	Value	Unit
Reverse voltage		V_R	5	V
DC Forward current	$T_{amb} \leq 70$ °C	I_F	20	mA
Surge forward current	$t_p \leq 10$ µs	I_{FSM}	0.1	A
Power dissipation	$T_{amb} \leq 70$ °C	P_V	85	mW
Junction temperature		T_j	100	°C
Operating temperature range		T_{amb}	- 40 to + 100	°C

Parameter	Test condition	Symbol	Value	Unit
Storage temperature range		T_{stg}	- 40 to + 100	°C
Soldering temperature	$t \leq 5$ s	T_{sd}	260	°C
Thermal resistance junction/ambient	mounted on PC board (pad size > 16 mm ²)	R_{thJA}	350	K/W

Optical and Electrical Characteristics

$T_{amb} = 25$ °C, unless otherwise specified

White

TLMW3146

Parameter	Test condition	Part	Symbol	Min	Typ.	Max	Unit
Luminous intensity	$I_F = 10$ mA	TLMW3146	I_V	40	65	100	mcd
Chromaticity coordinate x acc. to CIE 1931	$I_F = 10$ mA	TLMW3146	x	0.315		0.365	
Chromaticity coordinate y acc. to CIE 1931	$I_F = 10$ mA	TLMW3146	y	0.290		0.440	
Angle of half intensity	$I_F = 10$ mA		ϕ		± 60		deg
Forward voltage	$I_F = 10$ mA		V_F		3.5	4.0	V
Reverse voltage	$I_R = 10$ µA		V_R	5			V
Temperature coefficient of V_F	$I_F = 20$ mA		TC_{VF}		- 4		mV/K
Temperature coefficient of I_V	$I_F = 20$ mA		TC_{IV}		- 0.5		% / K


Chromaticity Coordinate Classification

Group	X		Y	
	min	max	min	max
4a	0.3150	0.3275	$Y = 1.4 x - 0.111$	$Y = 1.4 x - 0.071$
4b	0.3275	0.3400	$Y = 1.4 x - 0.111$	$Y = 1.4 x - 0.151$
4c	0.3150	0.3275	$Y = 1.4 x - 0.151$	$Y = 1.4 x - 0.111$
4d	0.3275	0.3400	$Y = 1.4 x - 0.151$	$Y = 1.4 x - 0.111$
5a	0.3400	0.3525	$Y = 1.4 x - 0.111$	$Y = 1.4 x - 0.071$
5b	0.3525	0.3650	$Y = 1.4 x - 0.111$	$Y = 1.4 x - 0.071$
5c	0.3400	0.3525	$Y = 1.4 x - 0.151$	$Y = 1.4 x - 0.111$
5d	0.3525	0.3650	$Y = 1.4 x - 0.151$	$Y = 1.4 x - 0.111$


Luminous Intensity Classification

Group	Luminous Intensity (mcd)	
	min	max
UC1	40	60
UC2	50	70
UD1	58	85
UD2	70	100


tolerance ± 0.005

Typical Characteristics ($T_{amb} = 25 \text{ }^{\circ}\text{C}$ unless otherwise specified)



16191

 T_{amb} - Ambient Temperature (°C)


16194

 I_F - Forward Current (mA)


16192

 T_{amb} - Ambient Temperature (°C)

16195

 V_F - Forward Voltage (V)

16193


 T_{amb} - Ambient Temperature (°C)

16196

 λ - Wavelength (nm)


TLMW3146

Vishay Semiconductors




16197 T_{amb} - Ambient Temperature (°C)

Figure 7. Rel. Luminous Intensity vs. Ambient Temperature




95 10319

Figure 10. Rel. Luminous Intensity vs. Angular Displacement




16198 I_F - Forward Current (mA)

Figure 8. Chromaticity Coordinate Shift vs. Forward Current






16930 Coordinates of Colorgroups

Figure 11. Coordinates of Colorgroups



16199 T_{amb} - Ambient Temperature (°C)

Figure 9. Forward Voltage vs. Ambient Temperature

Package Dimensions in mm

Mounting Pad Layout


Dimensions: IR and Vaporphase
(Wave Soldering)

Drawing-No. : 6.541-5025.01-4
Issue: 7; 05.04.04

95 11314

Ozone Depleting Substances Policy Statement

It is the policy of **Vishay Semiconductor GmbH** to

1. Meet all present and future national and international statutory requirements.
2. Regularly and continuously improve the performance of our products, processes, distribution and operating systems with respect to their impact on the health and safety of our employees and the public, as well as their impact on the environment.

It is particular concern to control or eliminate releases of those substances into the atmosphere which are known as ozone depleting substances (ODSs).

The Montreal Protocol (1987) and its London Amendments (1990) intend to severely restrict the use of ODSs and forbid their use within the next ten years. Various national and international initiatives are pressing for an earlier ban on these substances.

Vishay Semiconductor GmbH has been able to use its policy of continuous improvements to eliminate the use of ODSs listed in the following documents.

1. Annex A, B and list of transitional substances of the Montreal Protocol and the London Amendments respectively
2. Class I and II ozone depleting substances in the Clean Air Act Amendments of 1990 by the Environmental Protection Agency (EPA) in the USA
3. Council Decision 88/540/EEC and 91/690/EEC Annex A, B and C (transitional substances) respectively.

Vishay Semiconductor GmbH can certify that our semiconductors are not manufactured with ozone depleting substances and do not contain such substances.

**We reserve the right to make changes to improve technical design
and may do so without further notice.**

Parameters can vary in different applications. All operating parameters must be validated for each customer application by the customer. Should the buyer use Vishay Semiconductors products for any unintended or unauthorized application, the buyer shall indemnify Vishay Semiconductors against all claims, costs, damages, and expenses, arising out of, directly or indirectly, any claim of personal damage, injury or death associated with such unintended or unauthorized use.

Vishay Semiconductor GmbH, P.O.B. 3535, D-74025 Heilbronn, Germany
Telephone: 49 (0)7131 67 2831, Fax number: 49 (0)7131 67 2423