

FEATURES

- High Efficiency & Long Life
- Wide Input Range for Worldwide use (up to 305Vac)
- Compact Size
- Optimized Performance
- Fully Isolated & SELV
- Protections: Short Circuit/ Open Circuit/ Over Voltage/ Over Temperature
- Class 2 power unit



PRODUCT HIGHLIGHT

Output Voltage/Current 40W/700mA

:

Dimming: 1-10V / PWM

SPECIFICATION

Model Name	FSP40-ZZAP(070)MG	
Wattage	40W	
Case	Plastic	
IP Level	IP65	
Dimming	1-10V / PWM Dimming	
Input Electrical Specification	Input Voltage	120~277 Vac
	Input Frequency	47~63 Hz
	PFC	≥0.9
	Inrush Current	<5A/5mS @ Cold start, 240Vac, Full load
Constant Current / Constant Voltage	Constant Current	
Output Voltage and Current Rating	Output1	52-58 V , 700 mA
Output Electrical Specification	Efficiency	≥ 88 %
	Life	50.000 hours without system at full load and ambient <30°C @120Vac /240Vac
	Protection Function	OVP,OTP,SCP
Environmental Requirement	TEMP. Range	Operating : -20°C to +50°C Storage : -20°C to +85°C
	Insulation	Primary to Secondary: 500Vdc,25M ohms min.
EMC performance	EN55015	Class B Conducted, Class B radiated
	EN55022	Class B Conducted, Class B radiated
	EN61000-3-2	B
	EN61000-4-3	1
	EN61000-4-5	Surge: ±2 KV common mode ± 1KV differential
Dimension	162.5mm(L) x 43mm(W)x 32mm(H)	

PROTECTION FUNCTIONS

OVP,OTP,SCP

This content is subject to change, please refer to specification for more detail.
FSP reserve the right to change the content without prior notice