

LFV310-XXNAVTNCX LFV300

SICK Sensor Intelligence.

LEVEL SENSORS

LFV310-XXNAVTNCX | LFV300

LEVEL SENSORS



Ordering information

Туре	Part no.
LFV310-XXNAVTNCX	6039843

Other models and accessories → www.sick.com/LFV300



Detailed technical data

Features

Medium	Fluids
Measurement	Switch
Probe length	66 mm
Process pressure	-1 bar 64 bar
Process temperature	-50 °C +250 °C
Fill material density	0.5 g/cm ³ 2.5 g/cm ³
GOST approval	✓

Performance

Accuracy of sensor element	± 2 mm
Repeatability	≤ 1 mm
Viscosity	0.1 mPas 10,000 mPas
Response time	500 ms

Electronics

Power consumption	< 4.2 mA
Initialization time	<3s
VDE protection class 1	✓
Electrical connection	1⁄2" NPT
Supply voltage	Non-contact switch: 20 V AC/DC 253 V AC/DC
Hysteresis	2 mm
Output current	< 400 mA
Inductive load	1H
Capacitive load	100 nF
Enclosure rating	IP 66 / IP 67
Temperature drift	0,03 mm/K

Mechanics

SICK AT A GLANCE

SICK is one of the leading manufacturers of intelligent sensors and sensor solutions for industrial applications. A unique range of products and services creates the perfect basis for controlling processes securely and efficiently, protecting individuals from accidents and preventing damage to the environment.

We have extensive experience in a wide range of industries and understand their processes and requirements. With intelligent sensors, we can deliver exactly what our customers need. In application centers in Europe, Asia and North America, system solutions are tested and optimized in accordance with customer specifications. All this makes us a reliable supplier and development partner.

Comprehensive services complete our offering: SICK LifeTime Services provide support throughout the machine life cycle and ensure safety and productivity.

For us, that is "Sensor Intelligence."

WORLDWIDE PRESENCE:

Contacts and other locations -www.sick.com

