



DUAL POWER MOSFET (N-CHANNEL/P-CHANNEL)

DESCRIPTION

The UTC **UTT30NP30** is a dual power MOSFET. it uses UTC's advanced technology to provide customers with a minimum on-state resistance, low capacitance and low gate charge, etc.

The UTC **UTT30NP30** is suitable for CPU Power Delivery and DC-DC Converters, etc.

FEATURES

* N-Channel: 30A, 20V

$R_{DS(on)} < 15m\Omega @ V_{GS}=10V, I_D=30A$


$R_{DS(on)} < 18m\Omega @ V_{GS}=4.5V, I_D=30A$

P-Channel: -30A, -25V


$R_{DS(on)} < 25m\Omega @ V_{GS}= -10V, I_D= -30A$

$R_{DS(on)} < 24m\Omega @ V_{GS}= -4.5V, I_D= -30A$

* Low capacitance



SYMBOL




ORDERING INFORMATION

| Ordering Number | | Package | Pin Assignment | | | | | Packing |
|------------------|------------------|----------|----------------|----|---|----|----|-----------|
| Lead Free | Halogen Free | | 1 | 2 | 3 | 4 | 5 | |
| UTT30NP30L-TN4-R | UTT30NP30G-TN4-R | TO-252-4 | S1 | G1 | D | S2 | G2 | Tape Reel |

Note: Pin Assignment: G: Gate D: Drain S: Source

| | |
|---|--|
| UTT30NP30L-TN4-T <ul style="list-style-type: none"> (1) Packing Type (2) Package Type (3) Green Package | <ul style="list-style-type: none"> (1) R: Tape Reel (2) TN4: TO-252-4 (3) L: Lead Free, G: Halogen Free and Lead Free |
|---|--|

MARKING



■ ABSOLUTE MAXIMUM RATINGS (T_J=25°C, unless otherwise specified)

| PARAMETER | SYMBOL | RATINGS | | UNIT | |
|---------------------------|---------------------------------|-----------------|-----------|------|---|
| | | N-CHANNEL | P-CHANNEL | | |
| Drain-Source Voltage | V _{DSS} | 20 | -25 | V | |
| Gate-Source Voltage | V _{GSS} | ±8 | ±20 | V | |
| Drain Current | Continuous T _A =25°C | I _D | 30 | -30 | A |
| | Pulsed (Note) | I _{DM} | 120 | -120 | A |
| Power Dissipation | P _D | 3.1 | | W | |
| Junction Temperature | T _J | -55~+150 | | °C | |
| Storage Temperature Range | T _{STG} | -55~+150 | | °C | |

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged. Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

| PARAMETER | SYMBOL | RATINGS | UNIT |
|---------------------|-----------------|---------|------|
| Junction to Ambient | θ _{JA} | 40 | °C/W |

■ ELECTRICAL CHARACTERISTICS(T_J=25°C unless otherwise noted)

N-channel

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--|---------------------|--|-----|------|------|------|
| OFF CHARACTERISTICS | | | | | | |
| Drain-Source Breakdown Voltage | BV _{DSS} | V _{GS} =0V, I _D =250μA | 20 | | | V |
| Drain-Source Leakage Current | I _{DSS} | V _{DS} =20V, V _{GS} =0V, T _J =25°C | | | 1.0 | μA |
| Gate-Source Leakage Current | I _{GSS} | Forward V _{GS} =+8V, V _{GS} =0V | | | +100 | nA |
| | | Reverse V _{GS} =-8V, V _{GS} =0V | | | -100 | nA |
| ON CHARACTERISTICS | | | | | | |
| Gate Threshold Voltage | V _{GS(TH)} | V _{DS} =V _{GS} , I _D =250μA | 0.5 | | 1.2 | V |
| Static Drain-Source On-State Resistance (Note 2) | R _{DS(ON)} | V _{GS} =10V, I _D =30A | | | 15 | mΩ |
| | | V _{GS} =4.5V, I _D =30A | | | 18 | mΩ |
| DYNAMIC PARAMETERS | | | | | | |
| Input Capacitance | C _{ISS} | V _{GS} =0V, V _{DS} =20V, f=1.0MHz | | 1500 | | pF |
| Output Capacitance | C _{OSS} | | | 260 | | pF |
| Reverse Transfer Capacitance | C _{RSS} | | | 260 | | pF |
| SWITCHING PARAMETERS | | | | | | |
| Total Gate Charge (Note 2) | Q _G | V _{GS} =10V, V _{DS} =16V, I _D =30A | | 160 | 170 | nC |
| Gate to Source Charge | Q _{GS} | | | 5.5 | | nC |
| Gate to Drain Charge | Q _{GD} | | | 10.5 | | nC |
| Turn-ON Delay Time (Note 2) | t _{D(ON)} | V _{DS} =10V, I _D =1A V _{GS} =10V, R _G =3.3Ω | | 31 | 38 | nS |
| Rise Time | t _R | | | 57 | 62 | nS |
| Turn-OFF Delay Time | t _{D(OFF)} | | | 458 | 510 | nS |
| Fall-Time | t _F | | | 234 | 270 | nS |
| SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS | | | | | | |
| Drain-Source Diode Forward Voltage(Note 2) | V _{SD} | I _{SD} =30A | | 0.9 | 1.25 | V |

■ ELECTRICAL CHARACTERISTICS(Cont.)

P-Channel

| PARAMETER | SYMBOL | TEST CONDITIONS | MIN | TYP | MAX | UNIT |
|--|--------------|--|-----|------|------|------------|
| OFF CHARACTERISTICS | | | | | | |
| Drain-Source Breakdown Voltage | BV_{DSS} | $V_{GS}=0V, I_D=-250\mu A$ | -25 | | | V |
| Drain-Source Leakage Current | I_{DSS} | $V_{DS}=-24V, V_{GS}=0V, T_J=25^\circ C$ | | | -1.0 | μA |
| Gate-Source Leakage Current | Forward | I_{GSS} | | | +100 | nA |
| | Reverse | | | | -100 | nA |
| ON CHARACTERISTICS | | | | | | |
| Gate Threshold Voltage | $V_{GS(TH)}$ | $V_{DS}=V_{GS}, I_D=-250\mu A$ | -1 | -1.5 | -3 | V |
| Static Drain-Source On-State Resistance (Note 2) | $R_{DS(ON)}$ | $V_{GS}=-10V, I_D=-30A$ | | | 25 | m Ω |
| | | $V_{GS}=-4.5V, I_D=-30A$ | | | 34 | m Ω |
| DYNAMIC PARAMETERS | | | | | | |
| Input Capacitance | C_{ISS} | $V_{GS}=0V, V_{DS}=-15V, f=1.0MHz$ | | 1500 | | pF |
| Output Capacitance | C_{OSS} | | | 270 | | pF |
| Reverse Transfer Capacitance | C_{RSS} | | | 230 | | pF |
| SWITCHING PARAMETERS | | | | | | |
| Total Gate Charge (Note 2) | Q_G | $V_{GS}=-10V, V_{DS}=-20V, I_D=-30A$ | | 140 | 160 | nC |
| Gate to Source Charge | Q_{GS} | | | 5.4 | | nC |
| Gate to Drain Charge | Q_{GD} | | | 8.7 | | nC |
| Turn-ON Delay Time (Note 2) | $t_{D(ON)}$ | $V_{DS}=-12.5V, I_D=-1A$ $V_{GS}=-10V, R_G=3.3\Omega$ | | 34 | 42 | nS |
| Rise Time | t_R | | | 42 | 48 | nS |
| Turn-OFF Delay Time | $t_{D(OFF)}$ | | | 308 | 330 | nS |
| Fall-Time | t_F | | | 173 | 220 | nS |
| SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS | | | | | | |
| Drain-Source Diode Forward Voltage(Note 2) | V_{SD} | $I_S=-30A$ | | | -1.2 | V |

Notes: 1. Pulse Test: Pulse width limited by Max. junction temperature.

2. N-CH, P-CH are same, mounted on 2oz FR4 board $t \leq 10s$.

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. The information presented in this document does not form part of any quotation or contract, is believed to be accurate and reliable and may be changed without notice.