SPOS QWERTY KEYBOARDS

Small-sized Multifunctional Keyboard with Enhanced 135/123 Position Key Layout and Optional Magnetic Card Reader and Touchpad





Facts & Features (continued)

- Easy configuration file transfer with Window Explorer
- Comprehensive UPOS support for Windows and Linux Client-Server architectures
- Remote network installation with CHERRY Tools Activator
- Touchpad version reducing desktop footprint while ensuring easy cursor navigation
- Yellow status LED's
- Accessory kit available to reconfigure key layout

Facts & Features

- Compact size keyboard with QWERTY layout
- Enhanced US 135/123 position key Layout
- Robust product design with IP 54 spill and dust resistant key field for harsh environments
- Plug & play configuration for all common POS fortures
- Unique function enhancement with 'CHERRY Tools' virtual programming
- Fully programmable keyboard with 54/60 relegendable keys for easy layout configuration and quick function calls
- Option for unlimited programmability of all keys up to 3 layers provides convenient data access
- 'Moving of Key' allows for easy key position exchange including modifier functions
- High performance 3-track magnetic stripe reader with freely programmable headers and terminators for each track
- Dual insertion for bi-directional swipe of magnetic stripe card
- Audible and visual indication of MSR good reads
- Flexible parsing and configuration of magnetic stripe data including start/stop sentinels
- Powerful 'CHERRY Tools' configuration software allows for quick product set up and configuration

Technical Data

Current Input

Typ. 35 mA

Magnetic Stripe Reader

Standards:

ISO 7811/-12, AAMVA, JIS others on request PCI DSS 3.0 compliant

Durability: 1 million cycles

Reading Speed 3-125 inch/s at 75 Bit/inch 3-50 inch/s at 210 Bit/inch

Data is decoded to keyboard scancodes

Touchpad

Resolution: 1000 dpi 2 switch-activated mouse buttons

Cable Length

approx. 1.85 m approx. 6 ft

Key Layout

Compact size 135 / 123 position US key layout including Windows keys

Weight (without/with packaging)

Approx. 1.4 kg / 1.6 kg (without packaging) Approx. 3.08 lbs / 3.53 lbs (with packaging)

Dimensions

 Keyboard:
 360 x 198 x 38 mm

 Keyboard:
 14.17 x 7.79 x 1.49 inches

 Packaging:
 415 x 260 x 50 mm

 Packaging:
 16.34 x 10.24 x 1.97 inches



Technical Data (Continued)

Interface USB 2.0

Packaging Unit

22 keyboards per master carton 8 master cartons per pallet

Keyswitch Lifetime

25 million operations

Operating Temperature

0°C to 50°C

Storage Temperature

-20°C to 60°C

Agency Approvals / Instructions

CE, cURus, FCC Class B, VCCI, C-Tick, GOST-R, WHQL, RoHS, BSMI

Available Software

CHERRY Tools MS Windows ™ XP, Windows 7, 8.1, & 10

CHERRY Tools Runtime
MS Windows™ XP, Windows 7, 8.1, & 10

OPOS Local Edition
MS Windows™ XP, Windows 7, 8.1, & 10

OPOS Client/Server Edition
MS Windows™ XP, Windows 7, 8.1, & 10

JPOS Local Edition
MS Windows™ XP, Windows 7, 8.1, & 10
Suse Linus V8.1-9.0 / Kernel 2.4
Suse Linus V9.1 / Kernel 2.6

JPOS Client/Server Edition
MS Windows™ XP, Windows 7, 8.1, & 10
Suse Linus V8.1-9.0 / Kernel 2.4
Suse Linus V9.1 / Kernel 2.6

• Delivery Volume

Keyboard, Quick Guide, Keycap Puller, Keyboard Feet

3 Year Warranty

Order Description

Integration Level	Order Number	Interface	Color	Keys	Options
High Integration	G86-61411EUAEAA	USB	Lt. Gray	123	Touch Pad, MSR
High Integration	G86-61411EUADAA	USB	Black	123	Touch Pad, MSR
Moderate Integration	G86-61410EUAEAA	USB	Lt. Gray	135	MSR
Moderate Integration	G86-61410EUADAA	USB	Black	135	MSR
Moderate Integration	G86-61401EUADAA	USB	Black	123	Touch Pad
Minimum Integration	G86-61400EUADAA	USB	Black	135	

Available in various country versions upon request.



Cherry Americas, LLC 11200 88th Avenue Pleasant Prairie, WI 53158

USA Phone:

262.942.6508

Internet: www.cherryamericas.com

E-Mail: <u>keyboardsupport@cherryamericas.com</u>

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2017 Cherry Americas, LLC, Rev Date: January 27, 2017