

FEATURES:

- Designed for long haul Gigabit Ethernet 100/1000 Base-T, full duplex applications
- Supports 4 pairs of category 5 UTP cable
- Recognized By UL 60950-1
- Cable interface for isolation and low common mode emissions
- Meets all IEEE 802.3 and ANSI X3.236 standards including 350uH OCL with 8mA bias

YUAN DEAN SCIENTIFIC



LAN Filters


30F-3X/5X SERIES

10/100/1000 Base-T

PC Card

LAN Magnetics Modules

24PIN PCMCIA



ELECTRICAL SPECIFICATIONS@25°C-Operating temperature 0°C TO 70°C



Part Number	Insertion Loss (dB MAX)	Return Loss (dB min @100 Ω)					Differential to Common Mode (dB min)			Cross talk (dB min)			Hipot (V _{rms} min)
		1-30 MHz	40 MHz	50 MHz	60-80 MHz	100 MHz	30 MHz	60 MHz	100 MHz	30 MHz	60 MHz	100 MHz	
30F-30NL	-1.0	-18	-14.4	-13.1	-12	-10	-43	-37	-33	-45	-40	-35	1500
30F-50NL	-1.0	-18	-14.4	-13.1	-12	-10	-43	-37	-33	-45	-40	-35	1500



Markings and Dimensions

30F-30

30F-50



Unit: mm Unless otherwise specified, all tolerances are ± 0.25

Schematics

30F-30,30F-50

