

Ultra fast Rectifier


YG902C2

FEATURES

- With TO-220F packaging
- High junction temperature capability
- Low forward voltage, high current capability
- High current capability
- Low power loss, high efficiency
- Minimum Lot-to-Lot variations for robust device performance and reliable operation


APPLICATIONS

- Switching power supply
- Free-Wheeling diodes
- Reverse battery protection
- Center tap configuration



ABSOLUTE MAXIMUM RATINGS(T<sub>a</sub>=25°C)

SYMBOL	PARAMETER	VALUE	UNIT
V <sub>RRM</sub> V <sub>RMS</sub> V <sub>R</sub>	Peak Repetitive Reverse Voltage RMS Voltage DC Blocking Voltage	200	V
I <sub>F(AV)</sub>	Average Rectified Forward Current @T <sub>c</sub> =110°C	10	A
I <sub>FSM</sub>	Nonrepetitive Peak Surge Current (10ms single half sine-wave superimposed on rated load conditions)	500	A
T <sub>J</sub>	Junction Temperature	-40~150	°C
T <sub>stg</sub>	Storage Temperature Range	-40~150	°C



## Ultra fast Rectifier

YG902C2

## THERMAL CHARACTERISTICS

SYMBOL	PARAMETER	MAX	UNIT
$R_{th\ j-c}$	Thermal Resistance, Junction to Case	3.5	$^{\circ}C/W$

ELECTRICAL CHARACTERISTICS (Pulse Test: Pulse Width=300  $\mu$  s, Duty Cycle  $\leq$  1%)

SYMBOL	PARAMETER	CONDITIONS	MAX	UNIT
$V_F$	Maximum Instantaneous Forward Voltage	$I_F=5A; T_c=25^{\circ}C$	0.95	V
$I_R$	Maximum Instantaneous Reverse Current	$V_R=$ rated $V_{RRM}; T_c=25^{\circ}C$	100	$\mu$ A
$t_{rr}$	Maximum Reverse Recovery Time	$I_F=0.1A; I_R=0.2A, I_{rec}=0.05A$	35	ns